Coaxial **Matching Pad**

50/75Ω

В

MAX 4

(Ó)

Maximum Ratings

| Operating Temperature | -55°C to 100°C |
|-----------------------------------|-------------------------------|
| Storage Temperature | -55°C to 100°C |
| RF Input Power | 0.25W |
| Permanent damage may occur if any | of these limits are exceeded. |

Outline Drawing

BNC FEMALE CONN

D±.05

В

.62 15.75 49.28

Outline Dimensions (inch mm)

1.94 grams

wt

30.0

D

BNC MALE

CONN

DC to 2000 MHz

Features

- excellent VSWR 1.15: typ.
- excellent flatness
- wideband coverage, DC to 2000 MHz

Applications

impedance matching

BMP-5075R+



CASE STYLE: FF747

Connectors Model 75ΩF-BNC BMP-5075R+ 50ΩM-BNC

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Electrical Specifications


| FREQ. (MHz) | ATTENUATION (dB) Flatness Max. | | | VSWR (:1) Max. | | | POWER (W) | |
|--------------------------------|--------------------------------------|---------------|-----------------|----------------------|---------------|-----------------|------------------|------|
| f _L -f _U | Nom. | DC-100 MHz | 100-1000 MHz | 1000-2000 MHz | DC-100 MHz | 100-1000 MHz | 1000-2000 MHz | |
| DC-2000 | 5.7±0.1 | 0.2 | 0.3 | 0.4 | 1.06 | 1.22 | 1.4 | 0.25 |

Typical Performance Data

| Frequency (MHz) | Attenuation (dB) | VSWR (:1) | | |
|--------------------|---------------------|-------------|-------------|--|
| | () | 50 Ω | 75 Ω | |
| 10.00 | 5.71 | 1.01 | 1.00 | |
| 20.00 | 5.71 | 1.01 | 1.00 | |
| 60.00 | 5.71 | 1.01 | 1.00 | |
| 100.00 | 5.72 | 1.01 | 1.00 | |
| 110.00 | 5.71 | 1.01 | 1.01 | |
| 555.00 | 5.71 | 1.13 | 1.04 | |
| 1000.00 | 5.74 | 1.07 | 1.12 | |
| 1010.00 | 5.74 | 1.07 | 1.12 | |
| 1505.00 | 5.74 | 1.03 | 1.09 | |
| 2000.00 | 5.61 | 1.04 | 1.25 | |

Electrical Schematic R1 \sim 50 OHMS MALE 75 OHMS FEMALE R2 ≥ 0





A Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Min-Circuit's applicable established test performance criteria and measurement instructions. C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp



Mini-Circuits

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mini-Circuits: BMP-5075R+