MMIC Surface Mount Power Splitter/Combiner

2 Way-90° 50Ω

6000 to 14000 MHz

The Big Deal

- Wideband (6-14 GHz)
- Good Isolation and Return Loss
- Highly repeatable performance (GaAs based design)
- No external termination required
- High power handling (>30dBm)
- Small Size MCLP 4x4mm



EPQ-133+

CASE STYLE: DG1847

Product Overview

Mini-Circuits' EPQ-133+ is a wideband 6-14 GHz, 90° hybrid. It splits an input signal into two output signals with quadrature phase shift between them. It provides low loss, wideband in a small layout size and handles high power with good VSWR.

Key Features

Feature	Advantages
Small Size	The EPQ-133+ offers an industry leading combination of size, bandwidth and frequency. The small footprint (4mm x4 mm) allows for reduced parasitics in systems with improved performance and simplified layout.
Low Phase and Amplitude Unbalance	3.4 deg. and 0.5 dB unbalance make this 90° hybrid applicable for use in higher level integrated components such as image reject mixers, single sideband modulators, phase shifters, variable attenuators, and balance amplifiers.
High Power Handling	Capable of operating up to 32 dBm, MMIC structure of EPQ-133+ makes this 90° hybrid a robust, rugged product that can be used effectively in either the transmit or receive paths.

MMIC Surface Mount **Power Splitter/Combiner**

2 Way-90° 50Ω 6000 to 14000 MHz

Features

- Low insertion loss, 0.6 dB typ. at 8-10 GHz
- · Good isolation, 20 dB typ. at 8-10 GHz
- Miniature size, 4x4 mm
- High Power

Applications

- Balanced amplifiers
- Modulators
- Attenuator
- Point to Point
- Military

Electrical Specifications at 25°C

Parameter	Frequency (MHz)	Min.	Тур.	Max.	Unit	
Frequency Range		6000		14000	MHz	
	6000 - 8000	_	0.6	1.1		
Insertion Loss,	8000 - 10000	—	0.6	1.2	dD	
(Avg. of Mainline & Coupled) above 3dB	10000 - 12000	—	0.8	1.5	uв	
	12000 - 14000	—	1.0	2.0		
	6000 - 8000	16	20	—		
lociation	8000 - 10000	16	20	—	dD	
isolation	10000 - 12000	14	18	—	uв	
	12000 - 14000	13	16	—		
Amplitude Unholonge	6000 - 8000	—	0.5	1.7	dB	
	8000 - 10000	—	0.5	1.2		
Amplitude Oribalarice	10000 - 12000	—	0.6	1.2		
	12000 - 14000	—	0.4	1.6		
	6000 - 8000	—	2.9	5.7		
Phase Unbalance	8000 - 10000	—	3.4	7.0	Degree	
(Deviation from 90°)	10000 - 12000	—	4.1	8.8		
	12000 - 14000	—	4.4	—		
	6000 - 8000		1.2			
Input VSWP	8000 - 10000	8000 - 10000 1.2			.4	
	10000 - 12000		1.4		:1	
	12000 - 14000		1.6			
	6000 - 8000		1.2			
	8000 - 10000		1.1		:1	
	10000 - 12000		1.3			
	12000 - 14000		1.5			

Maximum Ratings

Parameter	Ratings		
Operating Temperature	-45°C to 85°C		
Storage Temperature	-65°C to 150°C		
Power Input (as a splitter)	32 dBm		
Internal Dissipation	30 dBm		

Permanent damage may occur if any of these limits are exceeded.

Pad Connections

Function	Pad Number
SUM PORT	1
PORT 1 (0°)	9
PORT 2 (+90°)	22
NC	2-8, 10-21,23,24

Simplified Electrical Schematic



* ESD rating Human body model (HBM): Class 1A(250 to <500 V) in accordance with ANSI/ESD 5.1-2007

> REV. A M164490 EPQ-133+ BS/CP/AM



EPQ-133+

Generic photo used for illustration purposes only CASE STYLE: DG1847

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications



EPQ-133+

Outline Drawing



PCB Land Pattern



Suggested Layout, Tolerance to be within $\pm .002$

Product Marking



Outline Dimensions (inch)

A	B	C	D	E	F	G	H	J
.157	.157	.039	.008	.104	.104	.009		.016
4.0	4.0	1.0	0.20	2.64	2.64	0.23		0.41
K	L	M	N	P	Q	R		wt
.020	.166	.166	.102	.012	.020	.102		grams
0.50	4 22	4 22	2 59	0.30	0.51	2.59		0.04

Demo Board MCL P/N: TB-961-133+ Suggested PCB Layout (PL-520)



NULES: 1. TRACE WIDTH AND GAP PARAMETERS ARE SHOWN FOR ROGERS R04350B WITH DIELECTRIC THICKNESS .010" ±001; COPFER: 1/2 02. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH AND GAP MAY NEED TO BE MODIFIED. 2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE. DENOTES PCB COPFER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER) SOLDER MASK OVER BARE COPPER)

DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Tape and Reel (F68)



DIRECTION OF FEED

Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches	Devices per Reel see note		
12	8	7	Small quantity standard	20 50 100 200 500	
		7	Standard	1000	
		13	Standard	2000 3000 4000	



i jpicari citorinance Bata									
Frequency (MHz)	Total Loss ¹ (dB)		Amplitude Isolatio Unbalance (dB) (dB)		Phase Unbalance (deg.)	VSWR (:1) S	VSWR (:1) 1	VSWR (:1) 2	
	S-1	S-2							
6000	4.03	2.93	1.10	19.91	88.38	1.25	1.17	1.21	
6500	3.81	3.15	0.66	19.89	88.23	1.25	1.14	1.24	
7000	3.63	3.33	0.30	20.08	88.18	1.24	1.10	1.24	
7500	3.48	3.48	0.00	20.36	88.16	1.22	1.08	1.21	
8000	3.35	3.61	0.26	20.66	88.13	1.18	1.06	1.18	
8500	3.26	3.72	0.46	20.85	88.11	1.15	1.04	1.13	
9000	3.19	3.81	0.61	20.74	88.15	1.15	1.03	1.11	
9500	3.16	3.88	0.73	20.23	88.12	1.19	1.05	1.12	
10000	3.16	3.94	0.78	19.44	87.94	1.24	1.10	1.15	
10500	3.21	3.99	0.78	18.55	87.71	1.32	1.14	1.19	
11000	3.32	4.03	0.71	17.64	87.42	1.41	1.16	1.26	
11500	3.48	4.07	0.58	16.84	87.22	1.49	1.14	1.36	
12000	3.68	4.08	0.39	16.27	87.20	1.56	1.07	1.46	
12500	3.90	4.05	0.15	16.02	87.34	1.63	1.05	1.55	
13000	4.10	3.98	0.12	16.06	87.64	1.69	1.16	1.57	
14000	4.48	3.68	0.80	17.04	88.29	1.68	1.40	1.45	

Typical Performance Data

1. Total Loss = Insertion Loss + 3dB splitter loss.









Additional Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mini-Circuits: EPQ-133+