SMA Fixed Attenuator

 50Ω

1W 1dB DC to 12000 MHz

Maximum Ratings

Operating Temperature -45°C to 100°C Storage Temperature -55°C to 100°C

Permanent damage may occur if any of these limits are exceeded

Features

- wideband coverage, DC to 12000 MHz
- 1 watt rating
- rugged unibody construction
- · off-the-shelf availability
- very low cost

Applications

- impedance matching
- · signal level adjustment



Generic photo used for illustration purposes only


CASE STYLE: FF704

Connectors Model SMA FW-1+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Outline Drawing



Outline Dimensions (inch)

В D Ε .410 1.43 .312 grams 10 41 36.32 7 92 10.0

Electrical Specifications at 25°C


Parameter	Condition (MHz)	Min.	Тур.	Max.	Unit
Frequency Range		DC	_	12000	MHz
Attenuation	10	_	1	_	
	DC - 3000	0.8	1.15	1.5	dB
	3000 - 8000	1.0	1.30	1.7	
	8000 - 12000	1.15	1.60	2.0	
VSWR	DC - 3000	_	1.05	1.20	
	3000 - 8000	_	1.15	1.35	:1
	8000 - 12000	_	1.35	_	
Input Power	DC - 12000	_	_	1.0	W


1. Flatness = variation over band divided by 2.


Typical Performance Data

Frequency (MHz)	Attenuation (dB)	VSWR (:1)
10.00	1.03	1.00
100.00	1.04	1.01
2000.00	1.18	1.04
3000.00	1.22	1.02
6000.00	1.34	1.14
8000.00	1.42	1.18
10000.00	1.59	1.33
11000.00	1.56	1.34
11500.00	1.55	1.34
12000.00	1.64	1.35
15000.00	1.51	1.04

Electrical Schematic







A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively. "Standard Terms"): Purchasers of this part. Ferrormance and updany authorities and contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 $\frac{\text{Mini-Circuits}}{\text{FW-1+}}$