
Coaxial **SMA Fixed Attenuator**

50Ω **1W** 7dB DC to 12000 MHz

Maximum Ratings

Operating Temperature	-45°C to 100°C
Storage Temperature	-55°C to 100°C
Permanent damage may occur if any	of these limits are exceeded.

Outline Drawing



Outline Dimensions (inch)

В	D	E	wt
.410	1.43	.312	grams
10.41	36.32	7.92	10.0

Features

- wideband coverage, DC to 12000 MHz
- 1 watt rating
- rugged unibody construction
- · off-the-shelf availability very low cost
- Applications
- impedance matching
- signal level adjustment





Generic photo used for illustration purposes only CASE STYLE: FF704

> Connectors Model SMA FW-7+

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Electrical Specifications at 25°C


Parameter	Condition (MHz)	Min.	Тур.	Max.	Unit
Frequency Range		DC	_	12000	MHz
	10	—	7	_	
	DC - 3000	6.6	7.2	7.7	
Attenuation	3000 - 8000	6.85	7.45	8.1	dB
	8000 - 12000	7.15	7.75	8.4	
	DC - 3000		1.05	1.20	
VSWR	3000 - 8000		1.15	1.30	:1
VSWIT	8000 - 12000	_	1.30		
Input Power	DC - 12000	—	—	1.0	W


1. Flatness = variation over band divided by 2.

Typical Performance Data VSWR Frequency (MHz) Attenuation (dB) (:1) 10.00 7.01 1.02 100.00 7.05 1 02 2000.00 7.21 1.02 3000.00 7.27 1.05 6000.00 7.47 1.10 8000.00 7.59 1.12 10000.00 7.70 1.16 11000.00 7.75 1.16 11500.00 7.75 1.16 7.73 12000.00 1.17 15000.00 7.69 1.12

Electrical Schematic







Notes

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"): Purchasers of this performance Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp



Mini-Circuits

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 $\frac{\text{Mini-Circuits}}{\frac{FW-7+}{2}}$