
Coaxial Fixed Attenuator

50Ω 1W 12dB

Maximum Ratings

Operating Temperature	-45°C to 100°C
Storage Temperature	-55°C to 100°C
Permanent damage may occur if any	of these limits are exceeded.

Outline Drawing



Outline Dimensions (inch)

wt	D	В
grams	1.94	.62
30.0	49.28	15.75

DC to 2000 MHz

Features

- excellent VSWR, 1.05:1 typ.
- excellent flatness, 0.10 dB typ. to 2000 MHz
- usable to 4000 MHz

Applications

- PCS
- instrumentation
- cellular





Generic photo used for illustration purposes only CASE STYLE: FF747

Connectors Model
BNC Male-BNC Female HAT-12+

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications


FREQ. RANGE (MHz)	ATTENUATION (dB) Flatness*				VSWR (:1)			MAX. INPUT POWER	
		DC-0.5 GHz	DC-1 GHz	DC-2 GHz	Total Band	DC-0.5 GHz	DC-1 GHz	DC-2 GHz	(W)
f _{L-} -f _U	Nom.	Тур.	Тур.	Тур.	Тур.	Тур.	Тур.	Тур.	
DC-2000	12±0.2	0.05	0.10	0.10	0.25	1.05	1.10	1.15	1.0


* Flatness = variation over band divided by 2.


Typical Performance Data

F	A 11 11	VONE	
Frequency (MHz)	Attenuation (dB)	VSWR (:1)	
10.00	12.04	1.00	
50.00	12.04	1.00	
100.00	12.06	1.00	
250.00	12.08	1.01	
500.00	12.10	1.01	
750.00	12.11	1.01	
1000.00	12.13	1.02	
1500.00	12.15	1.06	
1750.00	12.16	1.09	
2000.00	12.17	1.12	









Notes A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Nini-Circuit's applicable established test performance criteria and measurement instructions. C. The parts covered by this specification document are subject to Mini-Circuit shandard limited warranty and terms and conditions (collectively, "Standard Terms"). Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits vebsite at www.minicircuits.com/MCLStore/terms.jsp

REV. G M151107 EDR-5087/10 HAT-12 RVN/LC/CP/AM 200520

Mini-Circuits

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mini-Circuits: HAT-12+