

Coaxial

Fixed Attenuator

50Ω 1W 8dB DC to 2000 MHz

HAT-8+



CASE STYLE: FF747

Connectors	Model
BNC Male-BNC Female	HAT-8+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Maximum Ratings

Operating Temperature	-45°C to 100°C
Storage Temperature	-55°C to 100°C


Features

- excellent VSWR, 1.05:1 typ.
- excellent flatness, 0.15 dB typ. to 2000 MHz
- usable to 4000 MHz

Applications

- PCS
- instrumentation
- cellular

Outline Drawing



Outline Dimensions (inch/mm)

B	D	wt
.62	1.94	grams
15.75	49.28	30.0

Electrical Specifications




FREQ. RANGE (MHz)	ATTENUATION (dB) Flatness*				VSWR (:1)			MAX. INPUT POWER (W)	
	DC-0.5 GHz	DC-1 GHz	DC-2 GHz	Total Band	DC-0.5 GHz	DC-1 GHz	DC-2 GHz		
	Typ.	Typ.	Typ.	Typ.	Typ.	Typ.	Typ.		
f_c-f_u	Nom.								
DC-2000	8±0.2	0.05	0.10	0.15	0.25	1.05	1.10	1.10	1.0

* Flatness = variation over band divided by 2.

Typical Performance Data

Frequency (MHz)	Attenuation (dB)	VSWR (:1)
10.00	8.00	1.00
50.00	8.00	1.00
100.00	8.01	1.00
250.00	8.02	1.01
500.00	8.04	1.01
750.00	8.05	1.03
1000.00	8.07	1.03
1500.00	8.09	1.04
1750.00	8.10	1.05
2000.00	8.10	1.07

Electrical Schematic



Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
 C. The parts covered by this specification document are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

 REV. G
 M151107
 EDR-5087/8
 HAT-8+
 RVN/LC/CP/AM
 150724

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Mini-Circuits:](#)

[HAT-8+](#)