

Ceramic High Pass Filter

HFCW-242+

50Ω 2400 to 3300 MHz

The Big Deal

- Very good rejection, 20 dB typical
- Rugged, ceramic construction
- Tiny size, 0.063" x 0.032" x 0.024" (0603)
- Good power handling, 2W



CASE STYLE: JC0603C-4

Product Overview

Mini-Circuits' HFCW-242+ is a LTCC High Pass Filter with a passband from 2400 to 3300 MHz, supporting a variety of applications. This model provides 1.5 dB typical passband insertion loss and provides a very good stopband rejection due to strategically constructed layout with minimal interaction between components. It provides a wide operating temperature range from -55 to +125°C. Housed in a tiny 0603 ceramic form factor with wrap-around terminations, the filter is ideal for dense PCB layouts and with minimal performance variation due to parasitics.

Key Features

Feature	Advantages
LTCC Construction	Provides repeatable performance in a rugged, ceramic package well suited for tough environments such as high humidity and temperature extremes.
Tiny size (0.063 x 0.032 x 0.024")	Saves space in dense circuit board layouts and minimizes the effects of parasitics.
Good power handling	Supports a wide range of system power requirements.
Wrap-around terminations	Provides excellent solderability and easy visual inspection

Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



Ceramic High Pass Filter

50Ω 2400 to 3300 MHz

HFCW-242+



Generic photo used for illustration purposes only

CASE STYLE: JC0603C-4

Features

- Miniature size 0603
- High stop band rejections
- Low cost
- Aqueous washable

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Applications

- ISM Band
- WLAN
- Bluetooth
- Zigbee

Electrical Specifications^{1,2} at 25°C

Parameter		F#	Frequency (MHz)	Min.	Typ.	Max.	Unit
Stop Band	Rejection Loss	DC-F1	10 - 1650	20	25	—	dB
	Freq. Cut-Off	F2	2200	—	2.5	—	dB
Pass Band	Insertion Loss	F4-F5	2400 - 3300	—	1.5	2.5	dB
	Return Loss	F4-F5	2400 - 3300	—	9.5	—	

1. Tested on Evaluation Board TB-HFCW-242+

2. In Application where DC voltage is present at either input or output ports, coupling capacitors are required.


Maximum Ratings

Operating Temperature	-55°C to 125°C
Storage Temperature	-55°C to 125°C
RF Power Input ³	2W at 25°C


3. Passband rating, derate linearly to 0.5W at 125°C ambient.

Permanent damage may occur if any of these limits exceeded.

Functional Schematic






Typical Frequency Response



Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)	Return Loss (dB)
10	64.90	0.05
100	45.98	0.05
200	40.21	0.05
500	33.83	0.09
1000	37.59	0.18
1200	47.78	0.24
1650	27.57	0.55
1700	28.03	0.61
1800	33.42	0.78
2000	14.27	1.96
2200	2.56	14.86
2400	1.31	15.96
2500	1.14	16.04
2600	0.99	18.70
2700	0.88	24.27
2800	0.81	26.49
3000	0.83	15.42
3100	0.91	12.72
3300	1.11	9.59
3400	1.22	8.59



Notes

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp



www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com


REV. OR
ECO-004693
HFCW-242+
RS/CP/AM
201104
Page 2 of 3



Pad Connections

INPUT	1
OUTPUT	3
GROUND	2,5
NO CONNECTION	4,6


Product Marking: N/A

Evaluation Board MCL P/N: TB-HFCW-242+
Suggested PCB Layout (PL-553)



- NOTES:
- TRACE WIDTH IS SHOWN FOR FR4, GRADE IT-180TC (ITEQ CORP.) WITH DIELECTRIC THICKNESS .016±.0015. COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH & GAP MAY NEED TO BE MODIFIED.
 - BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
-  DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER).
-  DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK.

Outline Drawing



Outline Dimensions (inch mm)

A	B	C	D	E
.063	.032	.022	.012	.008
1.60	0.81	0.56	0.30	0.20
F	G	H		wt
.006	.008	.020		grams
0.15	0.20	0.51		.005

Notes

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Mini-Circuits:](#)

[HFCW-242+](#)