RFTransformer

0.01 to 100 MHz

T2.5-6-KK81+



Generic photo used for illustration purposes only CASE STYLE: KK81

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Maximum Ratings

Operating Temperature	-20°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	250mW
DC Current	30mA
Permanent damage may occur if any	of these limits are exceeded

Pin Connections


PRIMARY DOT	4
PRIMARY	6
SECONDARY DOT	3
SECONDARY	1
SECONDARY CT	_
NOT USED	2,5

Outline Drawing



Outline Dimensions (inch)

J	Н	G	F	E	D	С	В	Α
.05	.05	.100	.020	.042	.010	.23	.27	.30
1.27	1.27	2.54	0.51	1.07	0.25	5.84	6.86	7.62
wt	S	R	Q	Р	N	М	L	K
grams	.100	.050	.125	.600	.575	.26	.036	.020
0.50	2.54	1.27	3.18	15.24	14.61	6.60	0.91	0.51



Features

- good return loss
- also available with plug-in (X65) and flat-pack (W38) leads

Applications

- HF/VHF
- impedance matching
- receivers/transmitters


Transformer Electrical Specifications


Ω RATIO (Secondary/Primary)	FREQUENCY (MHz)	INSERTION LOSS*		
		MHz	MHz	MHz
2.5	0.01-100	0.01-100	0.02-50	0.05-20

^{*} Insertion Loss is referenced to mid-band loss, 0.2 dB tvp.

Typical Performance Data

FREQUENCY (MHz)	INSERTION LOSS (dB)	INPUT R. LOSS (dB)	
0.01	2.90	1.61	
0.02	1.26	4.15	
0.05	0.35	10.11	
0.10	0.20	15.86	
0.20	0.19	21.42	
20.00	0.40	11.56	
50.00	1.18	5.42	
53.67	1.30	5.02	
95.26	2.30	3.06	
100.00	2.38	3.00	





- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

 B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins.

 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Terms"): Purchases of this part. Ferrormance and updany attributes and contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mini-Circuits: T2.5-6-KK81+