

TCM2-33WX-2+

 50Ω 10 to 3000 MHz

Features

- wide bandwidth 10 to 3000 MHz
- balanced transmission line
- excellent return loss
- aqueous washable
- · patent pending

Applications

- PCS
- wideband push-pull amplifiers
- cellular



Generic photo used for illustration purposes only

CASE STYLE: DB1627

+RoHS Compliant
The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

	Available Tape and Reel at no extra cost
Reel Size	Devices/Reel
7"	20, 50, 100, 200, 500
13"	1000, 2000

Electrical Specifications at 25°C

Parameter	Frequency (MHz)	Min.	Тур.	Max.	Unit
Impedance Ratio (secondary/primary)			2		Ohm
Frequency Range		10		3000	MHz
Insertion Loss*	10 - 3000	_	1.5	3.0	dB
Amplitude Unbalance	10 - 3000	_	0.7	_	dB
Phase Unbalance	10 - 3000	_	4	_	Degree

^{*} Insertion Loss is referenced to mid-band loss, 0.8 dB typ.

Maximum Ratings

Parameter	Ratings		
Operating Temperature	-40°C to 85°C		
Storage Temperature	-55°C to 100°C		
RF Power	0.4W		
DC Current	30mA		


Permanent damage may occur if any of these limits are exceeded.

Pin Connections

Function	Pin Number			
PRIMARY DOT	6			
PRIMARY	2			
SECONDARY DOT	4			
SECONDARY	3			
GND	2,5			
NOT USED	1			


Product Marking






TCM2-33WX-2+

Outline Drawing






TOLERANCE TO BE WITHIN ±.002

Outline Dimensions (inch mm)

F	F	D	C	В	Α
.025	.040	.050	.160	.150	.160
0.64	1.02	1.27	4.06	3.81	4.06
0.04	1.02	1.27	4.00	3.01	4.00
wt		K	J	Н	G
grams		.030	.190	.065	.028
0.15		0.76	4.83	1.65	0.71

Demo Board MCL P/N: TB-654+ Suggested PCB Layout (PL-364)



NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .020" ± .0015"; COPPER: 1/2 0Z. ON EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.


2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE. DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)


DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK


Typical Performance Data

	,,			
Frequency (MHz)	Insertion Loss (dB)	Input R. Loss (dB)	Amplitude Unbalance (dB)	Phase Unbalance (Deg.)
10	0.87	21.66	0.03	0.01
100	0.78	28.58	0.03	0.04
400	0.95	21.26	0.05	0.82
700	1.12	18.13	0.12	0.83
1000	1.30	16.31	0.26	0.62
1600	1.72	14.75	0.74	1.70
2000	2.01	14.79	0.90	2.62
2500	2.46	15.01	0.79	1.26
2800	2.74	14.33	0.64	0.80
3000	2.93	13.77	0.54	1.09









Additional Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.

 C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website a www.minicircuits.com/MCLStore/terms.jsp



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mini-Circuits: TCM2-33WX-2+