
Coaxial **SMA Fixed Attenuator** DC to 6000 MHz

1W 1dB 50Ω

Maximum Ratings

Operating Temperature	-45°C to 100°C					
Storage Temperature	-55°C to 100°C					
Permanent damage may occur if any of these limits are exceeded						

Outline Drawing



Outline Dimensions (inch)

В	D	Е	wt
.410	1.43	.312	grams
10.41	36.32	7.92	10.0

Features

- wideband coverage, DC to 6000 MHz
- 1 watt rating
- rugged unibody construction
- off-the-shelf availability
- · very low cost

Applications

- impedance matching
- signal level adjustment





Generic photo used for illustration purposes only

CASE STYLE: FF704 Connectors Model SMA VAT-1+

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications


FREQ. RANGE (MHz)	ATTENUATION * (dB) Flatness **				VSWR (:1)			MAX. INPUT POWER	
		DC-3 GHz	3-5 GHz	5-6 GHz	DC-6 GHz	DC-3 GHz	3-5 GHz	5-6 GHz	(W)
f _L -f _U	Nom.	Тур.	Тур.	Тур.	Тур.	Тур. Мах.	Тур. Мах.	Тур.	
DC-6000	1±0.3	0.20	0.20	0.20	0.60	1.05 1.20	1.10 1.50	1.40	1.0


* Attenuation varies by 0.3 dB max. over temperature.


** Flatness= variation over band divided by 2.

Typical Performance Data Attenuation VSWR Frequency (MHz) (dB) (:1) 0.03 1.03 1.01 50.00 1.01 1.01 100.00 1.02 1.02 500.00 1.10 1.04 1000.00 1.17 1.07 2000.00 1.29 1.09 3000.00 1 42 1.06 4000.00 1.54 1.07 5000.00 1.74 1.23 6000.00 2.12 1.43

Electrical Schematic







A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warrantv and terms and conditions (collectively: "Standard Terms"): Purchasers of this performance

Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp

Mini-Circuits

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

REV. H M151107 VAT-1+ LC/TD/CP/AM 200520 Page 1 of 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 $\frac{\text{Mini-Circuits:}}{\frac{\text{VAT-1+}}{2}}$