
# Coaxial **SMA Fixed Attenuator**

#### 50Ω 10dB 2W

#### **Maximum Ratings**

| Operating Temperature             | -45°C to 100°C                |
|-----------------------------------|-------------------------------|
| Storage Temperature               | -55°C to 100°C                |
| Permanent damage may occur if any | of these limits are exceeded. |

#### **Outline Drawing**



### Outline Dimensions (inch )

| wt    | Е    | D     | В     |
|-------|------|-------|-------|
| grams | .312 | 1.43  | .74   |
| 11.4  | 7.92 | 36.32 | 18.80 |

# DC to 6000 MHz

#### Features

- wideband coverage, DC to 6000 MHz
- 2 watt rating
- rugged unibody construction
- off-the-shelf availability
- · very low cost

### **Applications**

- impedance matching
- signal level adjustment





Generic photo used for illustration purposes only CASE STYLE: DC1066

Connectors Model SMA VAT-10W2+

#### +RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


#### **Electrical Specifications**


| FREQ.<br>RANGE<br>(MHz)        | ATTENUATION *<br>(dB)<br>Flatness ** |          |         |         | VSWR<br>(:1) |           |           | MAX.<br>INPUT<br>POWER |     |
|--------------------------------|--------------------------------------|----------|---------|---------|--------------|-----------|-----------|------------------------|-----|
|                                |                                      | DC-3 GHz | 3-5 GHz | 5-6 GHz | DC-6 GHz     | DC-3 GHz  | 3-5 GHz   | 5-6 GHz                | (W) |
| f <sub>L</sub> -f <sub>U</sub> | Nom.                                 | Тур.     | Тур.    | Тур.    | Тур.         | Тур. Мах. | Тур. Мах. | Тур.                   |     |
| DC-6000                        | 10±0.3                               | 0.10     | 0.20    | 0.15    | 0.35         | 1.15 1.25 | 1.35 1.60 | 1.60                   | 2.0 |

\* Attenuation varies by 0.3 dB max. over temperature.

\*\* Flatness= variation over band divided by 2.

#### **Typical Performance Data** Attenuation VSWR Frequency (MHz) (dB) (:1) 9.98 10.00 1.00 100.00 10.02 1.00 1000.00 10.10 1.03 2000.00 1.08 10.11 3000.00 10.08 1.14 4000.00 10.03 1.21 4500.00 9.99 1.26 5000.00 9.95 1.34 5500.00 9.84 1.42 6000.00 9.79 1.54





A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warrantv and terms and conditions (collectively: "Standard Terms"): Purchasers of this performance

Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp



## Mini-Circuits

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mini-Circuits: VAT-10W2+