
Coaxial **SMA Fixed Attenuator** DC to 6000 MHz

2W 1dB 50Ω

Maximum Ratings

| Operating Temperature | -45°C to 100°C | | | | | | |
|---|----------------|--|--|--|--|--|--|
| Storage Temperature | -55°C to 100°C | | | | | | |
| Permanent damage may occur if any of these limits are exceeded. | | | | | | | |

Outline Drawing



Outline Dimensions (inch)

| wt | Е | D | В |
|-------|------|-------|-------|
| grams | .312 | 1.43 | .74 |
| 11.4 | 7.92 | 36.32 | 18.80 |

Notes

Features

- wideband coverage, DC to 6000 MHz
- 2 watt rating
- rugged unibody construction
- off-the-shelf availability
- · very low cost
- **Applications**
- impedance matching signal level adjustment





Generic photo used for illustration purposes only CASE STYLE: DC1066

Connectors Model SMA VAT-1W2+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Electrical Specifications


| FREQ. RANGE (MHz) | ATTENUATION * (dB) Flatness ** | | | VSWR (:1) | | | MAX. INPUT POWER | | |
|--------------------------------|--------------------------------------|----------|---------|--------------|----------|-----------|------------------------|---------|-----|
| | | DC-3 GHz | 3-5 GHz | 5-6 GHz | DC-6 GHz | DC-3 GHz | 3-5 GHz | 5-6 GHz | (W) |
| f _L -f _U | Nom. | Тур. | Тур. | Тур. | Тур. | Тур. Мах. | Тур. Мах. | Тур. | |
| DC-6000 | 1±0.3 | 0.20 | 0.20 | 0.20 | 0.60 | 1.10 1.20 | 1.30 1.50 | 1.55 | 2.0 |

* Attenuation varies by 0.3 dB max. over temperature.

** Flatness= variation over band divided by 2.

Typical Performance Data Attenuation VSWR Frequency (MHz) (dB) (:1) 10.00 0.98 1.00 100.00 1.02 1.01 1000.00 1.17 1.05 2000.00 1 26 1 0 5 3000.00 1.34 1.02 4000.00 1.49 1.07 4500.00 1.51 1.14 5000.00 1.57 1.24 5500.00 1.73 1.37 6000.00 1.88 1.54





A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins C. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively. "Standard Terms"): Purchasers of this part

Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp

REV. C M151107 VAT-1W2+ EDU-0334/1 URJ/LC/CP/AM 200924 Page 1 of 1

Mini-Circuits

www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mini-Circuits: VAT-1W2+