# **SMA Fixed Attenuator**

DC to 6000 MHz  $50\Omega$ 2dB **2W** 

#### **Maximum Ratings**

Operating Temperature -45°C to 100°C Storage Temperature -55°C to 100°C

Permanent damage may occur if any of these limits are exceeded

#### **Features**

- wideband coverage, DC to 6000 MHz
- 2 watt rating
- rugged unibody construction
- · off-the-shelf availability
- · very low cost

#### **Applications**

- impedance matching
- · signal level adjustment

### **VAT-2W2+**



Generic photo used for illustration purposes only


CASE STYLE: DC1066

Connectors Model SMA VAT-2W2+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

#### **Outline Drawing**



#### Outline Dimensions (inch )

wt	Е	D	В
grams	.312	1.43	.74
11.4	7.92	36.32	18.80


### **Electrical Specifications**


FREQ. RANGE (MHz)	GE (dB)				VSWR (:1)		MAX. INPUT POWER		
		DC-3 GHz	3-5 GHz	5-6 GHz	DC-6 GHz	DC-3 GHz	3-5 GHz	5-6 GHz	(W)
f <sub>L</sub> -f <sub>U</sub>	Nom.	Тур.	Тур.	Тур.	Тур.	Тур. Мах.	Тур. Мах.	Тур.	
DC-6000	2±0.3	0.20	0.20	0.25	0.65	1.10 1.20	1.30 1.50	1.50	2.0

<sup>\*</sup> Attenuation varies by 0.3 dB max. over temperature.

#### **Typical Performance Data**

Frequency (MHz)	Attenuation (dB)	VSWR (:1)	
10.00	1.97	1.00	
100.00	2.01	1.01	
1000.00	2.14	1.05	
2000.00	2.23	1.06	
3000.00	2.32	1.03	
4000.00	2.50	1.04	
5000.00	2.64	1.18	
5500.00	2.80	1.29	
5750.00	2.89	1.36	
6000.00	2.96	1.45	





A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively: "Standard Terms"): Purchases of this part. Ferrormance and updany authorities and contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

<sup>\*\*</sup> Flatness= variation over band divided by 2.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mini-Circuits: VAT-2W2+