SMA Fixed Attenuator


DC to 6000 MHz 50Ω 30dB **2W**

Maximum Ratings

Operating Temperature -45°C to 100°C Storage Temperature -55°C to 100°C

Permanent damage may occur if any of these limits are exceeded.

Outline Drawing



Outline Dimensions (inch)

wt	Е	D	В
grams	.312	1.43	.74
11.4	7.92	36.32	18.80

Features

- wideband coverage, DC to 6000 MHz
- 2 watt rating
- · rugged unibody construction
- · off-the-shelf availability
- · very low cost

Applications

- impedance matching
- · signal level adjustment

VAT-30W2+



Generic photo used for illustration purposes only

CASE STYLE: DC1066

Connectors Model SMA VAT-30W2+

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Electrical Specifications


FREQ. RANGE (MHz)	GE (dB)			VSWR (:1)		MAX. INPUT POWER			
		DC-3 GHz	3-5 GHz	5-6 GHz	DC-6 GHz	DC-3 GHz	3-5 GHz	5-6 GHz	(W)
f _L f _U	Nom.	Тур.	Тур.	Тур.	Тур.	Тур. Мах.	Тур. Мах.	Тур.	
DC-6000	30±0.3	0.70	0.45	0.20	1.30	1.25 1.35	1.45 1.70	1.60	2.0

^{*} Attenuation varies by 0.3 dB max. over temperature.

Typical Performance Data

Attenuation (dB)	VSWR (:1)
30.04	1.00
30.04	1.00
29.72	1.04
29.22	1.09
28.80	1.16
28.46	1.24
28.22	1.30
27.98	1.37
27.87	1.46
27.69	1.57
	(dB) 30.04 30.04 29.72 29.22 28.80 28.46 28.22 27.98 27.87





A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.

B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement ins.

C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively. "Standard Terms"): Purchasers of this part. Ferrormance and updany authorities and contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. The parts covered by this specification document are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

^{**} Flatness= variation over band divided by 2.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mini-Circuits: VAT-30W2+