

# Coaxial Bandpass Filter

## VBF-7331+

50Ω 6850 to 7850 MHz

### The Big Deal

- Good rejection
- Good VSWR
- Connectorized package



Generic photo used for illustration purposes only  
CASE STYLE: FF704

### Product Overview

The VBF-7331+ Band Pass Filter is constructed using internal LTCC Band Pass Filter structure to achieve repeatable performance. This offers low insertion loss and good rejection at the band reject edges. Built using Mini-Circuits proven unibody construction which integrates the RF connectors with the case body, the VBF-7331+ takes very little space and meets rugged test lab system environment.

### Key Features

Feature	Advantages
Good Rejection close to pass band	Provides good rejection of signals close to the pass band, for improved system performance.
Compact Versatile Case (1.43"x0.41")	Enables use in a variety of applications including space constrained connectorized systems. Connectors: SMA Female (1), SMA Male (1)
Rugged Unibody Construction	Mini-Circuits Unibody construction allows survivability in critical applications including militarized or industrial systems.

#### Notes

- A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.  
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.  
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)



# Bandpass Filter

50Ω 6850 to 7850 MHz

## VBF-7331+



Generic photo used for illustration purposes only

CASE STYLE: FF704

Connectors Model  
SMA VBF-7331+


### Features

- Small size
- Temperature stable
- Rugged unibody construction


### Applications

- Harmonic rejection
- Transmitters / Receivers
- UWB impulse radar
- Emission masking

### Functional Schematic



### Typical Frequency Response



#### +RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

### Electrical Specifications<sup>(1)</sup> at 25°C

Parameter	F#	Frequency (MHz)	Min.	Typ.	Max.	Unit
Pass Band	F1	7331	-	-	2	dB
	F2-F3	6850 - 7850	-	1.4	-	dB
	F2-F3	6850 - 7850	-	1.45	-	:1
Stop Band, Lower	DC-F4	10-5600	10	23	-	dB
	F4-F5	5600-5800	-	10	-	dB
Stop Band, Upper	DC-F5	10-5800	-	20	-	:1
	F6-F7	9300 - 10500	10	20	-	dB
	F7-F8	10500-13300	-	10	-	dB
	F6-F8	9300-13300	-	20	-	:1

(1) In Application where DC voltage is present at either input or output ports, coupling capacitors are required.





### Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input	2.5 W max.

\*Passband rating, derate linearly to 0.7 W at 100°C ambient  
Permanent damage may occur if any of these limits are exceeded.

### Typical Performance Data at 25°C

Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)	Frequency (MHz)	Group Delay (ns)
10	76.27	7226.80	6850	0.46
200	69.65	262.08	6900	0.45
900	44.13	118.17	6950	0.45
2150	30.09	84.25	7000	0.44
3000	25.06	77.66	7050	0.44
3700	22.00	67.17	7100	0.44
4250	20.12	55.05	7150	0.44
5600	30.34	20.53	7200	0.44
5800	16.15	12.98	7250	0.44
6250	3.07	2.37	7331	0.44
6850	1.38	1.28	7350	0.44
7331	1.43	1.40	7400	0.44
7850	1.78	1.10	7450	0.44
8600	13.90	8.34	7500	0.45
9300	25.50	18.83	7550	0.46
10000	24.67	23.10	7600	0.46
10500	28.52	24.93	7650	0.47
11400	14.97	12.91	7700	0.48
12100	28.03	25.93	7750	0.50
13300	29.93	23.48	7850	0.53



#### Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)




[www.minicircuits.com](http://www.minicircuits.com) P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

Coaxial Connections

PORT - 1	SMA-MALE
PORT - 2	SMA-FEMALE

Outline Drawing



Outline Dimensions ( <sup>inch</sup><sub>mm</sub> )

B	D	E	wt.
.410	1.43	.312	grams
10.41	36.32	7.92	10

Note: Please refer to case style drawing for details

**Notes**  
A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.  
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.  
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at [www.minicircuits.com/MCLStore/terms.jsp](http://www.minicircuits.com/MCLStore/terms.jsp)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Mini-Circuits:](#)

[VBF-7331+](#)