# Coaxial **High Pass Filter**

## **50**Ω

## 950 to 3200 MHz

## **Maximum Ratings**

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power Input*	7W max. at 25°C

\* Passband rating, derate linearly to 3W at 100°C ambient. Permanent damage may occur if any of these limits are exceeded.

## **Features**

- rugged unibody construction, small size
- 7 sections
- temperature stable
- excellent power handling, 7W
- low cost

## Applications

- sub-harmonic rejection
- transmitters/receivers
- · lab use






Generic photo used for illustration purposes only

CASE STYLE: FF704

Connectors Model SMA VHF-880+

+RoHS Compliant The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

#### **Outline Drawing** SMA FEMALE SMA MALE CONN CONN




## Outline Dimensions (inch)


В	D	Е	wt
.410	1.43	.312	grams
10.41	36.32	7.92	10.0

Electrical Specifications (T<sub>AMB</sub>=25°C) PASSBAND (MHz) STOP BAND fco, MHz **VSWR** (:1) NO. OF (MHz) SECTIONS Nom. Тур. Min Frequency (loss < 1.3 dB) (MHz) (loss 3 dB) (loss < 2 dB)(loss > 40 dB)(loss > 20 dB) Тур. Max Тур. Stopband 1.5:1 970-2400 500 640 880 1060-2500 950-3200 20:1 7

## typical frequency response



## electrical schematic



### **Typical Performance Data**


Frequency (MHz)	Insertion Loss (dB)	VSWR (:1)
1	82.28	868.59
100	65.99	868.59
500	43.09	52.65
640	23.32	24.48
750	10.12	8.60
810	4.81	3.78
880	1.98	1.81
950	1.20	1.36
970	1.09	1.32
1060	0.85	1.28
2400	0.56	1.55
2500	0.64	1.68
3200 4200	1.59 3.53	2.92 5.83
4200 5000	5.41	9.48
5000	5.41	9.40
VHF-880 INSERTION LOSS		VHF-880 VSWR
	10000	
90		
80	1000	
70		
60	<u> </u>	
50	¥ 100	
40		
30	10	
20		
10		
0+	1	

Notes

A Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document. B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/WCLStore/terms.jsp

REV. F M151777 VHF-880+ EDR-6437/1 RVN/AD/AM 200520 Page 1 of 1





www.minicircuits.com P.O. Box 350166, Brooklyn, NY 11235-0003 (718) 934-4500 sales@minicircuits.com

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mini-Circuits: VHF-880+