Accessories Type ADAPT 1605, Coding Adaptor





Product Description

Coding Adaptor between GAP 1605 and Dupline[®] modules without standard 6-pole connection plug. ADAPT 1605 has 4 clip-on terminals for Dupline[®] modules which are programmed through wires (e.g. G 8910 1101) and it has a M12connector for modules like G 8911 1010. ADAPT 1605 has a standard 6-pole connector for the GAP 1605 connection.

• Coding Adaptor between GAP 1605 and Dupline[®] modules without standard connection plug (e.g. G 8910 1101 and G 8911 1010)

Ordering Key

ADAPT 1605

Type no.

Type Selection

Ordering no.

ADAPT 1605

Product Specifications

General Specifications

Environment Degree of protection Pollution degree Operating temperature Storage temperature	IP 20 3 (IEC 60664) 0° to +50°C (+32° to +122°F) -20° to +60°C (-4° to +140°F)
Humidity (non-condensing)	20 to 80% RH
Mechanical resistance Shock Vibration	15 G (11 ms) 2 G (6 to 55 Hz)
Material	ABS, grey
Weight	100 g

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Carlo Gavazzi:

<u>AI-800</u> <u>AJ220</u> <u>AJ800</u> <u>AJ400</u> <u>ADAPT1605</u> <u>AI-400</u>