

SPDC



Single Phase Compact Power Supply



Description

The SPDC power supplies is a range where high performance meets high quality in a compact frame. These power supplies are offered in 120 W, 240 W, 480 W, and they have a universal input voltage range 85 VAC to 264 VAC and 130 VDC to 350 VDC.

The SPDC achieve a high energy efficiency of up to 94%, and can be connected in parallel to achieve twice the current. Reliability is guaranteed through the multiple integrated protections, and it also comes with built-in active PFC.

SPDC coupled compact dimensions with advance features to provide a power supply for all automation applications requiring reliability, quality and performance.

All specifications are at nominal values, full load, 25°C unless otherwise stated.

Benefits

- **Reliable power in very compact dimensions.** This SPDC has an ultra-slim DIN rail body, with up to 480 W in only 70 mm width of space
- **Built-in active PFC.** The power factor correction (PFC) circuit adjusts the power factor to 0.99@110VAC and 0.95@230VAC.
- **Parallel function.** The SPDC can easily be connected in parallel to provide for increased power or used in redundancy operations.
- **150% Power Boost.** The SPDC can provide 150% of the rated output power for up to 3 seconds, providing the extra power needed during critical startups.
- **Universal AC, DC input range.** SPDC Series can be powered with AC Voltage (85 VAC to 264 VAC) or with DC Voltage (130 VDC to 350 VDC).
- **Reliable critical protection.** Safety and reliability is guaranteed by the various output protections: Over Voltage (OVP), Over Load (OLP), Short Circuit (SCP) and Over Temperature (OTP).
- **High efficiency and wide operating ambient temperature.** The SPDC has a very high efficiency of up to 93.8%. The operating temperature range is, from -25°C to +60°C (without derating), and up to 70°C with -25% derating.
- **Ease of installation.** The SPDC can be installed in 5 different orientations, enabling the unit to fit easily into installation with limited space.

Applications

The SPDC is extremely suitable for applications which requires high efficiency, high safety standards and high PF corrections. It also provides the DC OK signaling with LED and relay output.

Main functions

- High efficiency up to 93.8%
- In-built active PFC, PF>0.95
- Output options of 12 VDC, 24 VDC or 48 VDC
- Universal input voltage range: 85 VAC to 264 VAC; 130 VDC to 350 VDC
- Bi-colour LED for status, and DC-OK relay contact
- Parallel function

References

Order code

 **SPDC** ☐ ☐ **1**

Enter the code entering the corresponding option instead of ☐

Code	Option	Description	Notes
S	-	Switching	Device typology
P	-	Power	
D	-	DIN rail	
C	-	Compact	
☐	12	12 VDC	Rated output voltage
	24	24 VDC	
	48	48 VDC	
☐	120	120 W	Rated output power
	240	240 W	
	480	480 W	
1	-	Single phase input	Input type

Selection guide


Output Voltage	120 W	240 W	480 W
12 VDC	SPDC121201	-	-
24 VDC	SPDC241201	SPDC242401	SPDC244801
48 VDC	-	-	SPDC484801

Further reading


Information	Where to find it	QR
SPDC datasheet	https://www.gavazziautomation.com/fileadmin/images/PIM/DATASHEET/ENG/SPDC_DS_ENG.pdf	
SPDC installation sheet	https://www.gavazziautomation.com/fileadmin/images/PIM/MANUALS/ENG/SPDC_IM.pdf	

Structure


SPDC 120 W



SPDC 240 W



SPDC 480 W



Element	Component	Function
A	DC OK Relay contacts	Output status. Max 30 V / 1 A or 60 V / 0.3 A or 30 VAC / 0.3 A Resistive load
B	+ V terminals	Positive DC Output terminals
C	- V terminals	Negative DC Output terminals
D	VADJ Trimmer	Output voltage adjustment
E	DC OK LED	Green when output voltage $\geq 90\%$ of rated output voltage Red when output voltage $\leq 80\%$ of rated output voltage, or, Overload
F	Single/Parallel Switch	Enabling or disabling of output parallel connection function
G	Power supply terminals	L, N supply terminals + GND
H	DIN rail mounting clip	Clip present on back side

Features


General data

	SPDC 120 W	SPDC 240 W	SPDC 480 W
Leakage current	<0.25mA (Input-Output)		
Earth leakage current	<3.5mA (Input-GND)		
Efficiency	89.5% (12 VDC) 91% (24 VDC)	94% (24 VDC)	93.8% (24 VDC) 93.8% (48 VDC)
Power loss @ nominal load	15 W	23 W	35 W
Power Factor (Full Load)	0.99 0.95		
	110 VAC 230 VAC		
Ingress Protection	IP20		
MTBF (MIL-HDBK-217F)	>300,000Hrs		
Case material	Metal, Stainless Steel		
Weight	550g (1.21lb)	780g (1.72lb)	1150g (2.535 lb)

Dimensions


SPDC 120 W

Unit : mm




SPDC 240 W

Unit: mm



SPDC 480 W

Unit: mm




Connection diagram

Terminal markings


SPDC 120 W

Terminal	Designation	Description
1	Ground	Ground this terminal to minimize high frequency emissions
2	N	Input terminals (neutral conductor, no polarity with DC input)
3	L	Input terminals (phase conductor, no polarity with DC input)
4	DC OK	DC ON relay contact (Common)
5	DC OK	DC ON relay contact (Normally open contact)
7	V+	Positive output terminal
6	V-	Negative output terminal
	Vout ADJ.	Potentiometer for output voltage adjustment
	DC status	LED indication of power supply output status
	Parallel	Switch for single or parallel operation




SPDC 240 W

Terminal	Designation	Description
1	Ground	Ground this terminal to minimize high frequency emissions
2	N	Input terminals (neutral conductor, no polarity with DC input)
3	L	Input terminals (phase conductor, no polarity with DC input)
4	DC OK	DC ON relay contact (Common)
5	DC OK	DC ON relay contact (Normally open contact)
6, 7	V+	Positive output terminal
8, 9	V-	Negative output terminal
	Vout ADJ.	Potentiometer for output voltage adjustment
	DC status	LED indication of power supply output status
	Parallel	Switch for single or parallel operation



SPDC 480 W

Terminal	Designation	Description
1	Ground	Ground this terminal to minimize high frequency emissions
2	N	Input terminals (neutral conductor, no polarity with DC input)
3	L	Input terminals (phase conductor, no polarity with DC input)
4	DC OK	DC ON relay contact (Common)
5	DC OK	DC ON relay contact (Normally open contact)
6, 7, 8	V+	Positive output terminal
9, 10, 11	V-	Negative output terminal
	Vout ADJ.	Potentiometer for output voltage adjustment
	DC status	LED indication of power supply output status
	Parallel	Switch for single or parallel operation



Environmental

	SPDC 120 W	SPDC 240 W	SPDC 480 W
Operating temperature	-25°C to 70°C -13°F to 158°F		
Storage temperature	-40°C to 85°C -40°F to 185°F		
Humidity	20% to 90% RH No condensing	5% to 90% RH No condensing	
Temperature derating from 60°C to 70°C (140°F to 158°F)	Refer to derating diagram		
Temperature coefficient	+/- 0.03%/°C		

Compatibility and conformity

	SPDC 120 W	SPDC 240 W	SPDC 480 W
Safety standards	EN60950-1		
EMC emission	EN55022, EN55024, FCC PART 15 Class B		
Harmonic current	EN61000-3-2, Class A		
EMC immunity	EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-8, EN61000-4-11, Heavy Industrial Level		
UL Certification cULus cURus	UL508 Listed UL60950-1 (2nd Edition)		
Vibration resistance	IEC 60068-2-6		

Insulation

	SPDC 120 W	SPDC 240 W	SPDC 480 W
Insulation / withstand voltage (input / GND)	2.5 kVAC / 10 mA		
Insulation / withstand voltage (input / output)	3 kVAC / 10 mA		
Insulation / withstand voltage (output / GND)	0.5 kVAC / 20 mA		
Output / DC OK	0.5 kVAC / 1 mA		
Insulation resistance	$\geq 10 \text{ M}\Omega$		
Overvoltage category	II		
Pollution degree	2		


Inputs

	SPDC 120 W	SPDC 240 W	SPDC 480 W
Rated input voltage	100 VAC to 240 VAC		
Input voltage range	85 VAC to 264 VAC (max. 264 VAC) 127 VDC to 375 VDC (max. 375 VDC)		90 VAC to 264 VAC (max. 264 VAC) 130 VDC to 350 VDC (max. 350 VDC)
AC current (max) 100 VAC 230 VAC	<1.5 A <0.65 A	<3 A <1.5 A	<7 A <3.5 A
Frequency range	47 Hz to 63 Hz		
Inrush current 100 VAC 230 VAC	<30 A <60 A	<20 A <40 A	<20 A <40 A
Inrush current (DC)	60 A	44 A	5.3 A
Internal input fuse	T5 A / 250 V	T5 A / 250 V	T10 A / 250 V
Standby-Consumption	<2.5 W	<3 W	<4 W

Outputs

	SPDC 120 W	SPDC 240 W	SPDC 480 W
Output Power	120 W	240 W	480 W
Voltage accuracy	±1%	±3%	±3%
Line regulation	±0.5%		
Load regulation	±1.0%		
Voltage regulation span 12 VDC 24 VDC 48 VDC	12 VDC to 14 VDC 24 VDC to 28 VDC -	- 24 VDC to 28 VDC -	- 24 VDC to 28 VDC 48 VDC to 56 VDC
Rated output current	10 A (12 VDC) 5 A (24 VDC)	10 A (24 VDC)	20 A (24 VDC) 10 A (48 VDC)
Ripple and Noise 0 to 70°C (32 to 158°F) -25 to 0°C (-13 to 32°F)	≤100 mV (12 VDC) ≤120 mV (24 VDC) ≤200 mV (12 VDC) ≤240 mV (24 VDC)	≤240 mV (24 VDC) ≤480 mV (24 VDC)	≤240 mV (24 VDC) ≤480 mV (48 VDC) ≤480 mV (24 VDC) ≤480 mV (48 VDC)
Hold up time	≤20 ms		
Set-up time	≤250 ms	≤3s	
Rise time	≤23 ms	≤26 ms	≤30 ms
Turn-on overshoot	≤5.0%		
Overshoot and undershoot	≤5.0%		
Series operation	Yes		
Parallel operation	Max 2 identical units		
Power boost	150% of rated output current		



Parallel operation




Performance

Current derating


SPDC 120W 12VDC



SPDC 120W 24VDC




SPDC 240W 24VDC




SPDC 480W 24VDC

Output Current Vs Ambient Temp.



SPDC 480W 48VDC



Installation

Ventilation and Cooling



Normal air convection; 25mm of free space on each side is recommended

Mounting method instruction



A1 is recommended output current, A2 is the allowed max output current (PSU lifetime is around half of A1)

120W 12VDC



Mounting A





Mounting B





Mounting C



Mounting D





Mounting E





120W 24VDC



Mounting A





Mounting B





Mounting C



Mounting D



Mounting E





Installation

Mounting method instruction



A1 is recommended output current, A2 is the allowed max output current (PSU lifetime is around half of A1). Below curves are tested under 230Vac (179~264Vac), when 110Vac input (85~175Vac), all derating points drops 10°C

240W 24VDC


Mounting A





Mounting B





Mounting C



Mounting D



Mounting E





Installation

Mounting method instruction



A1 is recommended output current, A2 is the allowed max output current (PSU lifetime is around half of A1). Below curves are tested under 230Vac (179~264Vac), when 110Vac input (85~175Vac), all derating points drops 10°C

480W 24VDC



Mounting A





Mounting B





Mounting C



Mounting D





Mounting E





480W 48VDC



Mounting A





Mounting B





Mounting C




Mounting D



Mounting E




Wiring diagram



Connection specification

	SPDC 120 W	SPDC 240 W	SPDC 480 W
Terminal type	Input: 6.35mm 3PIN screw terminals		
Screw driver blade	3.5mm slotted or cross screwdriver		
Tightening torque (Recommended)	1 Nm		
Flexible conductor Cross section Max	4 mm ²		
Flexible conductor Cross section Min	0.5 mm ²		
Conductor Cross section AWG Max	AWG20 (GND wire >18AWG)		
Conductor Cross section AWG Min	AWG10 (GND wire >18AWG)		
Rigid conductor Cross-section Min	6 mm ²		
Rigid conductor Cross-section Max	0.5 mm ²		
Max Wire Diameter	2.8 mm ²		

Block diagram



Troubleshooting

Signaling and controls

	SPDC 120 W	SPDC 240 W	SPDC 480 W
DC OK LED	Bicolour LED: Green-OK, Red-Fault		
DC OK output type	Normally Open contact		
Voltage free contact	Yes		
DC contact rating	Max 30 V / 1 A or 60 V / 0.3A (DC1)		
AC contact rating	Max 30 V / 0.3 A Resistive load (AC1)		
OK threshold	≥ 90% of rated output voltage		
Not OK threshold	≤ 80% of rated output voltage		

Operating description

Control and protection

	SPDC 120 W	SPDC 240 W	SPDC 480 W
Overvoltage protection	15-18 VDC (12 VDC) 29-33 VDC (24 VDC)	29-33 VDC (24 VDC)	28.8-33 VDC (24 VDC) 58-63 VDC (48 VDC)
Overload protection 100% ~ 150% of rated current >150% of rated current	Constant current limiting for some time (150% of rated current, last 3s) Hiccup mode, auto recovery: PS stop working for 7s, after 7s, if the load ≤ rated current, PS will work normally, auto recovery		
Current Limiting	Constant Current limiting		
Short Circuit protection	Long term mode. Auto recovery		
Over temperature protection	105±5°C (221°±41°F), detect on temperature controller; shut down O/P, auto recovery after temperature goes down		
Reverse voltage protection	No		

Glossary




CE: "Conformité Européene" or "European Conformity" ; Indicates the manufacturer declaration of conformity that the product meets the relevant health, safety and environmental protection requirements of the applicable EC directives.



cULus: This certification mark is based on the UL508 ; Standard for Industrial Control Equipment. The UL508 covers industrial control devices and devices accessory for starting, stopping, regulating, controlling, or protecting electric motors. In addition, UL508 also covers devices rated 1500 volts or less. Industrial control equipment covered by these requirements is intended for use in an ambient temperature of 0 – 40°C (32 – 104°F)



cRUus: This certification mark is based on the UL60950-1 ; Information Technology Equipment - Safety - Part 1. The UL60950-1 is applicable to mains-powered or battery-powered information technology equipment, including electrical business equipment and associated equipment, with a RATED VOLTAGE not exceeding 600 V.



Parallel Operation: Enable the use of 2 identical Power Supply units to be connected in Parallel to double the output current.



Power Boost: Increase the power output between 110% to 150% for a short period of time to sustain the initial load operations.



Compact dimension: The footprint is greatly reduced with this range, saving up to 50% space when compared to others.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Carlo Gavazzi:](#)

[SPDC242401](#) [SPDC121201](#) [SPDC241201](#) [SPDC244801](#) [SPDM121201](#)