NRGC-PN





NRG controller with PROFINET Communication





Main features

- Communication interface. The NRG controller bridges the field level devices to the control level to allow exchange of data in real-time with the NRG solid state relays.
- Reduced maintenance costs and downtime. Use of real-time data for prevention of machine stoppages during operation.
- Good quality products and low scrap rates. Real-time monitoring allows timely decisions for better machine and process management.
- Reduced efforts in troubleshooting. A number of faults can be distinguished to facilitate and reduce troubleshooting time.
- Fast installation and set-up. Control, monitoring and diagnostics all possible via the communication system.
- Compact dimensions. One controller with a product width of 35 mm can handle up to 32 RG..CM..N solid state relays.



Description

The NRGC-PN is the NRG controller in the NRG BUS chain.

The **NRGC-PN** interfaces directly with the main controller of the system through PROFINET communication. Each **NRGC-PN** in the system is identified by a unique MAC address which is printed on the façade of the product.

The **NRGC-PN** is mainly a facilitator of the communication between the main controller and each individual RG..N solid state relay in the system. The **NRGC-PN** also performs internal operations to setup and maintain the internal bus.

The **NRGC-PN** needs to be supplied with 24 VDC. LEDs on the front facade give a visual indication of the status of the **NRGC-PN**, of any ongoing communication with the main controller and the RG..Ns on the BUS chain and of any alarm condition related specifically to the **NRGC-PN**.

Specifications are noted at 25°C unless otherwise specified.



Applications

Any heating application where reliable and precise maintenance of temperatures is crucial to the quality of the end product. Typical applications include plastic machinery such as injection machines, extrusion machines and PET blow moulding machines, packaging machinery, sterilisation machinery, drying tunnels and semiconductor manufacturing equipment.




Main function

- Communication interface: PROFINET
- Connects up to 32 RG..CM..Ns
- Supply voltage 24 VDC +/-20%



The NRG system



System Overview

The NRG is a system consisting of one or more BUS chains that enable communication between the field devices (such as the solid state relays) and the control devices (such as the machine controller or PLC).

Each NRG BUS chain consists of the following 3 components:

- · the NRG controller
- the NRG solid state relay(s)
- the NRG internal BUS cables

The **NRG controller** is the interface to the machine controller. It acts as the master of the BUS chain when performing specific actions on the respective BUS chain, and acts as a gateway for the communication between the PLC and the RG..N solid state relays. It is not possible to operate the NRG system without the NRG controller.

The NRG controllers available are:

• NRGC

The NRGC is an NRG controller with a Modbus RTU interface over RS485. The NRGC is addressed via the assigned Modbus ID (from 1-247). In an NRG system operating on Modbus it is possible to have 247 NRG BUS chains.

NRGC-PN

NRGC-PN is an NRG controller with a PROFINET communication interface. The NRGC-PN is identified by a unique MAC address which is printed on the facade of the product. The GSD file can be downloaded from www. gavazziautomation.com

NRGC-EIP

NRGC-EIP is an NRG controller with an EtherNet/IP communication interface. The IP address is provided automatically via a DHCP server. The EDS file can be downloaded from www.gavazziautomation.com





System Overview - continued

The **NRG solid state relay** is the switching component in the NRG system. Each **RG..N** integrates a communication interface to exchange data with the machine controller (or PLC). The available RG..Ns that can be used in an NRG system are:

RG..D..N

The RG..D..N are solid state relays for use in an NRG system having the communication interface only for real time monitoring. Control of the RG..N is done via a DC control voltage. It is possible to have maximum 48 **RG..D..Ns** in one NRG BUS chain.

RG..CM..N

The RG..CM..N are solid state relays for use in an NRG system having a communication interface for control of the RG..N through the BUS and for real time monitoring. It is possible to have a maximum of 32 RG..CM..N in one NRG bus chain. There are two variants of the RG..CM..N:

RGx1A..CM..N - the solid state relay with zero cross switching

RGx1P..CM..N - the solid state relay with proportional switching.

For a review of the features available in both variants refer to the table below:

Feature	RGx1ACMN	RGx1PCMN
External control	•	-
ON / OFF switching	•	•
Burst switching	•	•
Distributed full cycle switching	•	•
Advanced full cycle switching	•	•
Phase angle	-	•
Soft start with time mode	-	•
Soft start with current limit mode	-	•
Voltage compensation	-	•
Monitoring of system parameters	•	•
SSR diagnostics	•	•
Load diagnostics	•	•
Overtemperature protection	•	•

It is not possible to mix RG..D..N and RG..CM..N in the same BUS chain.

The **NRG** internal **BUS** cables are proprietary cables that connect the NRG controller to the first RG..N in the NRG BUS chain and respective RG..Ns on the BUS. The internal BUS terminator, provided in the same package with the NRG controller, shall be plugged to the last RG..N in the NRG BUS chain.



NRG system required components

Description	Component code	Notes
Solid state relays	RGN	NRG solid state relays
NRG controller	NRGC	 NRGC: NRG controller with Modbus communication. NRGC-PN: NRG controller with PROFINET communication. NRGC-EIP: NRG controller with EtherNet/IP communication. 1x RGN-TERMRES is included in the NRGC packaging. The RGN-TERMRES is to be mounted on the last RGN on the bus chain.
NRG internal BUS cables	RCRGN-xxx	Proprietary cables terminated at both ends with a micro USB connector

NRGC-PN



List of contents

IRGC-PN	
References	
Structure	6
General data	7
Dimensions	7
Power supply specifications	7
Auto-addressing	8
Communications	9
Internal bus	
Compatibility and conformance	10
Environmental specifications	11
LED indicators	11
Alarm management	12
Connection diagram	13
Mounting	14
Connection specifications	15
OCPGN	16





References



Order code



NRGC-PN



Carlo Gavazzi compatible components

Description	Component code	Notes
Solid state relays	RGCMN	NRG solid state relays RGCMN: Communication interface for control of the RGN and for real time monitoring. Maximum 32x RGCMN in one BUS chain.
NRG Internal BUS cables	RCRGN-010-2	10cm cable terminated at both ends with a microUSB connector. Packed x4 pcs.
	RCRGN-075-2	75cm cable terminated at both ends with a microUSB connector. Packed x1 pc.
	RCRGN-150-2	150cm cable terminated at both ends with a microUSB connector. Packed x1 pc.
	RCRGN-350-2	350cm cable terminated at both ends with a microUSB connector. Packed x1 pc.
	RCRGN-500-2	500cm cable terminated at both ends with a microUSB connector. Packed x1 pc.


Further reading

Information	Where to find it	
User manual NRG PROFINET	http://www.gavazziautomation.com/docs/mt_gh/SSR_UM_NRG_PN.pdf	
Datasheet RGCMN solid state relay with control and real time monitoring via bus	http://www.gavazziautomation.com/docs/mt_gh/SSR_RG_CM_N.pdf	
GSDML file	http://www.gavazziautomation.com/images/PIM/OTHERSTUFF/GSDML/GSDML_NRGC-PN.zip	





Structure



Element	Component	Function
Us+ Us-	Supply connection	2 position spring plug – Us-, Us+ connection for powering the NRGC-PN
Push button	Communications check & Autoaddressing button	Enables and disables a Communications Check function of the BUS chain (link between NRGC-PN and RGNs) by pressing front button between 2 to 5 seconds Enables auto addressing of RGNs when pressed for 3 seconds during power up. Check 'Autoaddressing' section for more info.
MAC address	Device MAC address	Increment by 1 and 2 for MAC addresses of X1 and X2
ON LED	ON indicator	Indicates presence of Supply voltage on NRGC-PN
BUS LED	BUS indicator	Indicates ongoing communication with RGNs
SF LED	System Fault indicator	Indicates the presence of an alarm on the system
BF LED	Bus Fault indicator	Indicates issues with data exchange and PROFINET configuration
ALARM LED	ALARM indicator	Indicates presence of an alarm condition
Link / RX / TX LEDs	Link/Activity indicators	Indicates the status of the physical ethernet connection
X1, X2	PROFINET ports	2x RJ45 plugs for PROFINET communication
BUS	Micro-USB port – internal BUS	RCRGN cable connection for the internal BUS communications line




Features


General data

Material	Noryl (UL94 V0), RAL7035
Mounting	DIN rail
Dimensions	2-DIN
Touch protection	IP20, IP00 with door flap on front facade open
Weight	142g
l ('omnatinility	RGCCMN solid state contactors (RG end-devices) RGSCMN solid state relays (RG end-devices)

Dimensions



All dimensions in mm. Tolerances +/- 0.5 mm.



Performance



Power supply specifications


Supply port rating, Us	24 VDC
Supply voltage range, Us	19.2 – 32 VDC*
Reverse polarity protection	Yes
Consumption	< 12 W
LED Indication, Supply ON	Green LED
Power on	2 seconds

 $^{\ast}\,$ to be supplied by class 2 power source according to UL1310



Auto-addressing

The RG..Ns on the bus chain are automatically addressed upon the first start-up of the system. The RG..Ns are addressed based on their position on the bus chain.



In case of an RG..N replacement, or any changes to the NRG bus chain, the RG..Ns have to be re-addressed. Follow the procedure below to re-address the RG..Ns on the NRG bus chain manually. Alternatively, auto-addressing can be done via an acyclic command (check NRG PROFINET User Manual for further information)



Fig. 1 Hold the blue button while powering up the NRGC-PN



Fig. 2 Release when Alarm LED turns ON indicating that autoaddressing is complete



Communication

Communication protocol to Main Controller	PROFINET
GSD file	The PROFINET GSDML file for NRGC-PN is available electronically by going to www.gavazziautomation.com
Addressing	The MAC address of the device is listed on the façade of the NRGC-PN. Each physical Ethernet Port (X1, X2) has its own MAC address. X1 uses the device MAC address incremented by one and for X2 increment the device MAC address by two.
Connection to main controller	The PROFINET ports (X1, X2) are 100 Mbit, full duplex operation ports and should be connected to another PROFINET device with Cat5e (straight through) cable via the standard RJ45 connector (maximum length 100 m). The interconnecting cables should be fitted with plugs provided with an outer metallic shell with the shell connected to the wire screen of the cable.
LED indication - TX, RX	Yellow, Flashing - NRGC-PN is sending/receiving Ethernet frames
LED indication - Link	Green, ON - Device is linked to Ethernet

Internal Bus

Max. number of RGNs connected to NRGC	32x RGCMN
Connection to RGNs	RCRGN-xx 5-way cable terminated with micro-USB connection
BUS termination	RGN-TERMRES (1x pc. provided with 1x NRGC-PN) to be plugged on the last RGN on the BUS chain to terminate the internal BUS
LED indication - BUS	Yellow, ON indicating ongoing communication with the RG end-devices



Compatibility and Conformance

Approvals (pending)	
Standards compliance	LVD: EN 60947-5-1 EMCD: EN 60947-5-1 UL: UL508, E172877, NMFT cUL: C22.2 No. 14-18, E172877, NMFT7

Electromagnetic compatibility (EMC) - Immunity		
Electrostatic discharge (ESD)	EN/IEC 61000-4-2 8 kV air discharge, 4 kV contact (PC1)	
Radiated radio frequency	EN/IEC 61000-4-3 10 V/m, from 80 MHz to 1 GHz (PC1) 10 V/m, from 1.4 to 2 GHz (PC1) 3 V/m, from 2 to 2.7 GHz (PC1)	
Electrical fast transient (burst)	EN/IEC 61000-4-4 Input: 1kV , 5kHz & 100kHz (PC1) Internal bus: 1kV , 5kHz & 100kHz (PC1) PROFINET ports: 1kV , 5kHz & 100kHz (PC1) 2kV , 5kHz & 100kHz (PC2)	
Conducted radio frequency	EN/IEC 61000-4-6 10 V/m, from 0.15 to 80 MHz (PC1)	
Electrical surge	EN/IEC 61000-4-5 DC Output / Input, line to line: 500 V (PC2) DC Output / Input, line to earth: 500 V (PC2) Signal, line to earth 1 kV (PC2) ¹	
Voltage dips and interruptions	EN/IEC 61000-4-11 0% @ 5000 ms (PC2) 40% @ 200 ms (PC2) 60% @ 10, 30, 100, 300, 1000 ms (PC2)	
Voltage dips and interruptions on input lines	EN/IEC 61000-4-29 0% @ 1, 3, 10, 30, 100, 300, 1000 ms (PC2) 30% @ 10, 30, 100, 300, 1000 ms (PC2) 70% @ 10, 30, 100, 300, 1000 ms (PC2) 80% @ 10, 30, 100, 300, 1000 ms, 3 s, 10 s (PC2) 120% @ 10, 30, 100, 300, 1000 ms, 3 s, 10 s (PC2)	

1. Not applicable to shielded cables <10m. Additional suppression on data lines may be required if shielded cables are not used.

Electromagnetic compatibility (EMC) - Emissions		
Radio interference field emissions (radiated) EN/IEC 55011 Class A: from 30 to 1000 MHz		
Radio interference voltage emissions (conducted)	EN/IEC 55011 Class B: from 0.15 to 30 MHz	



Environmental specifications

Operating temperature	-20 to +65 °C (-4 to +149 °F)		
Storage temperature	-20 to +65 °C (-4 to +149 °F)		
Relative humidity	95% non-condensing @ 40°C		
Pollution degree	2		
Installation altitude	0 - 2000m		
EU RoHS compliant	Yes		
China RoHS			

LED indicators

	1	i e e e e e e e e e e e e e e e e e e e		
ON	Green	ON:	Us is present at terminals Us+, Us-	
ON		OFF:	Us is not present at terminals Us+, Us-	
Link	(-ireen		Device is linked to Ethernet	
(X1 & X2)			Device has no link to Ethernet	
	Yellow	ON:	During transmission of messages from NRGC-PN to RGNs	
BUS		OFF:	Idle bus between the NRGC-PN and RGNs and when NRGC-PN is receiving	
		OFF:	data from RGNs	
TX/RX		OFF:	No frames are being sent/received	
(X1 & X2)	Yellow	Flashing:	NRGC-PN is sending/receiving Ethernet frames	
	Red _	ON:	Flashing when alarm condition on NRGC-PN is present. Refer to Alarm	
ALARM			management section	
		OFF:	No alarm condition	
	Red _	ON:	Alarm is present in the system	
SF		OFF:	No error	
		Flashing:	DCP signal service is initiated	
	Red _	ON:	No configuration	
BF		OFF:	No error	
		Flashing:	No data exchange	



Alarm management

Alarm condition present	ALARM LED ON with a specific flashing rate Alarms are available as diagnostics messages via the PROFINET Diagnostic System. Refer to NRG PROFINET User Manual for further information		
Alarm types	arm types No. of Description flashes of fault		
	2	 Errors in the configurations of the internal NRG bus chain including: Number of RGNs on bus chain is > 32 (Device Limit Error) More than one RGN on the bus chain have the same address (Device conflict error) One of the RGNs does not have an address this may occur when a new RGN is introduced to the bus chain (Device Unconfigured Error) The internal Device ID of one of the RGNs on the bus chain does not correspond to its position on the bus (Device Position Error) 	
	Supply Error: Supply to NRGC-PN is outside of the specified range		
	8	Communication Error (BUS): An error in the communication link (internal BUS) between the NRGC-PN and RGNs	
	9	Internal Error: Detection of internal issues with the NRGC-PN	
	10	Termination (BUS) Error: Internal BUS chain not terminated	
Flashing rate	0.5s →	<u>3s</u> ■ ■	



Connection diagram

The NRG bus chain can be configured in a PROFINET network via a line, ring (support of Media Rudandancy Protocol), star or tree toplogies via the ethernet ports on the NRGC-PN.




Fig. 3 Example of a line configuration of the NRGC-PN with other PROFINET devices and controller






Fig. 4 Example of a star configuration of the NRGC-PN with other PROFINET devices and controller



Mounting









Connection specifications

Power connection		
Terminal	Supply: Us+, Us-	
	Top	
Conductors	Use 60/75°C copper (Cu) conductors	
Stripping length	12 - 13 mm	
Connection type	2-pole spring plug, pitch 5.08 mm	
Rigid (solid & stranded) UL/CSA rated data	0.2 – 2.5 mm², 26 – 12 AWG	
Flexible with end sleeve	0.25 – 2.5 mm ²	
Flexible without end sleeve	0.25 – 2.5 mm ²	
Flexible with end sleeve using TWIN ferrules	0.5 – 1.0 mm ²	

Communication - connection			
Terminal	X1, X2: RJ45 (x2) BUS: RCRGN-xxx-2		
	Bottom view		
PROFINET connection	RJ45 shielded plugs		
Cable for PROFINET	Not provided. Shielded CAT-5e straight cables.		
Max. length of ethernet cable	100 mtrs (between PROFINET devices)		
Cable for Internal Bus	RCRGN-xxx-2: 5-way USB micro connection - +24 supply line for RGNs - GND - RS485A - RS485B - Autoconfig / Auto addressing line		

RCRGN...



NRG internal BUS cable



Main features

- Cables available at various lengths to provide the internal BUS of the NRG system
- Cables terminated at both ends with a microUSB plug
- Connects the NRG controller to the RG..N solid state relay and respective RG..N solid state relays

D

Description

The **RCRGN** cables are proprietary cables that must be used with the NRG system for the internal BUS. These cables connect the NRG controller to the RG..N solid state relays and respective RG..N solid state relays.

The RCRGN... are 5-way cables carrying the communication, supply and autocofiguration lines. By means of autoconfiguration, the RG..Ns are assigned a unique ID based on the physical location and hence internal BUS wiring sequence when an autoconfiguration command is sent to the RG..Ns.

Carlo Gavazzi compatible components

Description	Component code	Notes
NRG Controller	NRGC	 NRGC: NRG controller with Modbus communication. NRGC-PN: NRG controller with PROFINET communication. NRGC-EIP: NRG controller with EtherNet/IP communication. 1x RGN-TERMRES is included in the NRGC packaging. The RGN-TERMRES is to be mounted on the last RGN on the bus chain.
Solid state relays	RGN	NRG solid state relays

Order code



RCRGN -

Enter the code entering the corresponding option instead of lacksquare

Code	Option	Description	Notes	
R		Cables		
С		Cables		
R				
G		Suitable for the NRG system		
N				
	010	10cm cable length	packed x 4 pcs.	
	075	75cm cable length	packed x 1 pc.	
	150	150cm cable length	packed x 1 pc.	
	350	350cm cable length	packed x 1 pc.	
	500	500cm cable length	packed x 1 pc.	
2		Terminated at the both ends with a microUSB connector		





COPYRIGHT ©2021 Content subject to change. Download the PDF: https://gavazziautomation.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Carlo Gavazzi: