

USED IN ASSEMBLY	MATING CONFIG DETAIL	MATING NON-DELPHI PART NUMBER	MATING DELPHI PART NUMBER	PREVIOUS PART NUMBER
-	15471275	-	-	-

ASSOCIATED PARTS		
PART NUMBER	QTY	DESCRIPTION
15410978	1	COV WIRE DRESS BLU
15404997	1	LOCK SECONDARY TPA MICRO BLU DK
15410977	1	LOCK SECONDARY TPA GT BLU
15357145	1	LOCK CPA GT TETHER RED
M1842011	1	MOUN WIRE TIE

CAVITY INFORMATION					
CAVITY NAME	TERMINAL	CABLE SEAL	CAVITY PLUG	*INSULATION CRIMP HEIGHT	*INSULATION CRIMP WIDTH
49	15392777	12191235	15305170	-	-
1-48	15356826	-	15356825	2.05	2.05

SEE NOTE 1

SEE NOTE 2

NOTES

- CABLE O.D. RANGE IS 1.90/1.47 DIA FOR MICRO 64 TERMINAL. 18 GAGE REQUIRES USAGE OF ULTRA THIN WALL CABLE.
- ICH AND ICW REPRESENT DIAMETRIC VALUES.

APPLICATION DRAWING
UNLESS OTHERWISE SPECIFIED
WHEN APPLICABLE, EQUIVALENT PART NUMBERS MAY BE SUBSTITUTED FOR ANY OF THE PART NUMBERS SHOWN IN THE CHARTS ON THIS DRAWING.
* THE VALUES REPRESENT THE CAVITY CAPABILITIES. THE ACTUAL TERMINAL CRIMP DIMENSIONS MUST BE LESS THAN THE VALUES SHOWN.

DELPHI	
DELPHI PACKARD ELECTRICAL/ELECTRONIC ARCHITECTURE WARREN, OH	
APVD1 JOSE LUIS TAPIA	DATE 28SE07
APVD2 ALFREDO ROJAS	28SE07
PUBLISHED DATE 31OC07	
DRAWING NAME ASM CONN 49 F GT 280 MICRO 64 SLD MODULAR	
DRAWING NUMBER 15463921	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Aptiv:](#)
[15463921](#)