








SYMBOL DEFINITION		
A DIMENSION WITHOUT AN INSPECTION REPORT SYMBOL  DOES NOT REQUIRE INSPECTION. IT MAY BE CONTROLLED ON THE INDIVIDUAL COMPONENT DRAWING.	TOTAL NO OF INSPECTIONS REQUIRED	61
	LAST NO. USED	22

MISSING SYMBOLS					DWG STATUS		ZONE	REVISION HISTORY	AUTH	DR	APVD 1	APVD 2
DATE	STG	REV	N/P	CHG								
28MR01	R	001	-	-				15355359 WAS SEPERATE DRAWING, 15410209 RELEASED	208294	CJC	CJC	CAM
29N001	R	002	-	-				UPDATED TOLERANCES	217960	CJC	CJC	CAM
26FE03	R	03	-	-				ALL PARTS - REVISED MATL SPEC WAS R0071790; DIMS WERE 8X 7.15 & 8X 3.58; 15410209 - DIM WAS 2X R3	237366	MAC	MAC	MP





NOTES

- UNLESS OTHERWISE SPECIFIED AND/OR INDICATED: DIMENSIONS ARE TO FACE OF VIEW SHOWN AND AUTOMATICALLY ROUNDED BY COMPUTER FOR INSPECTION. (SEE MATH MODEL FOR PRECISE DIMENSIONS.) FOR ALL OTHER DIMENSIONS NOT SHOWN BUT REQUIRED FOR TOOL BUILD, SEE MATH MODEL FOR PRECISE TOOL PATH DATA.
- MATING COMPONENTS OR EQUIVALENT: CONNECTOR 15366099
- TPA IS DESIGNED FOR USE WITH 2-RIB CABLE SEALS AS SHOWN ON 12191227 OR EQUIVALENT.
- MATERIAL RECYCLING CODE >PA66< PER SAE J1344. (2.3)X(0.1) RAISED CHARACTERS AS SHOWN TO BE LOCATED ON ANY EXTERIOR SURFACE. OPTIONAL CONSTRUCTION TO BE NO MATERIAL RECYCLING CODE.
- (2.3)X(0.1) RAISED DELPHI CORPORATE BRAND TO BE LOCATED ON ANY EXTERIOR SURFACE, PREFERABLY VISIBLE AT FINAL ASSEMBLY. OPTIONAL CONSTRUCTION TO BE "PED" OR NO LOGO.



15410209	01	AB	ACTIVE	102	M3592008 PA66 HS IM BLU	4.223
15355359	02	AC	ACTIVE	101	M3592008 PA66 HS IM BLU	3.312
PART	NO	REV	N/P	STATUS	TYPE	MATERIAL SPECIFICATION AND COLOR

		R 0.1 MAX		R 0.2 MAX		SHARP CORNER TOLERANCE		2 PROCESS SENSITIVE DIMENSION	
								DIMENSIONS ENCLOSED IN () INDICATE REFERENCE DIMENSIONS AND NO TOLERANCE LIMITS ARE ESTABLISHED	
DIMENSIONAL RANGE (MM)								CHART E1	
FROM	> 0	> 20	> 30	> 70	> 100	> 150	> 200	> 250	> 300
TO	20	30	70	100	150	200	250	300	400
TOLERANCE UNLESS OTHERWISE SPECIFIED									
	±0.15	±0.2	±0.3	±0.4	±0.5	±0.6	±0.8	±1	±1.2
ANGULAR TOLERANCE ±2°									

DWG TYPE		PART DRAWING	
STYLE			
VOLUME (CM³)		DISTR CODE	
SEE CHART		D	
ROUTING			
6900			
UNLESS OTHERWISE SPECIFIED			
THIS DOCUMENT IS IN ACCORDANCE WITH ASME Y14.5M-1994 AS AMENDED BY THE GM GLOBAL DIMENSIONING AND TOLERANCING ADDENDUM - 1997. ALL GEOMETRIC TOLERANCES AND RELATED DATUMS APPLY RFS. RULE #1 (PERFECT FORM AT MMC) DOES NOT APPLY WHEN RELATIONSHIP BETWEEN FEATURES IS ESTABLISHED BY ORIENTATION OR LOCATION TOLERANCES. SEPARATE POSITION CALLOUTS MAY BE GAGED SEPARATELY, REGARDLESS OF DATUM REFERENCE.			
ALL DIMENSIONS ARE IN MILLIMETERS			
REFERENCE			
THIRD ANGLE PROJECTION		DO NOT SCALE	
		USE MATH DATA	
			

DELPHI				
DELPHI PACKARD ELECTRIC SYSTEMS WARREN, OH				
			DATE	
DR	CRAIG COGGINS		28MR01	
APVD1	CRAIG COGGINS		28MR01	
APVD2	CRAIG COGGINS		30MR01	
APVD3	COURTNEY MANSKY		04AP01	
APVD4				
APVD5				
SUBSTANCES OF CONCERN AND RECYCLED CONTENT PER DELPHI 10949001				
MATERIAL SEE CHART				
DRAWING NAME				
TAXI LOCK TPA GT 150 280 16 N/A				
DRAWING NUMBER				
15410213				
SIZE	SCALE	FRAME NO	SHEET NO	STG
A1	2:1	1 OF 1	1 OF 1	R
				REV
				03
				N/P
				-

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Aptiv:](#)

[15410209](#)