


Quectel SC600T

Multi-mode Smart LTE Module with Wi-Fi & Bluetooth



SC600T is Quectel's new generation of multi-mode Smart LTE Cat 6 module with built-in Android 9.0 OS. Based on Qualcomm octa-core and 64-bit high-performance processors with built-in Adreno[™] 506 GPU, SC600T is designed to support leading performance, various multimedia features and Quick Charge 3.0 technology. It is ideal for both industrial and consumer applications with high data-rate and multimedia functions. SC600T is available in four variants: SC600T-NA*, SC600T-EM*, SC600T-JP* and Wi-Fi & BT only version SC600T-WF*.

SC600T supports multiple-input multiple-output (MIMO) technology. The use of multiple antennas at the receiver end at the same time and on the same frequency band greatly minimizes errors and optimizes the data speed. This module also combines high-speed wireless connectivity with embedded multi-constellation and high-sensitivity GNSS (GPS, GLONASS and BeiDou) receiver for positioning.

A rich set of interfaces (such as LCM, Camera, Touch Panel, MIC, SPK, UART, USB, I2C, SPI) extend the applicability of the module to a wide range of M2M applications, including smart POS, smart cash registers, smart home gateways, smart robots, smart wearables, security surveillance, PDA & tablets, vending machines, delivery lockers, police and law enforcement equipment, in-car video streaming and entertainment systems, etc.



Key **Benefits**

- ✓ LTE Cat 6 modem supporting 2x20MHz carrier aggregation, with maximum download speed up to 300Mbps
- ✓ Worldwide LTE, UMTS/HSPA+ and GSM/GPRS/EDGE coverage
- Dual LCDs and dual touch panels for independent display and operation: 1920x1200 @60fps for primary display and 1920x1080 @60fps for secondary display
- Support up to four cameras, with two of them working simultaneously
- ✓ Multi-constellation GNSS receiver available for applications requiring fast and accurate fixes in any environment
- ✓ Support recording and playback of 4k videos at 30fps



ARM Cortex-A53 64-bit Processor (Octa-core)



Smart LTE Cat 6 Max 300Mbps (DL) Max 50Mbps (UL)



GPS+GLONASS+ BeiDou



Adreno[™] 506 GPU









BT4.2 (BR/EDR+BLE)



Powerful Multimedia Function




ICC+IGA Package

Rev.: V1.0 | Status: Released

Quectel SC600T

Multi-mode Smart LTE Module with Wi-Fi & Bluetooth





Variant for EMEA/India/Korea/Taiwan/South Asia/Latin America/Australia/New Zealand

SC600T-EM*:

LTE FDD: B1/B2/B3/B4/B5/B7/B8/B20/B28

LTE TDD: B38/B39/B40/B41 WCDMA: B1/B2/B4/B5/B8 GSM: 850/900/1800/1900MHz

Variant for North America

SC600T-NA*:

LTE FDD: B2/B4/B5/B7/B12/B13/B14/B17/B25/

B26/B66/B71 LTE TDD: B41 WCDMA: B2/B4/B5

Variant for Japan

SC600T-JP*:

LTE FDD: B1/B3/B5/B8/B11/B18/B19/B21/B26/

ITF TDD: B41

WCDMA: B1/B6/B8/B19
Variant for the Global

SC600T-WF*:

Only Support Wi-Fi & BT

Data

LTE:

Cat 6 FDD: Max 300Mbps (DL)/Max 50Mbps (UL)
Cat 6 TDD: Max 265Mbps (DL)/Max 35Mbps (UL)

UMTS

DC-USDPA: Max 42Mbps (DL)
DC-HSUPA: Max 11.2Mbps (UL)
WCDMA: Max 384Kbps (DL/UL)

GSM:

GPRS: Max 107Kbps (DL)/85.6Kbps (UL) EDGE: Max 296Kbps (DL)/236.8Kbps (UL)

Electrical Characteristics

Supply Voltage: 3.55V~4.4V, 3.8V Typ. Consumption: 70uA @power off 3.6mA @sleep, Typ.

Output Power:

Class 4 (33dBm±2dB) for GSM850
Class 4 (33dBm±2dB) for EGSM900
Class 1 (30dBm±2dB) for DCS1800
Class 1 (30dBm±2dB) for PCS1900
Class E2 (27dBm±3dB) for GSM850 8-PSK
Class E2 (27dBm±3dB) for EGSM900 8-PSK
Class E2 (26dBm±3dB) for DCS1800 8-PSK

Class E2 (26dBm±3dB) for PCS1900 8-PSK Class 3 (24dBm+1/-3dB) for WCDMA bands Class 3 (23dBm±2dB) for LTE-FDD bands

Class 3 (23dBm±2dB) for LTE-TDD bands

Sensitivity:

TBD

Audio & Video

VolTE

Crystal Clear VoLTE with Ultra HD Voice and

SRVCC/CSFB

High Fidelity Music Playback of 24-bit/192kHz

Video: Encode:

3840x2160 @30fps (HEVC/H.264)

1080p @30fps (MPEG-4/VP8)

864x480 @30fps (H.263)

Decode:

3840x2160 @30fps (HEVC/H.264,VP8/VP9)

1080p @60fps (VC-1/MPEG-4/)

1080p @30fps (DivX4.x/5.x/6.x,MPEG-2)

864x480 @30fps (H.263) 720x480 @30fps (DivX3.11)

Wi-Fi Display Supports up to 1080P at 30fps for

Encoding and Decoding

Interfaces

LCM:

4-lane MIPI_DSI0 + 4-lane MIPI_DSI1 WUXGA (1920×1200) @60fps

WUXGA (1920×1200) @60tps

Camera

3 Groups of 4-lane MIPI_CSI, up to 2.1Gbps/Lane

Support 3 or 4 Cameras
Up to 24MP with Dual ISPs

Touch Panel:

Capacitive Touch Panel

Audio:

Speaker, Earpiece, Headphone, and 3 MICs for

Analog Audio

Support One Noise-canceling MIC

USB

Compliant with USB 3.0/2.0 , Support USB OTG

12C: × 5

(U)SIM: $\times 2 (1.8V/2.95V)$

 $\textbf{UART:} \times \textbf{3} \text{ (Support 4Mbps with Hardware Flow}$

Control)

SD Card: × 1 (3.0, 4-bit SDIO)

PWRKEY: 1.8V, Pulled-up Internally

SPI: × 2 (Can be Multiplexed into UART and I2S Respectively, and I2S Supports Both Tx and Rx)

ADC: × 2
GPIO: × 19
Motor Drive: × 1
Flash Driver: × 2
LED Sink: × 4

Antenna: 4 Solder Pads for Main/Rx-diversity/ GNSS/Wi-Fi & BT Antennas, Respectively

Enhanced Features

WI AN:

2.4G/5G, 802.11 a/b/g/n/ac

Bluetooth:

BT2.1+EDR/3.0/4.1 LE/4.2 BLE

GNSS: GPS/GLONASS/BeiDou

Cat 6 Modem with 2x20MHz CA Support Rx-diversity , DL MIMO 2 × 2

Support 3GPP E-UTRA Release 12

Bandwidth: 1.4/3/5/10/15/20MHz Built-in Charge IC & Fuel Gauge,

Qualcomm Quick Charge 3.0 (Optional)

Support Dual LCDs for Independent Display

Support Dual SIM Dual Standby Firmware Upgrade via USB Interface

General Features

OS: Android 9.0

Memory:

16GB eMMC+2GB LPDDR3 (Default)
32GB eMMC+4GB LPDDR3 (Optional)

Operating Temperature: -35° C $\sim +65^{\circ}$ C Dimensions: 43.0mm \times 44.0mm \times 2.85mm

Package: LCC+LGA Weight: Approx. 13.0g

* Under Development



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Quectel:

SC600TJPPA-E53-UGADA SC600TNAPD-E61-UGADA SC600TNANA-E53-UGADA SC600TEMPA-E53-UGADA SC600TWFPA-E53-UNNNA SC600TEMPA-E53-UGADA SC600TWFPD-E61-UNNNA SC600TEMPA-E53-TA0AA SC600TWFPA-E53-TA0AA SC600TWFPA-E53-TA0AA