



BAS70 SERIES

SURFACE MOUNT SCHOTTKY DIODES

VOLTAGE 70 Volt **CURRENT** 0.2 Ampere


FEATURES

- Fast switching speed
- Surface mount package ideally suited for automatic insertion
Electrical identical standard JEDEC
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Green molding compound as per IEC61249 Std. .
(Halogen Free)

MECHANICAL DATA

- Case: SOT-23, Plastic
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0003 ounces, 0.008 grams

SOT-23 Unit : inch(mm)




ABSOLUTE RATINGS

| Parameter | Symbol | Value | Units |
|--|-------------|-------|-------|
| Reverse Voltage | V_R | 70 | V |
| Peak Reverse Voltage | V_{RRM} | 70 | V |
| Average Rectified Current at Temp=25°C | $I_{F(AV)}$ | 0.2 | A |
| Non-repetitive Peak Forward Surge Current at t=1.0 s | I_{FSM} | 0.6 | A |

THERMAL CHARACTERISTICS

| Parameter | Symbol | BAS70 | BAS70A | BAS70C | BAS70S | Units |
|---|-----------------|------------|--------------|----------------|--------|-------|
| Marking code | - | A70 | A72 | A73 | A74 | - |
| Power Dissipation | P_D | 225 | | | | mW |
| Thermal Resistance , Junction to Ambient (Note 1) | $R_{\theta JA}$ | 556 | | | | °C/W |
| Operating Junction Temperature | T_J | -55 to 150 | | | | °C |
| Operating Storage Temperature | T_{STG} | -55 to 150 | | | | °C |
| Circuit Configuration | - | SINGLE | COMMON ANODE | COMMON CATHODE | SERIES | - |

Note : 1. Mounted on min pad conditions using FR-4 PCB





BAS70 SERIES

ELECTRICAL CHARACTERISTICS

| Parameter | Symbol | Test Condition | Min. | Typ. | Max. | Units |
|------------------------------|------------|---|------|------|----------------------|---------|
| Reverse Breakdown Voltage | $V_{(BR)}$ | $I_R=10 \mu A$ | 70 | -- | -- | V |
| Reverse Current | I_R | $V_R=70 V$ $V_R=50 V$ | -- | -- | 1.0 0.1 | μA |
| Forward Voltage | V_F | $I_F=1.0mA$ $I_F=10mA$ $I_F=15mA$ | -- | -- | 0.41 0.75 1.00 | V |
| Maximum Junction Capacitance | C_J | $V_R=0V, f=1.0MHz$ | -- | -- | 2.0 | pF |



BAS70 SERIES




FIG. 1 TYPICAL FORWARD CHARACTERISTIC




FIG. 2 TYPICAL REVERSE CHARACTERISTICS




FIG. 3 TYPICAL JUNCTION CAPACITANCE




FIG. 4 FORWARD CURRENT DERATING




Fig.5 Operating Temperature Derating Curve




BAS70 SERIES

MOUNTING PAD LAYOUT

SOT-23

Unit : inch(mm)



ORDER INFORMATION

- Packing information
 - T/R - 12K per 13" plastic Reel
 - T/R - 3K per 7" plastic Reel



BAS70 SERIES

Part No_packing code_Version

BAS70_R1_00001

BAS70_R2_00001

For example :

RB500V-40_R2_00001



| Packing type | Packing Code XX | | | Version Code XXXXX | | |
|--------------------------------------|------------------------|----------------------------------|----------------------|---------------------------|----------------------|---------------------------------------|
| | 1 st Code | Packing size code | 2 nd Code | HF or RoHS | 1 st Code | 2 nd -5 th Code |
| Tape and Ammunition Box (T/B) | A | N/A | 0 | HF | 0 | serial number |
| Tape and Reel (T/R) | R | 7" | 1 | RoHS | 1 | serial number |
| Bulk Packing (B/P) | B | 13" | 2 | | | |
| Tube Packing (T/P) | T | 26mm | X | | | |
| Tape and Reel (Right Oriented) (TRR) | S | 52mm | Y | | | |
| Tape and Reel (Left Oriented) (TRL) | L | PANASERT T/B CATHODE UP (PBCU) | U | | | |
| FORMING | F | PANASERT T/B CATHODE DOWN (PBCD) | D | | | |



BAS70 SERIES

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Panjit:](#)

[BAS70S_R2_10001](#) [BAS70S_R1_10001](#) [BAS70S_R2_00001](#) [BAS70S_R1_00001](#)