

# PJSOT03C-05~PJSOT36C-05

## STANDARD CAPACITANCE TVS ARRAY


**VOLTAGE** 3 ~ 36 Volt **POWER** 500 Watt

### FEATURES

- 500 Watts Peak Pulse Power per Line (  $t_p=8/20\mu s$  )
- Low Clamping Voltage
- Available in Multiple Voltage Types Ranging from 3V and 36V
- Unidirectional & Bidirectional Configurations
- ESD IEC-61000-4-2 Air  $\pm 30kV$ , Contact  $\pm 30kV$
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard


### MECHANICAL DATA

- Case: SOT-23
- Terminals : Solderable per MIL-STD-750, Method 2026
- Weight: 0.0003 ounce, 0.0084 gram



### SOT-23

Unit : inch(mm)



### DEVICE CHATACTERISTICS

Ratings at 25°C unless otherwise specified.

| Parameter  | Symbol    | Value                | Units |
|--|-----------|----------------------|-------|
| Forward Voltage@ 100mA, 300 $\mu s$ -Square Wave       | $V_F$     | 1.5                  | Volts |
| Peak Pulse Power ( $t_p=8/20\mu s$ )                   | $P_{PP}$  | 500                  | Watts |
| ESD IEC-61000-4-2 (Air)<br>ESD IEC-61000-4-2 (Contact) | $V_{ESD}$ | $\pm 30$<br>$\pm 30$ | kV    |
| Operating Temperature Range                            | $T_J$     | -50 to 150           | °C    |
| Storage Temperature Range                              | $T_{STG}$ | -50 to 150           | °C    |

| Part Number | Reverse Stand-off Voltage | Minum Breakdown Voltage | Max Clamping Voltage @ 8/20 $\mu sec$ | Peak Pulse Current 8/20 $\mu sec$ | Maximum Leakage Current | Off-State Capacitance, 1MHz Zero dc Bias<br>Note 1 | Marking Code |
|-------------|---------------------------|-------------------------|---------------------------------------|-----------------------------------|-------------------------|--|--------------|
|             | $V_{RWM}$                 | @ 1mA $V_{BR}$          | $V_{CL}$ @ $I_{PP}$                   | $I_{PP}$                          | @ $V_{RWM}$ $I_D$       | $C_d$  |              |
|             | Max. V                    | V                       | V                                     | Max. A                            | $\mu A$                 | Max. pF  |              |
| PJSOT03C-05 | 3                         | 4                       | 6.5                                   | 43                                | 125                     | 500  | 1EC          |
| PJSOT05C-05 | 5                         | 6                       | 9.8                                   | 42                                | 20                      | 550  | 2EC          |
| PJSOT08C-05 | 8                         | 8.5                     | 13.4                                  | 34                                | 10                      | 250  | 3EC          |
| PJSOT12C-05 | 12                        | 13.3                    | 19                                    | 21                                | 2                       | 150  | 4EC          |
| PJSOT15C-05 | 15                        | 16.7                    | 24                                    | 17                                | 1                       | 100  | 5EC          |
| PJSOT24C-05 | 24                        | 26.7                    | 43                                    | 12                                | 1                       | 88   | 6EC          |
| PJSOT36C-05 | 36                        | 40                      | 75                                    | 9                                 | 1                       | 85   | 7EC          |

Note 1: Capacitance is measured between Pin 3 and either Pin 1 or 2 for the PJSOT03-05C and PJSOT36C-05 individual capacitance is measured between Pin 1 to Pin 3 or Pin2 to Pin 3.

## PJSOT03C-05~PJSOT36C-05




FIG.1- PEAK PULSE POWER VS PULSE TIME




FIG.2- PULSE WAVE FORM





FIG.3- POWER DERATING CURVE

# PJSOT03C-05~PJSOT36C-05

## MOUNTING PAD LAYOUT



## ORDER INFORMATION

- Packing information
  - T/R - 12K per 13" plastic Reel
  - T/R - 3K per 7" plastic Reel

## PJSOT03C-05~PJSOT36C-05

**Part No\_packing code\_Version**

PJSOT03C-05\_R1\_00001

PJSOT03C-05\_R2\_00001

**For example :**

**RB500V-40\_R2\_00001**

Part No.

Serial number

Version code means HF

Packing size code means 13"

Packing type means T/R

| Packing Code <b>XX</b>               |                      |                                  |                      | Version Code <b>XXXXX</b> |                      |                                       |
|--------------------------------------|----------------------|----------------------------------|----------------------|---------------------------|----------------------|---------------------------------------|
| Packing type                         | 1 <sup>st</sup> Code | Packing size code                | 2 <sup>nd</sup> Code | HF or RoHS                | 1 <sup>st</sup> Code | 2 <sup>nd</sup> ~5 <sup>th</sup> Code |
| Tape and Ammunition Box (T/B)        | <b>A</b>             | N/A                              | <b>0</b>             | HF                        | <b>0</b>             | serial number                         |
| Tape and Reel (T/R)                  | <b>R</b>             | 7"                               | <b>1</b>             | RoHS                      | <b>1</b>             | serial number                         |
| Bulk Packing (B/P)                   | <b>B</b>             | 13"                              | <b>2</b>             |                           |                      |                                       |
| Tube Packing (T/P)                   | <b>T</b>             | 26mm                             | <b>X</b>             |                           |                      |                                       |
| Tape and Reel (Right Oriented) (TRR) | <b>S</b>             | 52mm                             | <b>Y</b>             |                           |                      |                                       |
| Tape and Reel (Left Oriented) (TRL)  | <b>L</b>             | PANASERT T/B CATHODE UP (PBCU)   | <b>U</b>             |                           |                      |                                       |
| FORMING                              | <b>F</b>             | PANASERT T/B CATHODE DOWN (PBCD) | <b>D</b>             |                           |                      |                                       |



## PJSOT03C-05~PJSOT36C-05

---

### Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panjit:

[PJSOT36C-05\\_R2\\_10001](#) [PJSOT36C-05\\_R1\\_00001](#) [PJSOT36C-05\\_R1\\_10001](#) [PJSOT36C-05\\_R2\\_00001](#)