



SBA220AH / SBA230AH / SBA240AH

EXTREME LOW VF SCHOTTKY RECTIFIER

Voltage 20-40 V **Current** 2 A

Features

- Ultra low forward voltage drop, low power loss
- Fast switching speed
- Surface mount package
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Applications

- Low voltage rectification
- Reverse polarity protection
- Low power consumption applications

Mechanical Data

- Case: Molded plastic, SOD-123HE
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0006 ounces, 0.0184 grams

SOD-123HE



Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	SBA220AH	SBA230AH	SBA240AH	UNIT
Maximum repetitive peak reverse voltage	V_{RRM}	20	30	40	V
Maximum rms voltage	V_{RMS}	14	21	28	V
Maximum dc blocking voltage	V_R	20	30	40	V
Maximum average forward rectified current	$I_{F(AV)}$		2		A
Peak forward surge current: 8.3ms single half sine-wave Superimposed on rated load	I_{FSM}		30		A
Typical thermal resistance	$R_{\theta JC}^{(1)}$ $R_{\theta JA}^{(2)}$		20 185		$^\circ\text{C}/\text{W}$
Operating junction temperature range	T_J		-55 to +150		$^\circ\text{C}$
Storage temperature range	T_{STG}		-55 to +150		$^\circ\text{C}$

Electrical Characteristics

PARAMETER	SYMBOL	TEST CONDITION		SBA220AH		SBA230AH		SBA240AH		UNIT
				TYP.	MAX.	TYP.	MAX.	TYP.	MAX.	
Forward voltage	V_F	$I_F = 10\text{mA}$	$T_J = 25^\circ\text{C}$	0.21	-	0.21	-	0.22	-	V
		$I_F = 0.5\text{A}$		0.33	-	0.34	-	0.37	-	
		$I_F = 2\text{A}$		-	0.46	-	0.49	-	0.53	
		$I_F = 10\text{mA}$	$T_J = 125^\circ\text{C}$	0.09	-	0.09	-	0.1	-	V
		$I_F = 0.5\text{A}$	0.24	-	0.26	-	0.27	-		
Reverse current	$I_R^{(3)}$	$V_R = 10\text{V}$	$T_J = 25^\circ\text{C}$	14	-	9	-	7.4	-	μA
		$V_R = 20\text{V}$		-	100	25	-	9.6	-	
		$V_R = 30\text{V}$		-	-	-	100	16	-	
		$V_R = 40\text{V}$		-	-	-	-	-	100	
		$V_R = 20\text{V}$	$T_J = 125^\circ\text{C}$	6.1	-	3.7	-	2.3	-	mA
		$V_R = 30\text{V}$	-	-	9.6	-	3.5	-		
		$V_R = 40\text{V}$	-	-	-	-	5.6	-		

Note : 1. Mounted on a FR4 PCB, single-sided copper, with 100cm^2 copper pad area.

2. Mounted on a FR4 PCB, single-sided copper, mini pad.

3. Short duration pulse test used to minimize self-heating effect.



SBA220AH / SBA230AH / SBA240AH

TYPICAL CHARACTERISTIC CURVES




Fig.1 Forward Current Derating Curve




Fig. 2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Reverse Characteristics




Fig.5 Typical Reverse Characteristics




Fig.6 Typical Forward Characteristics



SBA220AH / SBA230AH / SBA240AH




Fig.7 Typical Forward Characteristics




Fig.8 Typical Forward Characteristics




Fig.9 Operating Temperature Derating Curve




SBA220AH / SBA230AH / SBA240AH

Part No Packing Code Version

Part No Packing Code	Package Type	Packing Type	Marking	Version
SBA220AH_R1_00001	SOD-123HE	3K pcs / 7" reel	B7	Halogen free
SBA230AH_R1_00001	SOD-123HE	3K pcs / 7" reel	E7	Halogen free
SBA240AH_R1_00001	SOD-123HE	3K pcs / 7" reel	F7	Halogen free

Packaging Information & Mounting Pad Layout





SBA220AH / SBA230AH / SBA240AH

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panjit:

[SBA220AH_R1_00001](#)