STATSHIELD® METAL-OUT SERIES





Standard Document

ANSI/ESD S541 (ANSI/ESD S20.20)

ANSI/ESD S11.4

Electrical Properties Surface Resistance:

Outer Surface $1 \times 10^4 \text{ to} < 1 \times 10^8 \text{ ohms}$ Inner Surface $1 \times 10^4 \text{ to} < 1 \times 10^{11} \text{ ohms}$

Discharge Shielding <20 n.J

Charge Generation Teflon: -0.03 nC/sq. in. Quartz: +0.10 nC/sq. in.

Capacitance Probe (to dissipate 1 KV) <30 volts

Typical Values

ANSI/ESD STM11.11 ANSI/FSD STM11 11

ANSI/ESD STM11.31. EIA 541

Meets Requirements of:

ESD Protective Packaging

Test Procedures/Method

Level 3 Technical Requirements

Modified Incline Plane Modified Incline Plane

ANSI/EIA-541/Appendix E. 1kV Discharge

Physical Properties:

Date & Lot Code

Weld

Soft Fold Bottom

Film Thickness Nominal 3.0 mil (0.07mm) ±10% Width (Inside Dimensions) Nominal -0" / + 0.250"

Length (Inside Dimensions) Nominal ± 0.125", Offset 0 to 1/4"

Light Transmission 40% (Tobias) Puncture Resistance >10 lbs Heat Seal >10 lbs/in. Non-corrosive Pass

Silicone Not detected Marking Adhesion Pass

MIL-STD-3010, 1003

ASTM D-1003 MIL-STD-3010, 2065 375°F, 1/2 sec 60 psi MIL-STD-3010. M3005

FTIR

IPC-TM-650 2.4.1

Side Weld Seals 3/8 in. (±0.10) ** Bags are printed (hot stamped or thermal transferred) with an ESD protective symbol and a lot code for traceability. **

Width (W)

STATSHIELD®

RoHS

Static Shielding Ba

DescoIndustries.com


Made in America

Opening

Length (L)

Weld

Seal



Mixed Unsortable Plastic Scrap

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades

Desco's bags are recyclable

Statshield® bags are packaged 100 per package in an oversized shielding bag. See Shielding Bag Storage at TB-7507.

ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

- 1. Low charge generation
- Dissipative or conductive materials for intimate contact
- 3. A structure that provides electrostatic discharge shielding."

RoHS. REACH and Conflict Minerals Statement

See the Desco Industries RoHS, REACH, and Conflict Minerals Statement:

https://desco.descoindustries.com/pdf/Regulatory Statements Desco Statshield Bags.pdf

See the Desco Limited Warranty:

Desco.DescoIndustries.com/Limited-Warranty.aspx

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc. See Bag Selection Chart Click HERE



Specifications and procedures subject to change without notice.

STATSHIELD® BAG, SHIELDING, METAL-OUT CONSTRUCTION, 3.0 MIL (0.07mm)



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407

PHONE (781) 821-8370

DRAWING NUMBER 13010

DATE: September 2021

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Desco:

 $\underline{13035} \ \underline{13135} \ \underline{13065} \ \underline{13115} \ \underline{13070} \ \underline{13010} \ \underline{13125} \ \underline{13075} \ \underline{13050}$