

Characteristics:

- Brushes minimize static charge generation and remove electrostatic charges to ground when held by grounded personnel
- Conductive copper based nylon bristles mixed with natural materials
- · Available in 3 kinds of bristles soft, sem-firm, and firm
- · Semi-firm and soft bristles are ideal for chemical and electronics applications
- Firm bristles are mainly for electronics, especially circuit boards
- Conductive carbon loaded polypropylene handle
- Conductive handle's ESD properties are not effected by humidity as are wooden handle brushes
- RTT Resistance: 1 x 10^3 to <1 x 10^5 ohms tested per modified ANSI/ESD S4.1

Materials:

- Firm bristles conductive yarn and hog hair*
- Semi-fine bristles conductive yarn and horse hair*
- Soft Bristles conductive yarn and goat hair*

*Natural animal hair has potential to shed

ltem	Handle Type	Bristle Hardness	Overall Length	Overall Width	Bristle Length	Bristle Width	Bristle Height
<u>35690</u>	Round	Firm	6" (152 mm)	5/16" (8 mm)	7/16" (11 mm)	3/16" (5 mm)	3/16" (5 mm)
<u>35691</u>	Long	Firm	6" (152 mm)	1/2" (13 mm)	11/16" (17 mm)	1-1/4" (32 mm)	1/4" (6 mm)
<u>35692</u>	Long	Firm	7" (178 mm)	1/2" (13 mm)	10/16" (16 mm)	2-3/8" (60 mm)	5/16" (8 mm)
<u>35693</u>	Flat	Firm	6-1/4" (159 mm)	2-1/8" (54 mm)	3/4" (19 mm)	2" (51 mm)	3/16" (5 mm)
<u>35694</u>	Flat	Semi-Fine	5-1/4" (133 mm)	5/16" (8 mm)	13/16" (21 mm)	1/2" (13 mm)	3/16" (5 mm)
<u>35695</u>	Curved	Firm	4" (102 mm)	2-1/2" (64 mm)	1" (25 mm)	3" (76 mm)	1" (25 mm)
<u>35696</u>	Flat	Firm	5-1/8" (130 mm)	5/16" (8 mm)	10/16" (16 mm)	1/2" (13 mm)	3/16" (5 mm)
<u>36086</u>	Flat	Firm	5-3/4" (146 mm)	7/8" (22 mm)	3/4" (19 mm)	3/4" (19 mm)	3/16" (5 mm)
<u>36087</u>	Flat	Firm	5-3/4" (146 mm)	1-1/16" (27 mm)	3/4" (19 mm)	7/8" (22 mm)	3/16" (5 mm)
<u>36088</u>	Flat	Firm	6-1/4" (159 mm)	1-5/8" (41 mm)	3/4" (19 mm)	1-1/2" (38 mm)	3/16" (5 mm)
<u>36098</u>	Round	Soft	6-5/16" (160 mm)	3/16" (5 mm)	1" (25 mm)	1/4" (6 mm)	1/4" (6 mm)

Designed to fulfill ANSI/ESD S20.20 requirement to ground all conductors at ESD workstation.

ESD Handbook TR20.20 Table 1 lists under Typical Static Electricity Sources "Brushes (camel/pig hair and synthetic bristles)."

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." (TR 20.20 section 2.4)

Unless otherwise noted, tolerance is ±10%.

Specifications and procedures subject to change without notice. Made in Israel



Dimensions are taken from the bottom of the brush to the top of the bristles.

Synthetic vs. Natural Bristles

Synthetic bristles can easily become charged with static in standard humidity conditions. Natural hair usually builds static in areas of low humidity, but due to the conductive fibers in our brushes, this problem does not take effect.

Generally speaking, once the conductive yarn is added to the bristles, it neutralizes the possibility of static build up caused by the natural hair.

CONDUCTIVE BRUSHES3651 WALNUT AVE., CHINO, CA 91710DRAWING
DATE:
NUMBERDATE:
March
2021PHONE: (909) 627-2453NUMBER
35690March
2021

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Menda:

35696 35690 35692 35691 35693 35695 35694 36098 36087 36088 36086