

Features:

- Used in the rework and repair of printed circuit boards, computers, cell phones, or other electronics
- · Easily removes solder from components or pads on a circuit board
- Concentrated fine copper braiding utilizes less length of wick for each desoldering application
- Made of clean, oxide-free copper wire
- Tight weave enables quick "on and off" desoldering
- 5' and 10' lengths available on static dissipative bobbins in compliance with ESD Association Standard
- · Leaves a residue that is environmentally safe
- Uses flux classification type L0 per IPC J-STD-004B

Wire Specifications:

Wire Type	Width	Configuration
A Wire	0.025" (±0.003") .635mm (±0.08mm)	2 strands of 42awg X 16 (total 32 strands), 31 PPI
B Wire	0.050" (±0.004") 1.27mm (±0.10mm)	4 strands of 42awg X 16 (total 64 strands), 12.5 PPI
C Wire	0.075" (±0.005") 1.90mm (±0.13mm)	6 strands of 42awg X 16 (total 96 strands), 16 PPI
D Wire	0.095" (±0.007") 2.41mm (±0.18mm)	5 strands of 42awg X 24 (120 total strands), 19 PPI
E Wire	0.117" (±0.008") 2.97mm (±0.20mm)	5 strands of 40awg X 24 (120 total strands), 16 PPI

Bobbin Identification:

Width	Color Code	Letter Signifier
.025"	Gray	А
.050"	Yellow	В
.075"	Green	С
.100"	Blue	D
.125"	Brown	E



Specifications and procedures subject to change without notice.



individually stamped with a lot code. A certificate of compliance is available on our website.

QUICK BRAID DESOLDERING BRAID

11520 K-TEL DRIVE, MINNETONKA, MN 55343	DRAWING	DATE:
PHONE: (909) 627-2453	NUMBER	March
WEBSITE: EASYBRAIDCO.COM	Quick Braid	2019

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Menda:

 Q-B-10AS
 Q-A-500
 Q-A-5AS
 Q-D-25
 Q-A-10AS
 Q-E-25
 Q-E-50AS
 Q-E-5AS
 Q-D-5AS
 Q-A-100
 Q-C-50
 Q-C-50

 5AS
 Q-E-100
 Q-B-500
 Q-B-25AS
 Q-E-10AS
 Q-C-500
 Q-B-25
 Q-B-50
 Q-A-50
 Q-D-100
 Q-D-100

 D-10AS
 Q-D-50
 Q-C-25
 Q-A-25
 Q-B-5AS
 Q-C-100
 Q-C-10AS
 Q-E-500