

GREAT GOLDEN

Power Connectors


GG Series



- Featuring 200 Amp Size 0 Contacts
- Modular - 256 Possible Versions
- Hot Plug-Blind Mating
- "Safety Feature" Contacts




POSITRONIC
GLOBAL *Connector* SOLUTIONS




Typical Mating Systems


Cable to Cable



Panel Mount to Cable




Cable to Bus bar



Consult factory for availability of Bus bar contacts

Cable to Straight PCB Mount



Consult factory for availability of Straight PCB Mount Contacts

Unless otherwise specified, dimensional tolerances are:

- 1) Male contact mating diameters : ± 0.03 [0.001]
- 2) Contact termination diameters : ± 0.08 [0.003]
- 3) All other diameters : ± 0.13 [0.005]
- 4) All other dimensions : ± 0.38 [0.015]

Dimensions are in millimeters [inches].

All dimensions are subject to change.

Positronic believes the data contained herein to be reliable. Since the technical information is given free of charge, the user employs such information at his own discretion and risk. Positronic assumes no responsibility for results obtained or damages incurred from use of such information in whole or in part.



Technical Characteristics

Materials and Finishes:

Insulators: Glass-filled nylon, UL 94V-0, Gold color
Consult factory for high performance glass-filled polyester material option.

Contacts: Precision machined copper alloy with gold flash over nickel. Other finishes available upon request.

Electrical Characteristics:

Contact Current Rating (per UL 1977):

*Size 0 Contacts: 200 amperes, continuous (high conductivity material).
175 amperes, continuous (standard material).
(Size 0 contact with 0 AWG wire)

Size 12 Contacts: 45 amperes, continuous (high conductivity material).
35 amperes, continuous (standard material).

Size 16 Contacts: 28 amperes, continuous (high conductivity material).
20 amperes, continuous (standard material).

Size 20 Contacts: 5 amperes, nominal (standard material).

Initial Contact Resistance Max (per IEC 512-2, Test 2b) :

Size 0 Contacts: 0.00012 ohms (high conductivity material).
0.00038 ohms (standard material).

Size 12 Contacts: 0.0005 ohms (high conductivity material).
0.0016 ohms (standard material).

Size 16 Contacts: 0.0012 ohms (high conductivity material).
0.0024 ohms (standard material).

Size 20 Contacts: 0.0036 ohms (standard material).

Insulator Resistance (per IEC 512-2, Test 3a): 5 G ohms.

Voltage Proof:

Size 0 Contacts: 3000 V r.m.s.
Size 12 Contacts: 1500 V r.m.s.
Size 16 Contacts: 1500 V r.m.s.
Size 20 Contacts: 1000 V r.m.s.

Working Voltage:

Size 0 Contacts: 250 V r.m.s.
Size 12 Contacts: 500 V r.m.s.
Size 16 Contacts: 500 V r.m.s.
Size 20 Contacts: 333 V r.m.s.

Hot Pluggable, Size 12 Contacts: 250 V AC at 25 amperes for 50 cycles.

Mechanical Characteristics:

Blind Mating System: Molded in guides allow for misalignment up to 4.50 mm [0.177 inch]

Polarization: Provided by connector body design.

Removable Contacts (Size 0):

Insert contact in rear face of insulator and secure with locking clip; release from rear face of insulator by, first, removing locking clip. Female contacts feature "Closed Entry" design.

Removable Contacts (Size 12, Size 16 and Size 20):

Insert/remove contacts via rear face of insulator; release contacts via front face of insulator with a contact extraction tool. Female contacts feature "Closed Entry" design.

Removable Contact Retention in Connector Body
(per IEC 512-8, Test 15a):

Size 0 Contacts: 132 N [30 lbs.]
Size 12 Contacts: 67 N [15lbs.]
Size 16 Contacts: 67 N [15 lbs.]
Size 20 Contacts: 44 N [10 lbs.]

Sequential Contact Mating System:

Two level systems featured for Size 16 and Size 20 Contacts.

Consult factory for three levels of sequential contact mating option.

Mechanical Operations: 1,000 cycles.

Climatic Characteristic:


Working temperature: -55°C to +125°C.



Recognized:

UL: Certification in process.


TÜV: Consult factory.

Connector Combination - Total of 256 combinations







Above curves developed separately using Size 0 contact with 4 AWG wire. Four (4) Size 0 contacts under load.




Above curves developed separately using Size 16 contact with 12 AWG wire. (A) Twelve (12) Size 16 contacts under load. (B) Six (6) Size 16 contacts under load.



Above curves developed separately using Size 0 contact with 0 AWG wire. Four (4) Size 0 contacts under load.




Above curves developed separately using Size 12 contact with 10AWG wire. Four (4) Size 12 contacts under load.




Outline Dimensions

Male Connector




Female Connector




Removable contacts should be allowed to float after installation in the connector body.
 This enables superior mating performance.

Panel Cutout

Panel Cutout Dimensions For Float Bushing




Panel Cutout Dimensions For Jackscrew System



Accessories


Float Bushing

Specify code 82 or 83 in Step 5.



Jackscrew System

Specify code E for Turnable Male Jackscrew or T for Fixed Female Jackscrew in Step 5.




Materials and Finishes:

Float Bushing: Brass, zinc plating.
 Bushing Screw: Brass, zinc plating.

Materials and Finishes:


Fixed Female Jackscrew: Brass, zinc plate.
 Turnable Male Jackscrew: Brass, zinc plate.

Contact factory for dimensions and details of accessories.



Hood with Cable Clamp

Designate Code J in step 5 of ordering information.




Materials and Finishes:

Hood, Clamps and Screws: Steel, Zinc plating.

Consult factory for availability of Hood

Application Without Hood


Removable contacts should be allowed to float after installation in the connector body. This enables superior mating performance. Therefore, wires must remain approximately perpendicular to the connector for a recommended minimum distance. See diagram.



Removable, Solder, Straight PCB Mount Contacts

Typical connector installed with removable, solder, straight PCB mount contacts and Push-on Fasteners


Consult factory for straight PCB mount contacts (size 20, 16, and 12 only), alignment bars and push-on fastener ordering details and availability.






Size 12 Removable Crimp Contacts

Female




Male




Size 16 Removable Crimp Contacts

Female




Male




Size 20 Removable Crimp Contacts

Female



Male



Please use correct wire size and it should be smaller than ØA of the contact.
Consult factory for other contact sizes, materials, finishes and termination styles.

Removable contacts should be allowed to float after installation in the connector body.
This enables superior mating performance.

Part Number (Standard Material)	Part Number (High Conductivity Material)	Wire Size AWG [mm ²]	ØA	ØB	C
Female Contacts					
SFC1210N2	SFC1210N2S	10[6.0]	3.73[0.147]	N/A*	22.76[0.896]
SFC1212N2	SFC1212N2S	12[4.0]	2.54[0.100]	4.19[0.165]	
Male Contacts					
SMC1210BN	SMC1210BNS	10[6.0]	3.73[0.147]	N/A*	22.70[0.894]
SMC1212BN	SMC1212BNS	12[4.0]	2.54[0.100]	4.19[0.165]	

N/A* - Not applicable

Part Number (Standard Material)	Part Number (High Conductivity Material)	Wire Size AWG [mm²]	ØA	ØB	Sequential Mate	C
Female Contacts						
SFC1612N2	SFC1612N2S	12 [4.0]	N/A*	2.49[0.098]	N/A*	22.80 [0.898]
SFC1614N2	SFC1614N2S	14 [2.5]	2.06 [0.081]	2.64[0.104]		
SFC1616N2	SFC1616N2S	16 [1.5]	1.70 [0.067]	2.36[0.093]		
SFC1620N2	SFC1620N2S	20 [0.5]	1.14 [0.045]	1.73[0.068]		
Male Contacts						
SMC1612AN	SMC1612ANS	12 [4.0]	N/A*	2.49[0.098]	First	23.68 [0.932]
SMC1612BN	SMC1612BNS				Standard	19.87 [0.782]
SMC1614AN	SMC1614ANS	14[2.5]	2.06 [0.081]	2.67[0.105]	First	23.68 [0.932]
SMC1614BN	SMC1614BNS				Standard	19.87 [0.782]
SMC1616AN	SMC1616ANS	16[1.5]	1.70[0.067]	2.36[0.093]	First	23.68 [0.932]
SMC1616BN	SMC1616BNS				Standard	19.87 [0.782]
SMC1620AN	SMC1620ANS	20 [0.5]	1.14 [0.045]	1.73[0.068]	First	23.68 [0.932]
SMC1620BN	SMC1620BNS				Standard	19.87 [0.782]

N/A* - Not applicable

Part Number (Standard Material)	Wire Size AWG [mm ²]	ØA	ØB	Sequential Mate	C
Female Contacts					
SFC2020N2	20[0.5]	1.14[0.045]	1.73[0.068]	N/A*	22.30[0.878]
Male Contacts					
SMC2020AN	20[0.5]	1.14[0.045]	1.73[0.068]	First	23.93[0.942]
SMC2020BN				Standard	20.12[0.792]

N/A* - Not applicable


Materials:

Contacts: Copper alloy.
Retention Clips: Beryllium copper.


Finishes:

Gold flash over nickel plate.

Safety Features of Insulator and Size 0 Contact



The connector was designed to pass the IEC 60950 (figure 2C) test probe which provides protection from electric shock and energy hazards.




Materials and Finishes:

Male Probe Protector: Nylon, UL 94V-0, black color.
Crown Pressure Device: Beryllium copper, gold flash over nickel plate.




Size 0 Removable Crimp Contacts




Part Number (Standard Material)	Part Number (High Conductivity Material)	Wire Size AWG [mm ²]	ØA
Female Contacts			
GGFC00N	GGFC00NS	0[55]	10.50 [0.413]
GGFC04N	GGFC04NS	4[25]	7.50 [0.295]
Male Contacts			
GGMC00N	GGMC00NS	0[55]	10.50 [0.413]
GGMC04N	GGMC04NS	4[25]	7.50 [0.295]

Size 0 Removable Contacts, Internal Threads For Typical Ring Terminal




Part Number (Standard Material)	Part Number (High Conductivity Material)	Thread T
Female Contacts		
GGFIT00M	GGFIT00MS	M6 x 1
GGFIT00S	GGFIT00SS	1/4-20 UNC 2B
Male Contacts		
GGMIT00M	GGMIT00MS	M6 x 1
GGMIT00S	GGMIT00SS	1/4-20 UNC 2B

Size 0 Removable Contacts, External Threads For Typical Ring Terminal




Part Number (Standard Material)	Part Number (High Conductivity Material)	Thread T
Female Contacts		
GGFET00M	GGFET00MS	M6 x 1
GGFET00S	GGFET00SS	1/4-20 UNC 2A
Male Contacts		
GGMET00M	GGMET00MS	M6 x 1
GGMET00S	GGMET00SS	1/4-20 UNC 2A

Size 0 Removable Contacts, Right Angle Threads For Typical Ring Terminal



Part Number (Standard Material)	Part Number (High Conductivity Material)	Thread T
Female Contacts		
GGFRA00M	GGFRA00MS	M6 x 1
GGFRA00S	GGFRA00SS	1/4-20 UNC 2B
Male Contacts		
GGMRA00M	GGMRA00MS	M6 x 1
GGMRA00S	GGMRA00SS	1/4-20 UNC 2B



Ring Terminal
(Shown for reference only.)

Consult factory for BUS bar contacts availability

Materials:

Contacts: Copper alloy.

Locking Clips: Copper alloy and nylon.

Male Probe Plug : Nylon, UL 94V-O, black color

Finish:

Gold flash over nickel plate.

Consult factory for Silver plating option.

Insertion, Extraction, and Retention of Size 0 Contacts

Insertion

STEP 2: Lock the Locking Clip.

STEP 1: Insert the Contact from Rear Side.

Locking Clip

Materials:

Locking clip: Copper alloy with Nylon, UL 94V-O dielectric overmold, black color.

Finishes: Gold flash over nickel plate.


Extraction

STEP 1: Unlock the Locking Clip.

STEP 2: Extract the Contact from Rear Side.



Crimping Tool Part Number 9504 -21 -0



Same crimping tool (9504 -21 -0) is used for crimping '0' AWG wire and '4' AWG wire

Disclosure Statement:

Positronic Industries cannot be held responsible for defective crimps when customer utilizes other vendor's crimp tools. Samples of '0' AWG wire with strands combination of 300/26, 478/28, 292/26 have been crimped and tested at factory and are deemed compatible with our crimp tool. Consult factory prior to utilizing strands combinations not called out above.

Recommended Assembly Procedure For Crimp Termination:

1. Carefully strip back the cable insulation by 20.00mm [0.787] inch without damaging any of the conductor strands.
2. Insert the conductor wire strands into the crimp barrel at the rear of the contact. Ensure that all of the conductor wire strands are captured within the crimp barrel and that the cable conductor wire is visible through the inspection hole.
3. Utilizing the crimping tool, crimp the contact (as shown) making sure that the cable remains straight, for a distance of one meter or the entire length of cable if less than one meter in length from the crimping die, and touches the contact stopper while performing the crimp operation as shown in figure A and B below.




FIGURE 'A' Male contact





FIGURE 'B' Female contact

4. Examine crimp joints to ensure that the crimp is satisfactory.
5. Insert the crimp contact into the insulator and then visually align the locking clip groove and press in the locking clip. (As shown in Insertion and Extraction of Size 0 contact on page 7)
6. Ensure that the locking clip is flush with insulator.

Recommended Tools for Size 12, Size 16 and Size 20 Contacts

Contact Extraction Tool



Cycle-Controlled Step Adjustable Hand Crimp Tool



Positronic Recommended Conductor Tensile Strength (Pull Test)


To ensure proper crimp

Contact Size	Contact Extraction Tool	Hand Crimp Tool
Size 12	2711-0-0-0	9501 with 9502-19-0-0 positioner
Size 16	9081-6-0-0	9501 with 9502-17-0-0 positioner for Male Contacts 9501 with 9502-26-0-0 positioner for Female Contacts
Size 20	9081-5-0-0	9507 with 9502-21-0-0 positioner for Male Contacts 9507 with 9502-25-0-0 positioner for Female Contacts

Wire Size	Axial Load
0 AWG [55 mm ²]	2803N [630 lbs.]
4 AWG [25 mm ²]	1602N [360 lbs.]
10 AWG [6.0 mm ²]	601N [135lbs.]
12 AWG [4.0 mm ²]	445N [100 lbs.]
14 AWG [2.5 mm ²]	267N [60 lbs.]
16 AWG [1.5 mm ²]	165N [37 lbs.]
20 AWG [0.5 mm ²]	85N [19lbs.]

As per SAE AS 39029

Please see Positronic's SUMO catalog or consult factory for crimping and wire stripping information on Size 12, 16 and 20 contacts



Specify complete connector by following step 1 through step 5.

Step	1	2A	2B	2C	2D	3	4	5	6	7
Example	GG	8	7	6	8	M	1	0	/AA	xxx

STEP 1: Basic Series
GG4 : GG Series

STEPS 2: Connector Version
256 versions available . Specify using Step 2A through Step 2D. Each Step (2A, 2B, 2C, or 2D) can be any module.

Code 8 : One (1) size 0 power contact.

Code 7: Four (4) size 12 power contacts.

Code 6: Twelve (12) size 16 power contacts.

Code 5 : Nineteen (19) size 20 signal contacts.

Part Number Example: GG8568M10

Code 8 = 1ea. Size 0 power contact (Step 2A)

Code 5 = 19ea. Size 20 signal contacts (Step 2B)

Code 6 = 12ea. Size 16 power contacts (Step 2C)

Code 8 = 1ea Size 0 power contact (Step 2D)

MALE FACE FOR REFERENCE ONLY

STEP 7: Special Options
Consult factory for customization.

STEP 6: Environmental Compliance options
/AA : Compliant per EU Directive 2002/95/EC (RoHS)
Example: GG8567F10/AA
Note: If no environmental options are required, this step will not be used.
Example: GG8567F10

STEP 5: Mounting Style
0: No hardware.
82: Float mount 1.5 mm panel thickness.
83: Float mount 2.3 mm panel thickness.
E: Turnable male jackscrews .
T: Fixed female jackscrews.
J: Hood.*
EJ: Turnable male jackscrews with Hood.*
TJ: Fixed female jackscrews with Hood.*
*Consult factory for Hood availability.

STEP 4: Type of Contact
1: Removable contact.
Contacts ordered separately.

STEP 3: Connector Gender
F: Female
M: Male

Part Number Example: GG8767M1E

Code 8 = 1ea Size 0 power contact (Step 2A)

Code 7 = 4ea Size 12 power contacts (Step 2B)

Code 6 = 12ea Size 16 power contacts (Step 2C)

Code 7 = 4ea Size 12 power contacts (Step 2D)

MALE FACE FOR REFERENCE ONLY

Consult factory for the availability of two (2) size 8 power contacts or other contact sizes.
Consult factory for high performance glass-filled polyester material option.

NORTH AMERICAN SALES OFFICES

United States, Springfield, Missouri

Factory and Sales Office	800 641 4054
Puerto Rico Sales Office	800 641 4054
Mexico Sales Office	800 872 7674
Canada Sales Office	800 327 8272

info@connectpositronic.com

EUROPEAN SALES OFFICES

France, Auch Factory and Sales	33 (0) 5 6263 4491
Northern France Sales Office	33 (0) 1 4588 1388
Southern France Sales Office	33 (0) 4 6772 8028
Italy Sales Office	39 (0) 2 5411 6106
Germany Sales Office	49 (0) 23 5163 4739
United Kingdom Sales Office	44 (0) 7975 682 488

contact@connectpositronic.com
jchalaux@connectpositronic.com
plafon@connectpositronic.com
rmagni@connectpositronic.com
cbouche@connectpositronic.com
lbridwell@connectpositronic.com

Europe & Middle East Technical Agents:

Finland, United Kingdom, Scotland, Israel, Norway, Sweden, Turkey and the Ukraine.

ASIA / PACIFIC SALES OFFICES

Singapore Factory, Sales and Engineering Office

Singapore	+65 6842 1419
Japan	+81 35619 8072
South Korea	+82 31 909 8047
India	+91 20 2469 9910
Taiwan	+886 2 2937 8775
China Factory - Zhuhai	+86 756 3626 466
Beijing & Xian	+86 029 8839 5306
Shenzhen	+86 755 2643 7578
Shanghai	+86 158 2907 9779
Malaysia	+60 4 644 9688
New Zealand	+886 9350 67647
Australia	+61 2 4362 3477

singapore@connectpositronic.com
japan@connectpositronic.com
korea@connectpositronic.com
india@connectpositronic.com
taiwan@connectpositronic.com
zhuhai@connectpositronic.com
xian@connectpositronic.com
shenzhen@connectpositronic.com
shanghai@connectpositronic.com

newzealand@connectpositronic.com
australia@connectpositronic.com

POSITRONIC INDUSTRIES, INC

423 N Campbell Avenue, P O Box 8247,
Springfield, MO 65801, USA
Telephone: 1 417 866 2322
Fax: 1 417 866 4115
Email: info@connectpositronic.com

POSITRONIC INDUSTRIES, SAS

Zone Industrielle Est, 46 Route d'Engachies,
F32020, Auch Cedex 9, France
Telephone: 33 (0) 5 62 63 44 91
Telecopieur: 33 (0) 5 62 63 51 17
Email: contact@connectpositronic.com

POSITRONIC ASIA PTE LTD

3014A Ubi Road 1 # 07-01 Singapore 408703
Telephone: 65 6842 1419 Fax: 65 6842 1421
Email: singapore@connectpositronic.com

www.connectpositronic.com



POSITRONIC
GLOBAL *Connector* SOLUTIONS

GREAT GOLDEN
Power Connectors
GG Series

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[SFC1210N2S](#) [SFC1210N2S/AA](#) [SFC1612N2](#) [SFC1612N2/AA](#) [SMC1210BN](#) [SMC1210BN/AA](#) [SMC1612BN](#)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Positronic:

[SFC1210N2](#) [SFC1210N2/AA](#) [SFC1212N2](#) [SFC1212N2/AA](#) [SFC1212N2S](#) [SFC1212N2S/AA](#) [SFC1614N2](#)
[SFC1614N2/AA](#) [SFC1614N2S](#) [SFC1614N2S/AA](#) [SFC1616N2](#) [SFC1616N2/AA](#) [SFC1616N2S](#) [SFC1616N2S/AA](#)
[SFC1620N2](#) [SFC1620N2/AA](#) [SFC1620N2S](#) [SFC1620N2S/AA](#) [SFC2020N2](#) [SFC2020N2/AA](#) [SFC1210N2S](#)
[SFC1210N2S/AA](#) [SFC1612N2](#) [SFC1612N2/AA](#)