

ATP DDR2 DRAM Solutions

Intense Performance for Intense Workloads



DDR2 supersedes the original DDR specifications with data transfer speeds up to 800 MT/s. The memory clock speed of the industrial DDR2 SDRAM was reduced by half compared to first-generation DDR, enabling DDR2 to effectively operate up to 2X the DDR bus speed.

Apart from faster operation, DDR2 also consumes less power than its predecessor. With its operating voltage reduced from 2.5V to 1.8V, DDR2 cuts overall power consumption.

ATP DDR2 modules are available in several form factors suitable for diverse applications, including 240-pin full-size UDIMMs, 200-pin SO-DIMMs are also available for compact systems. These form factors are not interchangeable with DDR, DDR3 or DDR4.

Key Features

- Density: 256 MB to 4 GB
- Chipkill support

Applications

- Networking systems
- Telecommunication
- Gaming
- Healthcare
- Industrial PCs









Industrial

Test During

Complete Drive Test

Thicker Gold Finge

Specifications

DDR2			
DIMM Type	ECC UDIMM	Non-ECC UDIMM	Non-ECC SO-DIMM
Density	1 GB to 2 GB	1 GB to 2 GB	256 MB / 1 GB to 4 GB
Speed up to (MT/s)	800	800	800
PCB Height	Low Profile	Low Profile	Low Profile
Operating Temperature	0°C to 85°C / -40°C to 95°C	0°C to 85°C / -40°C to 95°C	0°C to 85°C / -40°C to 95°C

DDR2				
Module Type	UDIMM	SO-DIMM		
Function	Unbuffered ECC / Unbuffered Non-ECC	Unbuffered Non-ECC		
Density	1 GB / 2 GB	256 MB / 1 GB / 2 GB / 4 GB		
Frequency	800 MHz	800 MHz		
PCB Height	1.18"	1.18"		
Number of Pins	240	200		



To learn more about this product, contact your ATP Representative.

ATP TAIWAN(HQ)

ATP Global Footprint

TEL: +886-2-2659-6368 FAX: +886-2-2659-4982 sales-apac@atpinc.com ATP USA

TEL: +1-408-732-5000 FAX: +1-408-732-5055 sales@atpinc.com ATP EUROPE

TEL: +49-89-374-9999-0 FAX: +49-89-374-9999-29 sales-europe@atpinc.com ATP JAPAN

TEL: +81-3-6260-0797 FAX: +81-3-6260-0798 sales-japan@atpinc.com ATP CHINA

TEL: +86-21-5080-2220 FAX: +86-21-9687-0000-026 sales@cn.atpinc.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ATP Electronics:

<u>AJ28K64J8BJF7M</u> <u>AJ28K72H8BJF7M</u> <u>AJ56K64J8BJF7M</u> <u>AJ56K72H8BJF7M</u> <u>AZ28K64B8BJE6MI</u> AZ28K64B8BJE7M AZ56K64E8BJE6MI AZ56K64E8BJE7M AZ56K64E8BJF7MI