

ATP USB Drives Industrial Grade

Targeted Product Portfolio, Engineered Specifically for Your Mission Critical Applications





NANODURA

The ATP NANODURA is an industrial USB drive built for mission-critical embedded applications. Suitable for compact systems installed in limited spaces, NANODURA's rugged metal housing and ATP System in Package (SiP) technology offer rugged durability for dependable use in extreme operating temperatures ranging from -40°C to 85°C and resistance to water/moisture, vibration, shock and electrostatic discharge (ESD). NANODURA offers up to 60,000 program/erase (P/E) cycles, which is 20X higher than other USB drives in the market. The extraordinary endurance, advanced bad block algorithm and global wear leveling make NANODURA an excellent boot drive and ideal storage solution for applications with high performance and high data retention requirements. Hot swap support guarantees maximum availability, allowing drive removal and replacement without shutting down the system.

Key Features

- Global wear leveling
- Bad block management algorithm
- High reliability
- Hot swap supported

Applications

- Medical
- Industrial PC
- Automation applications

Specifications

Product Name		NANODURA			
Product Line		Premium	Superior		
Naming		B800Pi	B600Sc		
Flash Type		SLC	MLC		
Density		512 MB to 8 GB	8 GB to 16 GB		
Performance	Sequential Read up to (MB/s)	31	25		
	Sequential Write up to (MB/s)	21	18		
Interface		Compatible with USB 2.0 (480 Mbps)			
Operating Temperature (Tcase)*		-40°C to 85°C	0°C to 70°C		
Endurance TBW** (max.)		192 TB	19.2 TB		
Reliability	MTBF @ 25°C	>5,000,000 hours	>2,000,000 hours		
	Number of Insertions	10,000 minimum			
Dimensions: L x W x H (mm)		34.0 x 12.2 x 4.5			

 $^{^{\}ast}$ Case Temperature, the composite temperature as indicated by SMART temperature attributes.

^{**} Under highest Sequential write value. May vary by density, configuration and applications.

Technologies & Add-On Services	S.M.A.R.T.	Advanced Wear Leveling	Industrial Temperature	SiP (System in Package)
Premium	•	•	•	•
Superior	•	•	Δ	•

 $\Delta {:}$ Customization option available on a project basis.



ATP Global Footprint

To learn more about this product, contact your ATP Representative.

ATP TAIWAN(HQ)

TEL: +886-2-2659-6368 FAX: +886-2-2659-4982 sales-apac@atpinc.com ATP USA

TEL: +1-408-732-5000 FAX: +1-408-732-5055 sales@atpinc.com ATP EUROPE

TEL: +49-89-374-9999-0 FAX: +49-89-374-9999-29 sales-europe@atpinc.com ATP JAPAN

TEL: +81-3-6260-0797 FAX: +81-3-6260-0798 sales-japan@atpinc.com ATP CHINA

TEL: +86-21-5080-2220 FAX: +86-21-9687-0000-026 sales@cn.atpinc.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ATP Electronics:

AF16GUFNDNC-AADXX AF1GUFNDNC(I)-AAAXX AF2GUFNDNC(I)-AAAXX AF4GUFNDNC(I)-AACXX AF512UFNDNC(I)-AAAXX AF8GUFNDNC(I)-AAAXX AF8GUFNDNC-AADXX