

ATP SD/SDHC/SDXC Card

Industrial Grade

Targeted Product Portfolio, Engineered Specifically for Your Mission Critical Applications



ATP SD cards are the ideal storage format for industrial and automotive applications as they can be conveniently inserted into and easily removed from small host devices for convenient data transfer and storage expansion.

Made to perform dependably under rigorous conditions, ATP SD cards are designed with extensive longevity, which is typically required in industrial applications such as automation, networking, health care and more.

ATP SD cards also deliver the quality, durability and reliability to meet the requirements of major automotive OEM/Tier 1 suppliers, system developers and service providers for higher levels of data accuracy, consistency and integrity in applications such as maps/navigation systems, in-vehicle infotainment (IVI), Advanced Driver Assistance Systems (ADAS), and other data-intensive applications. These solutions can withstand extreme temperatures, dust and shock/vibration, and maintain data integrity under power cycling or sudden power-off events.











Now available in 3D triple-level cell (TLC) NAND flash with A1 Performance Class rating, ATP SD cards undergo endurance, data retention and wide temperature tests and are certified according to international, automotive-specific and temperature-related standards.

Key Features

- SD Life Monitor
- Advanced Wear Leveling
- SiP (System in Package)
- AutoRefresh technology
- Dynamic Data Refresh
- Power failure protection
- Industrial temperature
- Joint Validation
- 100% MP Level Test

Applications

- Industrial PC
- Medical devices
- Automation
- Automotive IVI systems
- Test and Measurement
- Surveillance systems
- Drive recorders
- Navigations
- Network cameras
- Mobile/Handheld computers

Technologies & Add-On Services		 Life Monitor	 Sudden Power-Off Recovery	 Advanced Wear Leveling	 AutoRefresh	 Dynamic Data Refresh	 Secure Erase	 Industrial Temperature	 System in Package	 Complete Drive Test	 Joint Validation
Product Line	Premium	Δ	•	•	•	Δ	•	•	•	•	Δ
	Superior	Δ	•	•	•	•	•	Δ	•	•	Δ
	Value			•					•		

Δ: Customization option available on a project basis.



Specifications

Product Name		SD/SDHC/SDXC				
Product Line		Premium			Superior	
Naming		S800Pi	S700Pi	S700Pi	S700Sc	S700Sc
Flash Type		SLC	iTemp SLC mode	iTemp 3D SLC mode	SLC mode	3D SLC mode
Density		512 MB to 8 GB	4 GB to 8 GB	8 GB to 32 GB	4 GB to 8 GB	8 GB to 32 GB
Performance	Sequential Read up to (MB/s)	70	76	98	76	98
	Sequential Write up to (MB/s)	39	50	60	50	60
Interface		512 MB ~ 2 GB, HS mode 4 GB ~ 8 GB, UHS-I	UHS-I	UHS-I	UHS-I	UHS-I
Operating Temperature		-40°C to 85°C			-25°C to 85°C	
Reliability	TBW* (max.)	192 TB	128 TB	320 TB	128 TB	320 TB
	MTBF @ 25°C	>5,000,000 hours	>3,000,000 hours			
	Number of Insertions	20,000 (SDA spec minimum 10,000)				
Dimensions: L x W x H (mm)		32.0 x 24.0 x 2.1				

Product Name		SD/SDHC/SDXC				
Product Line		Superior				Value
Naming		S600Si	S600Sc	S600Sia	S600Sc	S600Vc
Flash Type		iTemp MLC / 3D TLC	MLC	iTemp 3D TLC	3D TLC	3D TLC
Density		8 GB to 256 GB**	8 GB to 128 GB**	32 GB to 256 GB	32 GB to 256 GB	32 GB to 128 GB
Performance	Sequential Read up to (MB/s)	98	96	98	98	100
	Sequential Write up to (MB/s)	64	61	64	64	78
Interface		UHS-I				
Operating Temperature		-40 °C to 85 °C	-25 °C to 85 °C	-40 °C to 85 °C	-25 °C to 85 °C	-25 °C to 85 °C
Reliability	TBW* (max.)	154 TB	154 TB	154 TB	154 TB	36 TB
	MTBF @ 25 °C	>2,000,000 hours				>1,000,000 hours
	Number of Insertions	20,000 (SDA spec minimum 10,000)				
Dimensions: L x W x H (mm)		32.0 x 24.0 x 2.1				

* Under highest Sequential write value. May vary by density, configuration and applications.

** By project support.

To learn more about this product, contact your ATP Representative.

ATP Global Footprint

ATP TAIWAN(HQ)

TEL: +886-2-2659-6368
FAX: +886-2-2659-4982
sales-apac@atpinc.com

ATP USA

TEL: +1-408-732-5000
FAX: +1-408-732-5055
sales@atpinc.com

ATP EUROPE

TEL: +49-89-374-9999-0
FAX: +49-89-374-9999-29
sales-europe@atpinc.com

ATP JAPAN

TEL: +81-3-6260-0797
FAX: +81-3-6260-0798
sales-japan@atpinc.com

ATP CHINA

TEL: +86-21-5080-2220
FAX: +86-21-9687-0000-026
sales@cn.atpinc.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ATP Electronics:](#)

[AF256GSD4-BBAIM](#)