
Mounting Option


03-.116 (2.95) I.D. Floating Eyelets


Contact Detail

542-Wire Wrap .025 Sq.(0.64 Sq.) - Tail LG=.645(16.38)

.156 [3.96] Contact Spacing x .200 [5.08] Row Spacing







See Accompanying Page for:

- **Bend Detail**
- **Mounting Options**
- **Features and Specifications**

333 Series Card Edge Connector Part Number: 333-044-542-803



| ACAD REFERENCE N | . 333 ENG MASTER | | | |
|------------------|------------------|--|--|--|
| DRAWN: J.LEE | DATE: OCT. 14/09 | | | |
| CHECKED: | DATE: | | | |
| SCALE: NTS | SHEET 1 OF 4 | | | |
| DRAWING NUMBER | ISSUE | | | |

333 Assembly

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.

ISSUE NUMBER

ORIGINAL

1



| 333 Series Card Edge Connector Contact Bend Detail | | ACAD REFERENCE NO. 333 ENG MASTER | | | |
|---|----------------|-----------------------------------|------------------|--------|--|
| | | DRAWN: J.LEE | DATE: OCT. 14/09 | | |
| | | CHECKED: | DATE: | | |
| EDAC INC THESE DRAWINGS AND SPECIFICATIONS | | SCALE: NTS | SHEET 2 | 2 OF 4 | |
| TORONTO, ONTARIO ARE THE PROPERTY OF EDAC INC. AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE | DRAWING NUMBER | | ISSUE | | |
| OUR CONNECTION TO QUALITY & SERVICE WITHOUT WRITTEN PERMISSION. | | 333 Assembly | | 1 | |

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER



SSUE NUMBER

DRIGINAL

1



| 333 Series Card Edge Connector | | ACAD REFERENCE NO. 333 ENG MASTER | | | | | |
|--------------------------------|--|-----------------------------------|--|------------------|-------------|--------|-------|
| | | DRAWN: | J.LEE | DATE: OCT. 14/09 | | | |
| | Mounting Options | | CHECKED: | | DATE: | | |
| | EDAC INC THESE DRAWINGS AND SPECIFICATIONS | | SCALE: | NTS | SHEET : | 3 OF 4 | |
| | | RONTO, ONTARIO | ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE | DRAWING | NUMBER | | ISSUE |
| | YOUR CONNECTION TO QUA | MANUFACTURE OR SALE OF APPARATUS | | 3 | 33 Assembly | | 1 |

ISSUE NUMBER

ORIGINAL



Features

- .156 (3.96) Contact Spacing x .200 (5.08) Row Spacing
- Accepts .062 (1.57) Nominal Thickness P.C. Board
- High Profile Insulator Body .600 (15.24)
- Contact Termination Options include P.C. Tail, Wire Hole, Wire Wrap, 90 Degree, & Extender Board Bends
- Single or Dual Row Configurations
- Variety of Mounting Options, Flush or Offset Lugs
- Accepts Between Contact and In-Contact Polarizing Keys

Specifications

- Insulator Material: Thermoplastic Polyester, UL 94V-0, Colour: Green
- Contact Material: Copper, Nickel, Tin Alloy CA-725
- Contact Plating: Gold on the Mating Area, Tin on the Contact Tails, Nickel Underplate
- Current Rating: 3 Amperes Continuous
- Contact Resistance: 10 Milliohms Maximum
- Dielectric Withstanding Voltage: 1800 V AC rms at Sea Level Between Adjacent Contacts
- Insulation Resistance: 5000 Megohms Minimum
- Operating Temperature: -65 to +105 Degrees C
- Insertion Force: 16 oz (4.45 N) Maximum per Contact Pair when Tested with a .070 (1.78) Thick Gauge
- Withdrawal Force: 1 oz (0.28 N) Minimum per Contact Pair when Tested with a .054 (1.37) Thick Gauge

| 333 Series Card Edge Connector | ACAD REFERENCE NO. 333 ENG MASTER |
|------------------------------------|--|
| Features and Specifications | DRAWN: J.LEE DATE: OCT. 14/09 |
| realities and specifications | CHECKED: DATE: |
| | WINGS AND SPECIFICATIONS SCALE: NTS SHEET 4 OF 4 |
| I SI I I ORONTO, ONTARIO SHALL NOT | BE REPRODUCED, OR COPIED DRAWING NUMBER ISSUE |
| | JRE OR SALE OF APPARATUS 333 Assombly 1 |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EDAC:

333-044-542-803