Mounting Option 12-.128 (3.25) Dia. Side Mounting Holes **Contact Detail** 500-Wire Hole .050x.025(1.27x0.64) - Tail LG=.260(6.60) .156 [3.96] Contact Spacing x .200 [5.08] Row Spacing 5.161 [131.09] 5.000 [127.00] Card Slot Accepts .054 [1.37] to .070 (1.78) Thick P.C. Board 0.370 [9.40] 0.388 [9.86] Card Slot .160 [4.06] Point of Contact-0.350[8.89] SECTION A-A ACAD REFERENCE NO. 333 ENG MASTER 333 Series Card Edge Connector J.LEE DATE: OCT. 14/09 Part Number: 333-062-500-212 See Accompanying Page for: **Bend Detail** SHEET 1 OF 4 NTS

YOUR CONNECTION TO QUALITY & SERVICE

333 Assembly

Mounting Options

Features and Specifications

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.

ISSUE NUMBER

ORIGINAL

1



| 333 Series Card Edge Conn | ACAD REFERENCE NO. 333 ENG MASTER | | | |
|--|--|----------------|------------------|--------|
| Contact Bend Detail | | DRAWN: J.LEE | DATE: OCT. 14/09 | |
| Confider Bend Defail | CHECKED: | DATE: | | |
| EDAC INC | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INCAND | SCALE: NTS | SHEET 2 | 2 OF 4 |
| I I AII II | SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS | DRAWING NUMBER | | ISSUE |
| YOUR CONNECTION TO QUALITY & SERVICE | | 333 Assembly | | 1 |

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER



SSUE NUMBER

DRIGINAL

1



| 333 Series Card Edge Connector | | | ACAD REFERENCE NO. 333 ENG MASTER | | | |
|--------------------------------|---|--|-----------------------------------|-------------|-----------|--------|
| | | DRAWN: | J.LEE | DATE: O | CT. 14/09 | |
| | Mounting Options | | CHECKED: | | DATE: | |
| | EDAC INC THESE DRAWINGS AND SPECIFICATIONS | | SCALE: | NTS | SHEET : | 3 OF 4 |
| | IORONIO, ONIARIO SHALL NOT BE REPP OR USED AS THE BO WANUFACTURE OR S | ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE | DRAWING | NUMBER | | ISSUE |
| | | MANUFACTURE OR SALE OF APPARATUS | 3 | 33 Assembly | | 1 |

ISSUE NUMBER

ORIGINAL



Features

- .156 (3.96) Contact Spacing x .200 (5.08) Row Spacing
- Accepts .062 (1.57) Nominal Thickness P.C. Board
- High Profile Insulator Body .600 (15.24)
- Contact Termination Options include P.C. Tail, Wire Hole, Wire Wrap, 90 Degree, & Extender Board Bends
- Single or Dual Row Configurations
- Variety of Mounting Options, Flush or Offset Lugs
- Accepts Between Contact and In-Contact Polarizing Keys

Specifications

- Insulator Material: Thermoplastic Polyester, UL 94V-0, Colour: Green
- Contact Material: Copper, Nickel, Tin Alloy CA-725
- Contact Plating: Gold on the Mating Area, Tin on the Contact Tails, Nickel Underplate
- Current Rating: 3 Amperes Continuous
- Contact Resistance: 10 Milliohms Maximum
- Dielectric Withstanding Voltage: 1800 V AC rms at Sea Level Between Adjacent Contacts
- Insulation Resistance: 5000 Megohms Minimum
- Operating Temperature: -65 to +105 Degrees C
- Insertion Force: 16 oz (4.45 N) Maximum per Contact Pair when Tested with a .070 (1.78) Thick Gauge
- Withdrawal Force: 1 oz (0.28 N) Minimum per Contact Pair when Tested with a .054 (1.37) Thick Gauge

| 333 Series Card Edge Connector | ACAD REFERENCE NO. 333 ENG MASTER |
|--------------------------------|--|
| Features and Specifications | DRAWN: J.LEE DATE: OCT. 14/09 |
| realities and specifications | CHECKED: DATE: |
| | WINGS AND SPECIFICATIONS SCALE: NTS SHEET 4 OF 4 |
| | BE REPRODUCED, OR COPIED DRAWING NUMBER ISSUE |
| | JRE OR SALE OF APPARATUS 333 Assombly 1 |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EDAC:

333-062-500-212