

High Temperature Capacitors

85°C

- High temperature tolerant (-25 to $+85^{\circ}$ C) and highly reliable.
- Ideal for backing up of controls, electronic rice cooking jars, home bakeries and the like.



High temperature Miniaturized

DH


 DX DB

Marking color : White print on an indigo sleeve

Specifications

Item	Performance						
Category temperature range (°C)	-25 to +85						
Tolerance at rated capacitance (%)	-20 to +80						
Internal resistance	Rated capacitance (F)	0.047 0.1		0.22	0.47	0.68	1
at 1 kHz	Internal resistance (Ω Max.)	300	200	120	50	50	30
Characteristics at high	Percentage of capacitance change	of capacitance change Within ±30% of the value at 20°C					
and low temperature	Internal resistance	0℃					
	Test time 1000 hours						
Endurance (85°C)	Percentage of capacitance change	ge of capacitance change Within ±30% of the initial measured value					
	Internal resistance	Less than four times of the initial specified value					
Shelf life (85°C)	Test time: 1000 hours; Same as endurance.						
Applicable standards	Conforms to JIS C5160-1 2009 (IEC 62391-1 2006)						

Outline Drawing



Part numbering system (example : 5.5V0.1F)							
DH	_	5R5	D	104	Т		
Series code		Max.operating voltage symbol		Rated capacitance symbol			

Part number is refer to following table.

Standard Ratings

Max. operating voltage (V)	Rated capacitance (F)	ELNA Parts No.	φD×L (mm)
5.5	0.047	DH-5R5D473T	13.5×9.5
5.5	0.1	DH-5R5D104T	13.5×9.5
5.5	0.22	DH-5R5D224T	13.5×9.5
5.5	0.47	DH-5R5D474T	21.5×9.5
5.5	0.68	DH-5R5D684T	21.5×9.5
5.5	1	DH-5R5D105T	21.5×9.5

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Elna:

DH-5R5D104T DH-5R5D474T RSCH11045R5G09014T RSCH14745R5L09015T