

#2

0.73

**1** 640

(0.27)

0.25)

.18

#### SEIKO EPSON CORPORATION

### TCXO / VC-TCXO **HIGH STABILITY / Low noise**



Product Number TG2016SMN : X1G005441xxxx25 TG2520SMN : X1G005421xxxx27

**TG2016SMN / TG2520SMN** 

<ul> <li>Output frequency</li> </ul>	:	10 MHz to 55 MHz				
<ul> <li>Supply voltage</li> </ul>	:	1.8 V Typ./ 2.8 V Typ./ 3.0 V Typ./ 3.3 V Typ.				
<ul> <li>Frequency / temperature characteristics</li> </ul>						
	:	±0.5 × 10 <sup>-6</sup> Max. (-40 °C to +85 °C)				
		±2.0 × 10 <sup>-6</sup> Max. (-40 °C to +85 °C)				
<ul> <li>External dimensions</li> </ul>	s:	2.0 × 1.6 × 0.73 mm / 2.5 × 2.0 × 0.8 mm				
<ul> <li>Applications</li> </ul>	:	GPS, RF				
		Wireless communication devices				
		(LTE, WiMAX, Wi-Fi, W-LAN, IoT other)				
<ul> <li>Features</li> </ul>	:	Low noise				



TG2016SMN  $(2.0 \times 1.6 \times 0.73 \text{ mm})$ 




TG2520SMN  $(2.5 \times 2.0 \times 0.8 \text{ mm})$ 

Item	Symbol	тсхо		VC-TCXO			Condi	tions / R	emarks		
Rom	Cymbol		z to 55MHz				Contain		omanto		
Output frequency range	fo	16, 16.368, 16.369, 19.2, 20, 24, 25, 26,				Standard frequency					
1 1 9 0		27, 27.6, 30, 32, 38.4, 40, 48, 50, 52 MHz									
Supply voltage	Vcc	1.8 V $\pm$ 0.1 V / 2.8 V $\pm$ 5 % / 3.0 V $\pm$ 5 % / 3.3 V $\pm$ 5 %				Supply voltage range :1.7 V to 3.63 V					
Storage temperature range	T_stg	-40 °C to +90 °C					Storage as single product.				
Operating temperature range	T_use	G: -40 °C to +85 °C					After reflection 105 00				
Frequency tolerance Frequency/temperature	f_tol	$\pm 1.5 \times 10^{-6}$ Max.				After reflow, +25 °C					
characteristics	fo-Tc	C: ±0.5 × 10 <sup>-6</sup> Max. / -40 °C to +85 °C F: ±2.0 × 10 <sup>-6</sup> Max. / -40 °C to +85 °C				Standard stability version					
Frequency/load coefficient	fo-Load	±0.1 ×	10 <sup>-6</sup> Max.			$10 \text{ k}\Omega // 10 \text{ pF} \pm 10 \%$					
Frequency/voltage coefficient	fo-V <sub>CC</sub>	±0.1 ×	10 <sup>-6</sup> Max.			$V_{CC} \pm 5$ %					
Frequency aging	fage -	$\pm 0.5 \times 10^{\text{-6}}$ Max.				+25 °C, First year, fo = 10MHz, 12 MHz ≤ fo ≤ 20 MHz, 24 MHz ≤ fo ≤ 40 MHz					
	I_age	$\pm 1.5 \times 10^{\text{-6}}$ Max.				+25 °C ,First year, 10 MHz < fo < 12 MHz, 20 MHz < fo < 24 MHz, 40 MHz < fo ≤ 55 MHz					
Current consumption			nA Max.			10 MHz ≤ fo ≤ 26 MHz					
	lcc	1.8 mA Max.				26 MHz < fo ≤ 40 MHz					
	100	2.0 mA Max.				40 MHz < fo ≤ 50 MHz					
la se de se	Zin		2.1 mA Max.			50 MHz < fo $\leq$ 55 MHz					
Input impedance Z		500 kΩ Min				$V_{c} - GND (DC)$					
Frequency control range	f_cont	-	±	5.0 × 10 <sup>-6</sup> Min.	B: Vc = 0.9 V $\pm$ 0.6 V (V <sub>cc</sub> = 1.8 V) or C: Vc = 1.4 V $\pm$ 1.0 V (V <sub>cc</sub> = 2.8 V) or D: Vc = 1.5 V $\pm$ 1.0 V (V <sub>cc</sub> = 3.0 V) or E: Vc = 1.65 V $\pm$ 1.0 V (V <sub>cc</sub> = 3.3 V)						
Frequency change polarity	f_cp	- Positive polarity									
Symmetry	SYM	40 % to 60 %				GND level (DC cut)					
Output voltage	Vpp	0.8 V Min.				Peak to Peak					
Start-up time	t_str	1.0 ms Max.				t = 0 at 90% V <sub>CC</sub>					
Output load	Load_R Load C	10 kΩ				DC cut capacitor = 0.01 μF					
Note : Please contact us for re		10 pF									
	•	•		.®Vc function[Vc] (Symbol table)							
Product Name <u>TG20</u>	<u>16 SMN 26</u>	<u>.000000MHz E C G N</u>	<u>N</u> <u>M</u> 8 9	Voltage [V]		TCXO E:1.8		i i i i i i i i i i i i i i i i i i i	i i		
(Standard form) ①	$\overline{2}$	3 4 5 6 7		④V <sub>CC</sub> (Typ.)			E:1.8	B:2.8	A:3.0	C:3.3	
	(TG2016, T			(Typ.) ⑧Vc (Typ.)		:2.8 to 3.3 N: Non B 0.9 C:		C:1.4	D 1.5	E 1.65	
<sup>(2)</sup> Output (3. Clipped sille wave) <sup>(3)</sup> Frequency											
④ Supply voltage (Refer to symbol table) ⑤ Frequency / temperature characteristics (C: ±0.5 × 10 <sup>-6</sup> Max., F: ±2.0 × 10 <sup>-6</sup> Max.)											
		ature (G: -40 °C to +85 °C)									
		to symbol table , A: Vc =any	,								
External dimensions		(Unit:	mm)	Footprin	nt (Red	comme	ended)		(Unit: n	nm)	
TG2016SMN											
		#4 <del>2.5</del> #3		B							

(0.38) Pin map Pin Connection VC-TCXO тсхо #1 N.C.\*1 Vc GND S OUT ) e \*1) Please keep "N.C." pin OPEN condition or GND connection. "N.C." pin doesn't work as a ground pin. 

#4 (0.55)

1.5



For stable operation, please add a bypass Capacitor (0.01 uF to 0.1uF) between  $V_{\text{CC}}$  and GND. Please place it as close to TCXO as possible.

# PROMOTION OF ENVIRONMENTAL MANAGEMENT SYSTEM CONFORMING TO INTERNATIONAL STANDARDS

At Seiko Epson, all environmental initiatives operate under the Plan-Do-Check-Action (PDCA) cycle designed to achieve continuous improvements. The environmental management system (EMS) operates under the ISO 14001 environmental management standard.

All of our major manufacturing and non-manufacturing sites, in Japan and overseas, completed the acquisition of ISO 14001 certification.

#### WORKING FOR HIGH QUALITY

In order provide high quality and reliable products and services than meet customer needs, Seiko Epson made early efforts towards obtaining ISO9000 series certification and has acquired ISO9001 for all business establishments in Japan and abroad. We have also acquired IATF 16949 certification that is requested strongly by major automotive manufacturers as standard.

Explanation of the mark that are using it for the catalog

ISO 14000 is an international standard for environmental management that was established by the International Standards Organization in 1996 against the background of growing concern regarding global warming, destruction of the ozone layer, and global deforestation.

IATF 16949 is the international standard that added the sector-specific supplemental requirements for automotive industry based on ISO9001.

Pb Free	► Pb free.
RoHS	<ul> <li>Complies with EU RoHS directive.</li> <li>*About the products without the Pb-free mark.</li> <li>Contains Pb in products exempted by EU RoHS directive.</li> <li>(Contains Pb in sealing glass, high melting temperature type solder or other.)</li> </ul>
For Automotive	► Designed for automotive applications such as Car Multimedia, Body Electronics, Remote Keyless Entry etc.
Automotive Safety	► Designed for automotive applications related to driving safety (Engine Control Unit, Air Bag, ESC etc ).

#### NOTICE : PLEASE READ CAREFULLY BELOW BEFORE THE USE OF THIS DOCUMENT ©Seiko Epson Corporation 2020

- 1. The content of this document is subject to change without notice. Before purchasing or using Epson products, please contact with sales representative of Seiko Epson Corporation ("Epson") for the latest information and be always sure to check the latest information published on Epson's official web sites and resources.
- 2. This document may not be copied, reproduced, or used for any other purposes, in whole or in part, without Epson's prior consent.
- 3. Information provided in this document including, but not limited to application circuits, programs and usage, is for reference purpose only. Epson makes no guarantees against any infringements or damages to any third parties' intellectual property rights or any other rights resulting from the information. This document does not grant you any licenses, any intellectual property rights or any other rights with respect to Epson products owned by Epson or any third parties.
- 4. Using Epson products, you shall be responsible for safe design in your products; that is, your hardware, software, and/or systems shall be designed enough to prevent any critical harm or damages to life, health or property, even if any malfunction or failure might be caused by Epson products. In designing your products with Epson products, please be sure to check and comply with the latest information regarding Epson products (including, but not limited to this document, specifications, data sheets, manuals, and Epson's web site). Using technical contents such as product data, graphic and chart, and technical information, including programs, algorithms and application circuit examples under this document, you shall evaluate your products thoroughly both in stand-alone basis and within your overall systems. You shall be solely responsible for deciding whether to adopt/use Epson products with your products.
- 5. Epson has prepared this document carefully to be accurate and dependable, but Epson does not guarantee that the information is always accurate and complete. Epson assumes no responsibility for any damages you incurred due to any misinformation in this document.
- No dismantling, analysis, reverse engineering, modification, alteration, adaptation, reproduction, etc., of Epson products is allowed.
   Epson products have been designed, developed and manufactured to be used in general electronic applications and specifically designated applications ("Anticipated Purpose"). Epson products are NOT intended for any use beyond the Anticipated Purpose that requires particular quality or extremely high reliability in order to refrain from causing any malfunction or failure leading to critical harm to life and health, serious property damage, or severe impact on society, including, but not limited to listed below ("Specific Purpose"). Therefore, you are strongly advised to use Epson products only for the Anticipated Purpose. Should you desire to purchase and use Epson products for Specific Purpose, Epson makes no warranty and disclaims with respect to Epson products, whether express or implied, including without limitation any implied warranty of merchantability or fitness for any Specific Purpose. Please be sure to contact our sales representative in advance, if you desire Epson products for Specific Purpose:

Space equipment (artificial satellites, rockets, etc.)/ Transportation vehicles and their control equipment (automobiles, aircraft, trains, ships, etc.) / Medical equipment/ Relay equipment to be placed on sea floor/ Power station control equipment / Disaster or crime prevention equipment/Traffic control equipment/ Financial equipment Other equipment and the state of a list is a state of the state of the

Other applications requiring similar levels of reliability as the above

- 8. Epson products listed in this document and our associated technologies shall not be used in any equipment or systems that laws and regulations in Japan or any other countries prohibit to manufacture, use or sell. Furthermore, Epson products and our associated technologies shall not be used for the purposes of military weapons development (e.g. mass destruction weapons), military use, or any other military applications. If exporting Epson products or our associated technologies, please be sure to comply with the Foreign Exchange and Foreign Trade Control Act in Japan, Export Administration Regulations in the U.S.A (EAR) and other export-related laws and regulations in Japan and any other countries and to follow their required procedures.
- 9. Epson assumes no responsibility for any damages (whether direct or indirect) caused by or in relation with your non-compliance with the terms and conditions in this document or for any damages (whether direct or indirect) incurred by any third party that you give, transfer or assign Epson products.
- 10. For more details or other concerns about this document, please contact our sales representative.
- 11. Company names and product names listed in this document are trademarks or registered trademarks of their respective companies.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Epson:

TG2016SMN 16.0000M-ECGNNM0 TG2016SMN 16.0000M-ECGNNM5 TG2016SMN 16.0000M-ECGNNMB TG2016SMN 16.0000M-MCGNNM0 TG2016SMN 16.0000M-MCGNNM5 TG2016SMN 16.0000M-MCGNNMB TG2016SMN 16.3680M-ECGNNM0 TG2016SMN 16.3680M-ECGNNM5 TG2016SMN 16.3680M-ECGNNMB TG2016SMN 16.3680M-MCGNNM0 TG2016SMN 16.3680M-MCGNNM5 TG2016SMN 16.3680M-MCGNNMB TG2016SMN 16.3690M-ECGNNM5 TG2016SMN 16.3690M-MCGNNM0 TG2016SMN 16.3690M-MCGNNM5 TG2016SMN 16.3840M-MCGNNM0 TG2016SMN 16.3840M-MCGNNM3 TG2016SMN 16.3840M-MCGNNM5 TG2016SMN 19.2000M-BSGNBB0 TG2016SMN 19.2000M-ECGNNM0 TG2016SMN 19.2000M-ECGNNM5 TG2016SMN 19.2000M-MCGNNM0 TG2016SMN 19.2000M-MCGNNM5 TG2016SMN 19.2000M-TCGNNM5 TG2016SMN 20.0000M-ECGNNM0 TG2016SMN 20.0000M-ECGNNM5 TG2016SMN 20.0000M-ECGNNMB TG2016SMN 20.0000M-MCGNNM0 TG2016SMN 20.0000M-MCGNNM5 TG2016SMN 20.0000M-MCGNNMB TG2016SMN 20.0000M-TCGNNM0 TG2016SMN 20.0000M-TCGNNM3 TG2016SMN 20.0000M-TCGNNM5 TG2016SMN 24.0000M-ECGNNM0 TG2016SMN 24.0000M-ECGNNM5 TG2016SMN 24.0000M-ECGNNMB TG2016SMN 24.0000M-MCGNNM0 TG2016SMN 24.0000M-MCGNNM5 TG2016SMN 25.0000M-ECGNNM0 TG2016SMN 25.0000M-ECGNNM5 TG2016SMN 25.0000M-MCGNNM0 TG2016SMN 25.0000M-MCGNNM5 TG2016SMN 26.0000M-ACGNDM3 TG2016SMN 26.0000M-ECGNNM0 TG2016SMN 26.0000M-ECGNNM12 TG2016SMN 26.0000M-ECGNNMX TG2016SMN 26.0000M-MCGNNM0 TG2016SMN 26.0000M-MCGNNM5 TG2016SMN 27.0000M-ECGNNM0 TG2016SMN 27.0000M-ECGNNM5 TG2016SMN 27.0000M-ECGNNMB TG2016SMN 27.0000M-MCGNNM0 TG2016SMN 27.0000M-MCGNNM5 TG2016SMN 27.0000M-MCGNNMB TG2016SMN 27.6000M-ECGNNM0 TG2016SMN 27.6000M-ECGNNM5 TG2016SMN 27.6000M-MCGNNM0 TG2016SMN 27.6000M-MCGNNM5 TG2016SMN 30.0000M-ECGNNM0 TG2016SMN 30.0000M-ECGNNM5 TG2016SMN 30.0000M-MCGNNM0 TG2016SMN 30.0000M-MCGNNM5 TG2016SMN 32.0000M-ECGNNM0 TG2016SMN 32.0000M-ECGNNM5 TG2016SMN 32.0000M-MCGNNM0 TG2016SMN 32.0000M-MCGNNM5 TG2016SMN 32.0000M-MCGNNMB TG2016SMN 38.4000M-ECGNNM0 TG2016SMN 38.4000M-ECGNNM12 TG2016SMN 38.4000M-MCGNNM0 TG2016SMN 38.4000M-MCGNNM5 TG2016SMN 40.0000M-CCGNEMB TG2016SMN 40.0000M-ECGNNM0 TG2016SMN 40.0000M-ECGNNM5 TG2016SMN 40.0000M-ECGNNMB TG2016SMN 48.0000M-ECGNNM0 TG2016SMN 48.0000M-ECGNNM5 TG2016SMN 48.0000M-MCGNNM0

TG2016SMN 48.0000M-MCGNNM5	TG2016SMN 52.0000M-ECGNNM0	TG2016SMN 52.0000M-MCGNNM0
TG2016SMN 52.0000M-MCGNNM5	TG2016SMN 52.0000M-MCGNNMB	TG2016SMN 32.0000M-ECGNNMX
TG2016SMN 10.0000M-MCGNNM0	TG2016SMN 10.0000M-MCGNNM3	TG2016SMN 10.0000M-MCGNNM5
TG2016SMN 10.0000M-MCGNNMX	TG2016SMN 26.0000M-ZCGNNA0	TG2016SMN 26.0000M-ZCGNNAB
TG2016SMN 26.0000M-ZCGNNAX	TG2016SMN 32.0000M-TCGNNM0	TG2016SMN 38.4000M-ECGNBM0
TG2016SMN 38.4000M-ECGNBMB	TG2016SMN 38.4000M-EFGNNM0	TG2016SMN 38.4000M-TFGNNM0
TG2016SMN 38.4000M-TFGNNM5	TG2016SMN 38.4000M-TFGNNM6	TG2016SMN 40.0000M-CCGNEA0
TG2016SMN 40.0000M-CCGNEMX		