

A TyRex Technology Family Company

# HLC<sup>®</sup> SCRATCHGUARD<sup>®</sup> Test Reference Cables

# The Megladon Difference

**Test Reference Cables** manufactured by Megladon are the highest-performing fiber optic cables available and are specifically designed to be the ideal cord for testing fiber optic connectors.

Our team carefully selects all of the components, from precision-drilled ferrules to controlled core glass, to ensure the best possible performance from the assembly. We apply our patented HLC termination process to every connector, creating the best possible optical performance (IL & ORL) and unsurpassed endface durability. The extended durability of the HLC connectors ensures better test data over extended use and reduced expense in product testing.

For more information on Megladon's HLC process and products, please visit megladonmfg.com.

### **KEY BENEFITS**

- Exclusive HLC Termination Process
- ✓ SCRATCHGUARD Durable Mating Surface
- Available in all major connector & fiber types
- Exceptional Optical Performance
- High-Precision Materials
- Custom built for test application

## APPLICATIONS

- Fiber Optic Performance Testing
- Manufacturing Lines
- Fiber Loss Test Sets
- Optical Return Loss Meters
- Lab Instrumentation



# <section-header>

# PERFORMANCE CHARACTERISTICS

Megladon HLC SCRATCHGUARD Singlemode (SM) Test Reference Cables				
Wavelength 1310 & 1550				
UPC	Min	Max	Units	
Initial Insertion Loss (UPC)		-0.10	dB	
Initial Return Loss (UPC)		-60	dB	
APC	Min	Max	Units	
Initial Insertion Loss		-0.10	dB	
Initial Return Loss		-75	dB	

### Megladon HLC SCRATCHGUARD Multimode (MM) Test Reference Cables

Wavelength 850 & 1300			
UPC	Min	Max	Units
Initial Insertion Loss (UPC)		-0.07	dB
Initial Return Loss (UPC)		-45	dB

# **ENVIRONMENTAL CHARACTERISTICS**

Megladon HLC SCRATCHGUARD Test Reference Cables				
	Min	Max	Units	
Radius of Curvature (UPC)	10	20	mm	
Radius of Curvature (APC)	7	12	mm	
Apex Offset	0	25	um	
Fiber Height	-50	+25	nm	
Key Error (APC)	-0.2	0.2	degrees	
Angle (APC)	7.8	8.2	degrees	

# STANDARD CONNECTOR SPECS

Megladon HLC SCRATCHGUARD Test Reference Cables			
Mating Durability	1000+ mates		
Drill Hole	125um +0.5/-0um		
Concentricity	0.3um drill hole to ferrule		

# MEGLADDN<sup>®</sup> MANUFACTURING GROUP, LTD

Your Fiber Optic Solutions Partner • Reliable - Rugged - Repeatable

12317 Technology Blvd., Ste. 100 · Austin, Texas · (512) 491-0006 · megladonmfg.com

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Megladon Manufacturing:

<u>TRC-1ADS2-002M</u> <u>TRC-6ADS2-002M</u> <u>TRC-1AAS2-002M</u> <u>TRC-6ACS2-002M</u> <u>TRC-1ACS2-002M</u> <u>TRC-6AAS2-002M</u>