



DC2000B PCIe 4.0 NVMe M.2 SSD

Enterprise class for server applications

Kingston DC2000B is a high-performance PCIe 4.0 NVMe M.2 SSD that uses the latest Gen 4x4 PCIe interface with 112-layer 3D TLC NAND. Ideally suited for use in high-volume rack-mount servers as an internal boot drive(s) to preserve valuable front-loading drive bays, as well as for use in purpose-built systems where a high-performance M.2 SSD is needed that includes hardware-based on-board power loss protection (PLP). New for DC2000B is an integrated aluminium heatsink that offers broader thermal compatibility for a wide range of systems. DC2000B delivers low latency and excellent IO consistency to handle various workloads from boot drive applications to high-speed application caching. DC2000B is rated at 0.4 DWPD write endurance and carries a five-year warranty.

- PCIe 4.0 NVMe Gen 4x4 performance
- Hardware-based power loss protection
- Latency and IOPS consistency
- · Designed for data center environments



Key Features

PCIe 4.0 NVMe performance
 Utilises PCIe Gen 4x4 lanes for high-performance speeds.

On-board power loss protection (PLP)

- Reduce the possibility of data loss and/or corruption due to unexpected power-off.
- Low latency and IOPS consistency
 Firmware optimised to deliver low latency and IO consistency for high duty cycle workloads.
- Designed for data center environments
 Optimised to meet the demands of server boot applications with low latency and IO consistency as the key design

Specifications

| Form factor | M.2 2280 |
|---|---|
| Interface | PCIe 4.0 x4 NVMe |
| Capacities ¹ | 240GB, 480GB, 960GB |
| NAND | 3D TLC |
| Sequential read/write | 240GB - 4500/400 MBs 480GB - 7000/800 MBs 960GB - 7000/1300 MBs |
| Steady-state 4k read/write ² | 240GB - 260000/18000 IOPS 480GB - 530000/32000 IOPS 960GB - 540000/47000 IOPS |
| Total bytes written (TBW) ³ | 240GB - 175 TBW 480GB - 350 TBW 960GB - 700 TBW |



| Latency read (avg) | 240GB-960GB: 70μs |
|------------------------------------|--|
| Latency write (avg) | 240GB – 53μs 480GB – 29μs 960GB – 20μs |
| Power loss protection (power caps) | Yes |
| Enterprise SMART tools | Reliability tracking, usage statistics, SSD life remaining, wear levelling, temperature |
| Endurance | 240GB — (0.4 DWPD/5yrs) ⁴ 480GB — (0.4 DWPD/5yrs) ⁴ 960GB — (0.4 DWPD/5yrs) ⁴ |
| Power consumption | 240GB: Average read: 2.97W Average write: 4.02W Max read: 3.01W Max write: 4.09W 480GB: Average read: 3.22W Average write: 5.60W Max read: 3.29W Max write: 5.77W 960GB: Average read: 3.26W Average write: 7.36W Max read: 3.36W Max write: 7.80W |
| Storage temperature | -40°C ~ 85°C |
| Operating temperature | 0°C ~ 70°C |
| Dimensions | 80mm x 22mm x 8.3mm |
| Weight | 240GB - 9g 480GB - 10g 960GB - 11g |
| Vibration non-operating | 20G peak (10-2,000Hz) |



| MTBF | 2 million hours |
|-------------------------------|--|
| Warranty/support ⁵ | Limited five-year warranty with free technical support |

Part Numbers

SEDC2000BM8

| SEDC2000BM8/240G | |
|------------------|--|
| SEDC2000BM8/480G | |
| SEDC2000BM8/960G | |



Product Image



- 1. Some of the listed capacity on a Flash storage device is used for formatting and other functions and thus is not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the product. For more information go to Kingston's Flash Memory Guide.
- 2. Measurement taken once the workload has reached steady state but including all background activities required for normal operation and data reliability.
- 3. Total Bytes Written (TBW) is derived from the JEDEC Client Workload (JESD219A).
- 4. Drives Writes Per Day (DWPD) derived from the JEDEC Enterprise Workload (JESD219A).
- 5. Limited warranty based on 5 years or "Percentage Used" which can be found using the Kingston SSD Manager (kingston.com/ssdmanager). For NVMe SSDs, a new unused product will show a Percentage Used value of 0, whereas a product that reaches its warranty limit will show a Percentage Used value of greater than or equal to one hundred (100). See kingston.com/wa for details.



THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE.

©2024 Kingston Technology Europe Co LLP and Kingston Digital Europe Co LLP, Kingston Court, Brooklands Close, Sunbury-on-Thames, Middlesex, TW16 7EP, England. Tel: +44 (0) 1932 738888 Fax: +44 (0) 1932 785469 All rights reserved. All trademarks and registered trademarks are the property of their respective owners. MKD-07252024

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Kingston:

SEDC2000BM8/240G SEDC2000BM8/480G SEDC2000BM8/960G