



Industrial microSD Memory Card

Ideal for Extreme Conditions

Kingston's Industrial microSD card is designed and tested to withstand the most demanding environmental factors. With an operating temperature of -40°C to 85°C, it can operate normally even in extreme desert heat to below freezing conditions. The card utilizes industry-leading pSLC mode to provide top transfer speeds up to 100MB/s read and 80MB/s write¹. It is rated up to 1920 TBW² with 30K P/E cycles and a built-in feature set specific to endurance, performance, and industrial needs. Kingston's Industrial microSD ships with a UHS-I SD adapter and is available in capacities from 8GB-64GB³.

- Durable in Extreme Temperatures
- High Endurance
- UHS-I Speed Class U3, V30, A1
- Industrial Grade Built-In Features



Key Features

Durable in extreme temperatures

Designed and tested to withstand temperature range of -40°C to 85°C for use in harsh conditions

High endurance and reliability

Up to $1920~\text{TBW}^2$ and rated to endure 30K P/E cycles to meet requirements for a wide range of industrial applications

UHS-I compliant

Read/write speeds up to 100/80MB/s¹ with U3, V30, and A1 support for Android based applications

Industrial grade built-in features

Strong ECC engine, Wear Leveling, Bad Block management and an optional health monitoring tool to manage the lifespan of your card⁴

Specifications

Capacities ³	8GB, 16GB, 32GB, 64GB
Speed ¹	Up to 100MB/s read, 80MB/s write
Performance ¹	Class 10, UHS-I, U3, V30, A1
Endurance ²	Up to 1920 TBW 30K P/E cycles
NAND	TLC in pSLC mode
microSDHC Card Dimensions	11mm x 15mm x 1mm
SD Adapter Dimensions	24mm x 32mm x 2.1mm
Format	FAT32 for SDHC and ExFAT for SDXC
Operating & Storage Temperature	-40°C to 85°C



Voltage	3.3V
Industrial Features	 Bad Block Management Strong ECC Engine Power Failure Protection Wear Leveling Auto-Refresh Read Distribution Protection Dynamic Data Refresh SiP – System in Package Garbage Collection Health Monitoring
Durability	Waterproof ⁵ Temperature proof ⁶ Protected from airport x-rays ⁷
Thermal Cycle Testing	Interval testing completed at various extreme temperatures
Vigorous Temperature Humidity Bias	Several hundred hours of testing to ensure durability at varying levels of humidity
Wide Temp Chamber Testing	Completed on all SDCIT2 cards prior to production
Warranty ⁴	3 years

Part Numbers

Card (SD adapter included)

SDCIT2/8GB	
SDCIT2/16GB	



SDCIT2/32GB			
SDCIT2/64GB			

Card (SD adapter not included)

SDCIT2/8GBSP		
SDCIT2/16GBSP		
SDCIT2/32GBSP		
SDCIT2/64GBSP		



Product Image



- 1. Speed may vary due to host and device configuration.
- 2. Terabytes Written (TBW) is derived from the endurance under the highest capacity and is based on internal metrics that quantifies how much data can be written to a card in its lifespan.
- 3. Some of the listed capacity on a Flash storage device is used for formatting and other functions and thus is not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the product. For more information go to Kingston's Flash Memory Guide.
- 4. Kingston Flash Cards are designed and tested for compatibility with consumer-grade market products. It is recommended that you contact Kingston directly for any OEM opportunities or special use applications that are beyond standard daily consumer usage. For more information on intended use, please refer to the Flash Memory Guide
- 5. IEC/EN 60529 IPX7 certified for protection against continual water submersion up to 30 min. and depth up to 1m.
- 6. Withstands temperature range from -40 °C to 85 °C.
- 7. Protected against X-ray exposure based on ISO7816-1 guidelines.



THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE.

©2024 Kingston Technology Corporation, 17600 Newhope Street, Fountain Valley, CA 92708 USA. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. MKD-04122024

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Kingston:

SDCIT2/8GBCA SDCIT2/16GBCP SDCIT2/8GBCP SDCIT2/16GBCA SDCIT2/32GBCP SDCIT2/32GBCA SDCIT2/64GBCA SDCIT2/64GBCP