



CONTACT CONFIGURATION

SWITCH FUNCTION			
POS. 1	POS. 2	POS. 3	
DN	NONE	<DN>	
2-3	N/A	2-1	

< >=MOMENTARY

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: 0.0=±0.4
0.00=±0.25
 3. TERM. NOS. FOR REF. ONLY
 4. RATING: 0.4 (VA) max. @20 VAC or DC max.
 5. FIXED TERMINAL & MOVING CONTACT: Cu alloy w/ Au plate over Ni plate.
 6. ELECTRIC LIFE: 30,000 make-and-break cycles at full load.
 7. INSULATION RESISTANCE: 1,000 Mega-ohm min.
 8. DIELECTRIC STRENGTH: 1,000 V RMS @sea level.
 9. OPERATING TEMP.: -30°C to 85°C

E-SWITCH®

C	15214	CHANGES NOTED WITH	8/29/05	PH	TITLE 200 MSP2 T3 B2 M6 R E			
B	15039	CHANGED ACTUATOR LENGTH	7/1/05	JB				
A	10649	RELEASED FOR PRODUCTION	6/1/00	GLG	SCALE	DATE	DR	REV
REV.	ECN No.	DESCRIPTION	DATE	CHKD	2:1	5/25/00	GLG	C
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED								

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

E-Switch:

[200MSP2T3B2M6RE](#)