

Connecting comb 16-pole



product brand name	SIRIUS
product category	Connecting combs
product designation	Connecting comb
design of the product	For linking the same potentials, current carrying capacity for infeed max. 6 A/16-pole

### General technical data

display version LED	No
product component	
• semi-conductor output	No
flammability class of enclosure material	UL94 V-0
reference code according to IEC 81346-2	X
Substance Prohibitance (Date)	03/25/2015
product component plug-in socket	No

### Connections/ Terminals

product function removable terminal	No
-------------------------------------	----

### Installation/ mounting/ dimensions

height	3.3 mm
width	99 mm
depth	11 mm

### Ambient conditions

ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C

### Certificates/ approvals

General Product Approval	Declaration of Conformity	Marine / Shipping
--------------------------	---------------------------	-------------------



[Confirmation](#)



other

[Confirmation](#)

### Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RQ3901-0D>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RQ3901-0D>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<https://support.industry.siemens.com/cs/ww/en/ps/3RQ3901-0D>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RQ3901-0D&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RQ3901-0D&lang=en)

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3RQ3901-0D/manual>



last modified:

5/6/2021 

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

3RQ39010D