



Monitoring relay, can be mounted to Contactor 3RT2, Size S2 basic, analog adjustment Apparent current monitoring 8...80 A, 50...60 Hz, 2-phase Supply 24-240 V AC/DC 1 change-over contact Monitoring for Current overshoot and undershoot Phase failure, Cable break with or without fault buffer ON delay 0-60 s Noise pulse suppression 0-30 s Switching hysteresis 6% Screw connection system

| | |
|--|---|
| product brand name | SIRIUS |
| product designation | Monitoring relays |
| design of the product | analogically adjustable, 2-phase current monitoring |
| product type designation | 3RR2 |
| General technical data | |
| size of contactor can be combined company-specific | S2 |
| operating apparent power rated value | 4 VA |
| insulation voltage for overvoltage category III according to IEC 60664 | |
| • with degree of pollution 3 rated value | 690 V |
| surge voltage resistance rated value | 6 kV |
| consumed current at 24 V | 90 mA |
| protection class IP | |
| • on the front | IP20 |
| • of the terminal | IP00 |
| shock resistance | 10g / 11 ms |
| vibration resistance | 10 ... 55 Hz / 0.35 mm |
| mechanical service life (operating cycles) typical | 10 000 000 |
| electrical endurance (operating cycles) at AC-15 at 230 V typical | 100 000 |
| reference code according to IEC 81346-2 | K |
| relative repeat accuracy | 2 % |
| Substance Prohibitance (Date) | 03/01/2017 |
| Supply voltage | |
| type of voltage of the supply voltage | AC/DC |
| supply voltage 1 at AC | |
| • at 50 Hz | 24 ... 240 V |
| • at 60 Hz | 24 ... 240 V |
| supply voltage 1 at DC | 24 ... 240 V |
| supply voltage frequency 1 | 50 ... 60 Hz |
| Measuring circuit | |
| type of current for monitoring | AC |
| adjustable current response value current | |
| • 1 | 8 ... 80 A |
| • 2 | 8 ... 80 A |
| adjustable response delay time | |
| • when starting | 0 ... 60 s |
| • with lower or upper limit violation | 0 ... 30 s |
| Precision | |
| temperature drift per °C | 0.1 %/°C |

| | |
|---|--|
| Short-circuit protection | |
| design of the fuse link for short-circuit protection of the auxiliary switch required | fuse gG: 4 A |
| Communication/ Protocol | |
| protocol is supported IO-Link protocol | No |
| type of voltage supply via input/output link master | No |
| Auxiliary circuit | |
| number of CO contacts | |
| • for auxiliary contacts | 1 |
| operational current of auxiliary contacts at AC-15 | |
| • at 24 V | 3 A |
| • at 230 V | 3 A |
| • at 400 V | 3 A |
| operational current of auxiliary contacts at DC-13 | |
| • at 24 V | 1 A |
| • at 125 V | 0.2 A |
| • at 250 V | 0.1 A |
| contact rating of auxiliary contacts according to UL | B300 / R300 |
| Main circuit | |
| operating power rated value | 2.5 W |
| ampacity of the semiconductor output in SIO mode | 20 mA |
| operational current at 17 V minimum | 5 mA |
| Electromagnetic compatibility | |
| EMC emitted interference according to IEC 60947-1 | ambience A (industrial sector) |
| EMC immunity according to IEC 60947-1 | ambience A (industrial sector) |
| Connections/ Terminals | |
| product component removable terminal for main circuit | No |
| product component removable terminal for auxiliary and control circuit | Yes |
| type of electrical connection | |
| • for main current circuit | screw-type terminals |
| • for auxiliary and control circuit | screw-type terminals |
| type of connectable conductor cross-sections for main contacts | |
| • solid | 2x (1 ... 35 mm ²), 1x (1 ... 50 mm ²) |
| • stranded | 2x (1 ... 35 mm ²), 1x (1 ... 50 mm ²) |
| • finely stranded with core end processing | 2x (1 ... 25 mm ²), 1x (1 ... 35 mm ²) |
| connectable conductor cross-section for main contacts | |
| • solid or stranded | 1 ... 50 mm ² |
| • finely stranded with core end processing | 1 ... 35 mm ² |
| type of connectable conductor cross-sections | |
| • for auxiliary contacts | |
| — solid | 1x (0.5 ... 4 mm ²), 2x (0.5 ... 2.5 mm ²) |
| — finely stranded with core end processing | 1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.5 mm ²) |
| • for AWG cables for auxiliary contacts | 2x (20 ... 14) |
| AWG number as coded connectable conductor cross section for main contacts | 18 ... 1 |
| tightening torque with screw-type terminals | 0.8 ... 1.2 N·m |
| Installation/ mounting/ dimensions | |
| mounting position | any |
| fastening method | direct mounting |
| height | 99 mm |
| width | 55 mm |
| depth | 112 mm |
| required spacing | |
| • with side-by-side mounting | |
| — forwards | 0 mm |
| — backwards | 0 mm |
| — upwards | 0 mm |
| — downwards | 10 mm |
| — at the side | 0 mm |
| • for grounded parts | |

- forwards 10 mm
- backwards 0 mm
- upwards 10 mm
- at the side 10 mm
- downwards 10 mm
- for live parts
 - forwards 10 mm
 - backwards 0 mm
 - upwards 10 mm
 - downwards 10 mm
 - at the side 10 mm

Ambient conditions

| | |
|---|----------------|
| installation altitude at height above sea level maximum | 2 000 m |
| ambient temperature | |
| • during operation | -25 ... +60 °C |
| • during storage | -40 ... +80 °C |

Certificates/ approvals

General Product Approval

EMC



[Confirmation](#)



Declaration of Conformity

Test Certificates

Marine / Shipping



EG-Konf.

[Special Test Certificate](#)



ABS



LRS



PRS

Marine / Shipping

other



[Confirmation](#)

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RR2143-1AW30>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RR2143-1AW30>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)




<https://support.industry.siemens.com/cs/ww/en/ps/3RR2143-1AW30>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RR2143-1AW30&lang=en

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/3RR2143-1AW30/manual>



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

[3RR21431AW30](#)