SIEMENS

Data sheet



key-operated switch Siemens, 22 mm, round, plastic, special lock, with 2 keys, 2 switch positions O-I, latching, actuating angle $90^\circ,\,10:30h/13:30h,$ key removal O+I

product brand name SIRIUS ACT Product designation Key-operated switches	nroduct brand namo	SIRIUS ACT
design of the product product type designation product time Plastic, black, 22 mm Actuator principle of operation of the actuating element product extension optional light source color of the actuating element silver material of the actuating element shape of possible of the actuating element shape of the actuati	•	
product type designation product line Plastic, black, 22 mm Actuator principle of operation of the actuating element product extension optional light source of the actuating element material of the actuating element silver material of the actuating element silver outer diameter of the actuating element (Key outer diameter of the actuating element number of switching positions 2 switch position for key distraction actuating angle olockwise lock make Siemens Front ring product component front ring design of the front ring plastic color of the front ring plack General technical data protection class IP of the terminal degree of protection NEMA rating shock resistance according to IEC 60068-2-27 for railway applications according to EN 61373 operating frequency maximum About the fire of the control of the Color of the Color of the formal protection resistance according to IEC 60068-2-8 of or railway applications according to EN 61373 operating frequency maximum About the color of		
product line Plastic, black, 22 mm Actuator principle of operation of the actuating element latching, 90* (10:30 h/13:30 h) product extension optional light source No of the actuating element silver material of the actuating element metal shape of the actuating element Key outer diameter of the actuating element 29.5 mm number of switching positions 2 switch position for key distraction O+1 actuating angle clockwise 90*		
Actuator principle of operation of the actuating element product extension optional light source color • of the actuating element material of the actuating element silver outer diameter of the actuating element color actuating positions 2 switch position for key distraction actuating angle • clockwise lock make Front ring product component front ring design of the front ring design of the front ring color of the front ring black General technical data Protection ABMA rating • of the terminal degree of protection NEMA rating • according to IEC 60068-2-27 • for railway applications according to EN 61373 vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 Category 1, Class B vibration Feroit color of the Government of the G		
principle of operation of the actuating element product extension optional light source color • of the actuating element material of the actuating element shape of the actuating element very outer diameter of the actuating element number of switching positions 2 switch position for key distraction actuating angle • clockwise lock make Front ring product component front ring design of the front ring material of the front ring standard material of the front ring plastic color of the front ring protection class IP • of the terminal degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 • for railway applications according to EN 61373 vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 category 1, Class B vibration resistance • according for IEC 60068-2-6 • for railway applications according to EN 61373 category 1, Class B vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 category 1, Class B vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 category 1, Class B vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 category 1, Class B vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 category 1, Class B vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 category 1, Class B vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 category 1, Class B vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 category 1, Class B	·	i idolo, bidon, LL IIIII
product extension optional light source color of the actuating element shape of the actuating element 29.5 mm number of switching positions 2 switch position for key distraction actuating angle olockwise lock make Siemens Front ring product component front ring design of the front ring material of the front ring standard material of the front ring color of the front ring protection class IP of the terminal lipzo degree of protection NEMA rating shock resistance according to IEC 60068-2-7 sinusoidal half-wave 15g / 11 ms caterial risa (Category 1, Class B vibration resistance according to IEC 60068-2-6 of or railway applications according to EN 61373 Category 1, Class B vibration resistance according to IEC 60068-2-6 of or railway applications according to EN 61373 Category 1, Class B vibration resistance according to IEC 60068-2-6 of or railway applications according to EN 61373 Category 1, Class B vibration resistance according to IEC 60068-2-6 of or railway applications according to EN 61373 Category 1, Class B vibration resistance according to IEC 61346-2 Substance Prohibitance (Date) B10 value with high demand rate according to SN 31920 100 000		latching 00° (10:30 h/13:30 h)
color • of the actuating element material of the actuating element shape of the actuating element cuter diameter of the actuating element number of switching positions 2 switch position for key distraction actuating angle • clockwise 10ck make Siemens Front ring product component front ring design of the front ring material of the front ring color of the front ring plastic color of the front ring plastic color of the front ring for the terminal degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 • for railway applications according to EN 61373 vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 category 1, Class B operating frequency maximum 1800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) B10 value with high demand rate according to SN 31920 100 000		
• of the actuating element metal shape of the actuating element Key outer diameter of the actuating element 29.5 mm number of switching positions 2 switch position for key distraction O+I actuating angle • clockwise 90° lock make Siemens Front ring product component front ring Standard material of the front ring plastic color of the front ring black General technical data protection class IP • of the terminal IP20 degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance • according to IEC 60068-2-27 • for railway applications according to EN 61373 operating frequency maximum 1800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 S Substance Prohibitance (Date) Safety related data B10 value with high demand rate according to SN 31920 100 000	<u> </u>	NO
material of the actuating element Key outer diameter of the actuating element 29.5 mm number of switching positions 2 switch position for key distraction O+I actuating angle electockwise 90° lock make Siemens Front ring product component front ring Yes design of the front ring plastic color of the front ring black General technical data protection class IP of the terminal IP20 degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance according to IEC 60068-2-27 of or railway applications according to EN 61373 Category 1, Class B vibration resistance according to IEC 60068-2-6 of or railway applications according to EN 61373 Category 1, Class B operating frequency maximum 1800 17h mechanical service life (operating cycles) typical 1000 000 safety related data B10 value with high demand rate according to SN 31920 100 000		silver
shape of the actuating element		
outer diameter of the actuating element number of switching positions 2 switch position for key distraction actuating angle clockwise 90° lock make Siemens Front ring product component front ring design of the front ring attenting material of the front ring black General technical data protection class IP of the terminal degree of protection NEMA rating shock resistance according to IEC 60068-2-27 iof railway applications according to EN 61373 category 1, Class B vibration resistance according to IEC 60068-2-6 of or railway applications according to EN 61373 category 1, Class B operating frequency maximum nechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Safety related data B10 value with high demand rate according to SN 31920 100 000		
number of switching positions 2 switch position for key distraction O+I actuating angle		·
switch position for key distraction actuating angle clockwise po° lock make Siemens Front ring product component front ring design of the front ring material of the front ring color of the front ring protection class IP of the terminal lp20 degree of protection NEMA rating shock resistance according to IEC 60068-2-27 for railway applications according to EN 61373 vibration resistance according to IEC 60068-2-6 for railway applications according to EN 61373 category 1, Class B vibration resistance according to IEC 60068-2-6 for railway applications according to EN 61373 category 1, Class B vibration resistance according to IEC 60068-2-6 for railway applications according to EN 61373 category 1, Class B vibration resistance according to IEC 60068-2-6 for railway applications according to EN 61373 category 1, Class B operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) 10/01/2014 Bato vibration resistance 10 0000		
actuating angle • clockwise lock make Front ring product component front ring design of the front ring material of the front ring color of the front ring plastic color of the front ring black General technical data protection class IP of the terminal lp20 degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 of or railway applications according to EN 61373 vibration resistance • according to IEC 60068-2-6 of or railway applications according to EN 61373 category 1, Class B vibration resistance • according to IEC 60068-2-6 of or railway applications according to EN 61373 category 1, Class B operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) B10 value with high demand rate according to SN 31920 100 000		-
clockwise 90°		
Iock make Siemens		90°
product component front ring product component front ring design of the front ring material of the front ring plastic color of		
product component front ring design of the front ring material of the front ring color of the front ring black General technical data protection class IP of the terminal degree of protection NEMA rating shock resistance according to IEC 60068-2-27 of or railway applications according to EN 61373 vibration resistance according to IEC 60068-2-6 of or railway applications according to EN 61373 category 1, Class B vibration resistance of or railway applications according to EN 61373 category 1, Class B operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) 1000 000 1000 000		
design of the front ring material of the front ring plastic color of the front ring black General technical data protection class IP of the terminal lP20 degree of protection NEMA rating shock resistance according to IEC 60068-2-27 of or railway applications according to EN 61373 vibration resistance according to IEC 60068-2-6 of or railway applications according to EN 61373 category 1, Class B vibration resistance of or railway applications according to EN 61373 category 1, Class B vibration resistance of or railway applications according to EN 61373 category 1, Class B vibration resistance of or railway applications according to EN 61373 category 1, Class B vibration resistance of or railway applications according to EN 61373 category 1, Class B vibration requency maximum 1 800 1/h mechanical service life (operating cycles) typical 1 000 000 reference code according to IEC 81346-2 Substance Prohibitance (Date) 10/01/2014 Safety related data B10 value with high demand rate according to SN 31920 100 000	product component front ring	Yes
material of the front ring black General technical data protection class IP IP66, IP67, IP69(IP69K) of the terminal IP20 degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance oaccording to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms for railway applications according to EN 61373 Category 1, Class B vibration resistance oaccording to IEC 60068-2-6 10 500 Hz: 5g for railway applications according to EN 61373 Category 1, Class B operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical 1 000 000 reference code according to IEC 81346-2 S Substance Prohibitance (Date) 100 000 B10 value with high demand rate according to SN 31920 100 000		Standard
protection class IP of the terminal liP20 degree of protection NEMA rating shock resistance according to IEC 60068-2-27 for railway applications according to EN 61373 vibration resistance according to IEC 60068-2-6 for railway applications according to EN 61373 category 1, Class B vibration resistance according to IEC 60068-2-6 for railway applications according to EN 61373 category 1, Class B operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) B10 value with high demand rate according to SN 31920 100 000		plastic
protection class IP	color of the front ring	black
of the terminal degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance • according to IEC 60068-2-27	General technical data	
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance • according to IEC 60068-2-27 • for railway applications according to EN 61373 vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 Category 1, Class B vibration resistance • for railway applications according to EN 61373 Category 1, Class B operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Safety related data B10 value with high demand rate according to SN 31920 100 000	protection class IP	IP66, IP67, IP69(IP69K)
shock resistance • according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms • for railway applications according to EN 61373 Category 1, Class B vibration resistance • according to IEC 60068-2-6 10 500 Hz: 5g • for railway applications according to EN 61373 Category 1, Class B operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical 1 000 000 reference code according to IEC 81346-2 S Substance Prohibitance (Date) 10/01/2014 Safety related data B10 value with high demand rate according to SN 31920 100 000	of the terminal	IP20
according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms for railway applications according to EN 61373 Category 1, Class B vibration resistance according to IEC 60068-2-6 for railway applications according to EN 61373 Category 1, Class B operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Safety related data B10 value with high demand rate according to SN 31920 100 000	degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13
for railway applications according to EN 61373 Category 1, Class B vibration resistance	shock resistance	
vibration resistance • according to IEC 60068-2-6 • for railway applications according to EN 61373 Category 1, Class B operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Safety related data B10 value with high demand rate according to SN 31920 10 500 Hz: 5g Category 1, Class B 10 800 1/h 1 000 000 1 000 000 1 000 000	 according to IEC 60068-2-27 	sinusoidal half-wave 15g / 11 ms
 according to IEC 60068-2-6 for railway applications according to EN 61373 Category 1, Class B operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical 1 000 000 reference code according to IEC 81346-2 Substance Prohibitance (Date) 10/01/2014 Safety related data B10 value with high demand rate according to SN 31920 100 000 	 for railway applications according to EN 61373 	Category 1, Class B
	vibration resistance	
operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Safety related data B10 value with high demand rate according to SN 31920 1 800 1/h 1 000 000 1 000 000	according to IEC 60068-2-6	10 500 Hz: 5g
mechanical service life (operating cycles) typical 1 000 000 reference code according to IEC 81346-2 S Substance Prohibitance (Date) 10/01/2014 Safety related data B10 value with high demand rate according to SN 31920 100 000	 for railway applications according to EN 61373 	Category 1, Class B
reference code according to IEC 81346-2 S Substance Prohibitance (Date) 10/01/2014 Safety related data B10 value with high demand rate according to SN 31920 100 000	operating frequency maximum	1 800 1/h
Substance Prohibitance (Date) 10/01/2014 Safety related data B10 value with high demand rate according to SN 31920 100 000	mechanical service life (operating cycles) typical	1 000 000
Safety related data B10 value with high demand rate according to SN 31920 100 000	reference code according to IEC 81346-2	S
B10 value with high demand rate according to SN 31920 100 000	Substance Prohibitance (Date)	10/01/2014
	Safety related data	
proportion of dangerous failures	B10 value with high demand rate according to SN 31920	100 000
	proportion of dangerous failures	

 with low demand rate according to SN 31920 	20 %
 with high demand rate according to SN 31920 	20 %
failure rate [FIT] with low demand rate according to SN 31920	100 FIT
Ambient conditions	
ambient temperature	
during operation	-25 +70 °C
during storage	-40 +80 °C
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	61 mm
installation width	29.5 mm
installation depth	25.4 mm
Certificates/ approvals	
Further information	

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1000-5BF11-0AA0-Z Y01

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1000-5BF11-0AA0-Z Y01

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1000-5BF11-0AA0-Z Y01

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1000-5BF11-0AA0-Z Y01&lang=en

		_
last modified:	1/26/2022	7

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

A6X30135988