

Siemens  
EcoTech




Selector switch, illuminable, 22 mm, round, plastic, green, selector switch, short, 3 switch positions I>O<II, momentary contact type, actuating angle 2x45°, 10:30h/12h/13:30h



|                                                    |                                                                       |
|----------------------------------------------------|-----------------------------------------------------------------------|
| product brand name                                 | SIRIUS ACT                                                            |
| product designation                                | Selector switches                                                     |
| design of the product                              | Actuating/signaling element                                           |
| product type designation                           | 3SU1                                                                  |
| product line                                       | Plastic, black, 22 mm                                                 |
| <b>Enclosure</b>                                   |                                                                       |
| number of command points                           | 1                                                                     |
| <b>Actuator</b>                                    |                                                                       |
| design of the actuating element                    | Selector, short                                                       |
| principle of operation of the actuating element    | momentary contact, 2x45° (10:30 h/12 h/13:30 h), return on both sides |
| product extension optional                         |                                                                       |
| • light source                                     | Yes                                                                   |
| • contact module                                   | Yes                                                                   |
| color of the actuating element                     | green                                                                 |
| material of the actuating element                  | plastic                                                               |
| shape of the actuating element                     | Handle                                                                |
| outer diameter of the actuating element            | 32.3 mm                                                               |
| number of switching positions                      | 3                                                                     |
| actuating angle                                    |                                                                       |
| • clockwise                                        | 45°                                                                   |
| • anticlockwise                                    | 45°                                                                   |
| <b>Front ring</b>                                  |                                                                       |
| product component front ring                       | Yes                                                                   |
| design of the front ring                           | standard                                                              |
| material of the front ring                         | plastic                                                               |
| color of the front ring                            | black                                                                 |
| <b>General technical data</b>                      |                                                                       |
| protection class IP                                | IP66, IP67, IP69(IP69K)                                               |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13                                            |
| shock resistance                                   |                                                                       |
| • according to IEC 60068-2-27                      | sinusoidal half-wave 15g / 11 ms                                      |
| • for railway applications according to EN 61373   | Category 1, Class B                                                   |
| vibration resistance                               |                                                                       |
| • according to IEC 60068-2-6                       | 10 ... 500 Hz: 5g                                                     |
| • for railway applications according to EN 61373   | Category 1, Class B                                                   |
| operating frequency maximum                        | 1 800 1/h                                                             |
| mechanical service life (operating cycles) typical | 1 000 000                                                             |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| reference code according to IEC 81346-2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | S                                                                  |
| Substance Prohibittance (Date)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 10/01/2014                                                         |
| <b>Safety related data</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                    |
| proportion of dangerous failures                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                    |
| • with low demand rate according to SN 31920                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | 20 %                                                               |
| • with high demand rate according to SN 31920                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 20 %                                                               |
| B10 value with high demand rate according to SN 31920                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 300 000                                                            |
| failure rate [FIT] with low demand rate according to SN 31920                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 100 FIT                                                            |
| <b>Ambient conditions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                    |
| ambient temperature                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                    |
| • during operation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -25 ... +70 °C                                                     |
| • during storage                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | -40 ... +80 °C                                                     |
| environmental category during operation according to IEC 60721                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| <b>Environmental footprint</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                    |
| Environmental Product Declaration (EPD)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Yes                                                                |
| Global Warming Potential [CO2 eq] total                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 0.787 kg                                                           |
| Global Warming Potential [CO2 eq] during manufacturing                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 0.566 kg                                                           |
| Global Warming Potential [CO2 eq] during operation                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 0.235 kg                                                           |
| Global Warming Potential [CO2 eq] after end of life                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | -0.015 kg                                                          |
| Siemens Eco Profile (SEP)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Siemens EcoTech                                                    |
| <b>Installation/ mounting/ dimensions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                    |
| height                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 32.3 mm                                                            |
| width                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 32.3 mm                                                            |
| shape of the installation opening                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | round                                                              |
| mounting diameter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 22.3 mm                                                            |
| positive tolerance of installation diameter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 0.4 mm                                                             |
| mounting height                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 28.8 mm                                                            |
| installation width                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 32.3 mm                                                            |
| installation depth                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 25.4 mm                                                            |
| <b>Approvals Certificates</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                    |
| General Product Approval                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Test Certificates                                                  |
| <div>   <a href="#">Confirmation</a>   <a href="#">Type Test Certificates/Test Report</a> </div>                                                                                                                                                                                                                                                                                                                                                      |                                                                    |
| Test Certificates                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Marine / Shipping                                                  |
| <div> <a href="#">Special Test Certificate</a>     <a href="#">Confirmation</a> </div>                                                                                                                                                                                                                                                                                                                                                                |                                                                    |
| <b>Environment</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                    |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                    |
| <b>Further information</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                    |
| Information on the packaging<br><a href="https://support.industry.siemens.com/cs/ww/en/view/109813875">https://support.industry.siemens.com/cs/ww/en/view/109813875</a><br>Information- and Downloadcenter (Catalogs, Brochures,...)<br><a href="https://www.siemens.com/ic10">https://www.siemens.com/ic10</a><br>Industry Mall (Online ordering system)<br><a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1002-2BM40-0AA0">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1002-2BM40-0AA0</a><br>Cax online generator<br><a href="http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&amp;mlfb=3SU1002-2BM40-0AA0">http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&amp;mlfb=3SU1002-2BM40-0AA0</a> |                                                                    |



last modified:

2/6/2024 

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Siemens:](#)

[3SU10022BM400AA0](#)