3SU1050-0AA10-0AA0-Z Y15

Data sheet



Pushbutton, 22 mm, round, metal, shiny, black, pushbutton, flat, latching, Push-to-release mechanism, with laser labeling, upper case and lower case, always upper case at the beginning of the word

product brand name	SIRIUS ACT
product designation	Pushbuttons
design of the product	Actuating/signaling element
product type designation	3SU1
product line	Metal, shiny, 22 mm
Enclosure	
number of command points	1
Actuator	
design of the actuating element	Flat button
principle of operation of the actuating element	latching
product extension optional	
• light source	No
contact module	Yes
color of the actuating element	black
material of the actuating element	plastic
shape of the actuating element	round
outer diameter of the actuating element	29.5 mm
marking of the actuating element	Customized labeling, text in lower case / capital letters, all words start with capital letters
type of unlocking device	push-to-unlatch mechanism
Front ring	
product component front ring	Yes
design of the front ring	Standard
	Standard
material of the front ring	Metal, high gloss
material of the front ring	Metal, high gloss
material of the front ring color of the front ring	Metal, high gloss
material of the front ring color of the front ring General technical data	Metal, high gloss silver
material of the front ring color of the front ring General technical data protection class IP	Metal, high gloss silver IP66, IP67, IP69(IP69K)
material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating	Metal, high gloss silver IP66, IP67, IP69(IP69K)
material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance	Metal, high gloss silver IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13
material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27	Metal, high gloss silver IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13
material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance	Metal, high gloss silver IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms
material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6	Metal, high gloss silver IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms 10 500 Hz: 5g
material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum	Metal, high gloss silver IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms 10 500 Hz: 5g 1 800 1/h
material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance	Metal, high gloss silver IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms 10 500 Hz: 5g 1 800 1/h 500 000
material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2	Metal, high gloss silver IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms 10 500 Hz: 5g 1 800 1/h 500 000 S
material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date)	Metal, high gloss silver IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms 10 500 Hz: 5g 1 800 1/h 500 000 S
material of the front ring color of the front ring General technical data protection class IP degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions	Metal, high gloss silver IP66, IP67, IP69(IP69K) 1, 2, 3, 3R, 4, 4X, 12, 13 sinusoidal half-wave 15g / 11 ms 10 500 Hz: 5g 1 800 1/h 500 000 S

environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	11 mm
installation width	29.5 mm
installation depth	24.3 mm
Further information	

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-0AA10-0AA0-Z Y15

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1050-0AA10-0AA0-Z Y15

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-0AA10-0AA0-Z Y15

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-0AA10-0AA0-Z Y15&lang=en

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

A6X30140578