SIEMENS

Data sheet

3SU1050-5JL01-0AA0-Z Y01

	key-operated switch Siemens with key monitoring, 22 mm, round, special lock, with 2 keys, 3 switch positions I-O-II, latching, actuating angle 2x45°,
	10:30h/12h/13:30h, key removal/ejection in O
product brand name	SIRIUS ACT
product designation	Key-operated switches
design of the product	Actuating/signaling element
product type designation	3SU1
product line	Metal, shiny, 22 mm
Actuator	
principle of operation of the actuating element	latching, 2x45° (10:30 h/12 h/13:30 h)
product extension optional light source	No
color	
of the actuating element	silver
material of the actuating element	metal
shape of the actuating element	Key
outer diameter of the actuating element	29.5 mm
number of switching positions	3
switch position for key distraction	0
actuating angle	
• clockwise	45°
anticlockwise	45°
	Siemens
Front ring	
	Yes
product component front ring	Standard
design of the front ring	
_ material of the front ring color of the front ring	Metal, high gloss silver
General technical data	
protection class IP	
of the terminal	IP66, IP67, IP69(IP69K) IP20
degree of protection NEMA rating	
	1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance	sigurgidal half ways 15g / 11 mg
shock resistance • according to IEC 60068-2-27	sinusoidal half-wave 15g / 11 ms
shock resistance • according to IEC 60068-2-27 vibration resistance	
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6	10 500 Hz: 5g
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum	10 500 Hz: 5g 1 800 1/h
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical	10 500 Hz: 5g 1 800 1/h 300 000
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2	10 500 Hz: 5g 1 800 1/h 300 000 S
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date)	10 500 Hz: 5g 1 800 1/h 300 000
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions	10 500 Hz: 5g 1 800 1/h 300 000 S
shock resistance according to IEC 60068-2-27 vibration resistance according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature 	10 500 Hz: 5g 1 800 1/h 300 000 S 10/01/2014
shock resistance according to IEC 60068-2-27 vibration resistance according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature during operation 	10 500 Hz: 5g 1 800 1/h 300 000 S 10/01/2014 -25 +70 °C
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage	10 500 Hz: 5g 1 800 1/h 300 000 S 10/01/2014 -25 +70 °C -40 +80 °C
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721	10 500 Hz: 5g 1 800 1/h 300 000 S 10/01/2014 -25 +70 °C
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions	10 500 Hz: 5g 1 800 1/h 300 000 S 10/01/2014 -25 +70 °C -40 +80 °C 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions height	10 500 Hz: 5g 1 800 1/h 300 000 S 10/01/2014 -25 +70 °C -40 +80 °C 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%) 29.5 mm
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions height width	10 500 Hz: 5g 1 800 1/h 300 000 S 10/01/2014 -25 +70 °C -40 +80 °C 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%) 29.5 mm 29.5 mm
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions height width shape of the installation opening	10 500 Hz: 5g 1 800 1/h 300 000 S 10/01/2014 -25 +70 °C -40 +80 °C 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%) 29.5 mm 29.5 mm round
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions height width	10 500 Hz: 5g 1 800 1/h 300 000 S 10/01/2014 -25 +70 °C -40 +80 °C 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%) 29.5 mm 29.5 mm
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions height width shape of the installation opening	10 500 Hz: 5g 1 800 1/h 300 000 S 10/01/2014 -25 +70 °C -40 +80 °C 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%) 29.5 mm 29.5 mm round
shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation • during storage environmental category during operation according to IEC 60721 Installation/ mounting/ dimensions height width shape of the installation opening mounting diameter	10 500 Hz: 5g 1 800 1/h 300 000 S 10/01/2014 -25 +70 °C -40 +80 °C 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%) 29.5 mm 29.5 mm round 22.3 mm

installation depth	25.4 mm
Certificates/ approvals	
Further information	
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business	
Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).	
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures)	
https://www.siemens.com/ic10 Industry Mall (Online ordering system)	
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-5JL01-0AA0-Z Y01	
Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1050-5JL01-0AA0-Z Y01	
Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-5JL01-0AA0-Z Y01	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,)	

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-5JL01-0AA0-Z Y01&lang=en

last modified:

1/26/2022 🖸

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens: A6X30145809