



Pushbutton, compact, with extended stroke (12 mm), 22 mm, round, Metal, black, pushbutton, high, momentary contact type, with holder, with laser labeling, upper case and lower case, always upper case at the beginning of the word

|  |   |
|--|---|
| product brand name                                 | SIRIUS ACT  |
| product designation                                | Pushbuttons   |
| design of the product                              | Complete unit   |
| product type designation                           | 3SU1  |
| product line                                       | Metal, shiny, 22 mm   |
| <b>Enclosure</b>                                   |   |
| number of command points                           | 1   |
| <b>Actuator</b>                                    |   |
| design of the actuating element                    | Flat button with extended stroke  |
| principle of operation of the actuating element    | momentary contact type  |
| product extension optional                         |   |
| • light source                                     | No  |
| • contact module                                   | Yes   |
| color of the actuating element                     | black   |
| material of the actuating element                  | plastic   |
| shape of the actuating element                     | round   |
| outer diameter of the actuating element            | 29.5 mm   |
| marking of the actuating element                   | Customized labeling, text in lower case / capital letters, all words start with capital letters |
| <b>Front ring</b>                                  |   |
| product component front ring                       | Yes   |
| design of the front ring                           | Standard  |
| material of the front ring                         | Metal, high gloss   |
| color of the front ring                            | silver  |
| <b>General technical data</b>                      |   |
| protection class IP                                | IP66, IP67, IP69(IP69K)   |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13  |
| shock resistance                                   |   |
| • according to IEC 60068-2-27                      | sinusoidal half-wave 15g / 11 ms  |
| • for railway applications according to EN 61373   | Category 1, Class B   |
| vibration resistance                               |   |
| • according to IEC 60068-2-6                       | 10 ... 500 Hz: 5g   |
| • for railway applications according to EN 61373   | Category 1, Class B   |
| operating frequency maximum                        | 3 600 1/h   |
| mechanical service life (operating cycles) typical | 5 000 000   |
| reference code according to IEC 81346-2            | S   |
| Substance Prohibitance (Date)                      | 10/01/2014  |
| <b>Ambient conditions</b>                          |   |
| ambient temperature                                |   |
| • during operation                                 | -25 ... +70 °C  |

|  |  |
|--|--|
| • during storage   | -40 ... +80 °C   |
| environmental category during operation according to IEC 60721 | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| <b>Installation/ mounting/ dimensions</b>                      |  |
| height   | 40 mm  |
| width  | 30 mm  |
| shape of the installation opening                              | round  |
| mounting diameter  | 22.3 mm  |
| positive tolerance of installation diameter                    | 0.4 mm   |
| mounting height  | 32.5 mm  |
| installation width   | 29.5 mm  |
| installation depth   | 30.9 mm  |
| <b>Certificates/ approvals</b>                                 |  |
| <b>Further information</b>                                     |  |

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1250-0FB10-0AA0-Z Y15>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1250-0FB10-0AA0-Z Y15>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1250-0FB10-0AA0-Z Y15>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1250-0FB10-0AA0-Z Y15&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1250-0FB10-0AA0-Z Y15&lang=en)

last modified:

1/26/2022 

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

A6X30143924