## **SIEMENS**

Data sheet 3VA9604-0JJ43



Wire connector TA4.3 4 x 120...240  $\rm mm^2$  for 4 cables 4 units accessories for: 3VA15/25 1000

| Model  |                            |
|--|----------------------------|
| product brand name   | SENTRON                    |
| product designation  | accessories                |
| design of the product  | terminal cover             |
| accessories  | Terminal cover             |
| General technical data   |                            |
| designation / of the terminal  | TA4.3                      |
| type of electrical connection / with control wire tap                          | No                         |
| Connections according IEC  |                            |
| connectable conductor cross-section  |                            |
| <ul> <li>for copper cable / stranded / minimum</li> </ul>                      | 120 mm²                    |
| • for copper cable / stranded / maximum  | 240 mm²                    |
| stripped length  | 23.1 / 44.5 mm             |
| tightening torque / when using copper cables                                   |                            |
| <ul><li>stranded</li></ul>   | 120 - 240 mm²: 36.7 Nm     |
| • finely stranded  | 185 mm²: 36.7 Nm           |
| Connetctions according UL  |                            |
| permissible temperature / of connectable conductor / according to UL 486A-486B | 90 °C                      |
| stripped length  | 0.91 1.75                  |
| connectable conductor cross-section  |                            |
| • for copper cable / stranded / minimum  | 4/0                        |
| • for copper cable / stranded / maximum  | 500                        |
| • for copper cable / finely stranded / minimum                                 | 4/0                        |
| • for copper cable / finely stranded / maximum                                 | 500                        |
| • for aluminum cable / stranded / minimum                                      | 4/0                        |
| • for aluminum cable / stranded / maximum                                      | 500                        |
| tightening torque / when using copper cables                                   |                            |
| • stranded   | 4/0 - 500 kcmil: 325 lb-in |
| • finely stranded  | 4/0 - 500 kcmil: 325 lb-in |

## urther information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9604-0JJ43

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


https://support.industry.siemens.com/cs/ww/en/ps/3VA9604-0JJ43


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3VA9604-0JJ43">http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3VA9604-0JJ43</a>


CAx-Online-Generator http://www.siemens.com/cax

**Tender specifications** 

http://www.siemens.com/specifications









last modified:

7/4/2023

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

3VA96040JJ43