

### product type designation

product description



Figure similar

### PROFIBUS connector

PROFIBUS bus connector, RS 485, screw, with programming port, 35°

SIPLUS DP PROFIBUS plug with R - with PG - inclined based on 6ES7972-0BB42-0XA0 with conformal coating, -40...+70 °C, connection plug for PROFIBUS up to 12 Mbps, with inclined cable outlet, terminating resistor with isolating function, with PG socket

suitability for use

For connecting PROFIBUS stations to the PROFIBUS bus cable

### transfer rate

transfer rate / with PROFIBUS DP

9.6 kbit/s ... 12 Mbit/s

### interfaces

number of electrical connections

- for PROFIBUS cables

2

- for network components or terminal equipment

1

type of electrical connection

- for PROFIBUS cables

Screw

- for network components or terminal equipment

9-pin sub D connector

type of electrical connection / FastConnect

No

### mechanical data

design of terminating resistor

Resistor combination integrated and connectable via slide switch

material / of the enclosure

plastic

locking mechanism design

Screwed joint

### design, dimensions and weights

type of cable outlet

35 degree cable outlet

width

15.8 mm

height

54 mm

depth

39.5 mm

net weight

67 g

### ambient conditions

ambient temperature

- during operation

-40 ... +70 °C

- during storage

-40 ... +70 °C

- during transport

-40 ... +70 °C

- in horizontal mounting position / during operation

70 ... -40 °C

- during storage and transport

70 ... -40 °C

installation altitude / at height above sea level / maximum

5000 m

ambient condition / relating to ambient temperature - air pressure - installation altitude

Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)

relative humidity


- with condensation / maximum

100 %; RH incl. condensation/frost permitted (no commissioning in bedewed state)

- with condensation / according to IEC 60068-2-38 / maximum

100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation

resistance to biologically active substances

<ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> </ul>	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
<ul style="list-style-type: none"> <li>conformity according to EN 60721-3-6</li> </ul>	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
resistance to chemically active substances <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> <li>conformity according to EN 60721-3-6</li> </ul>	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
resistance to mechanically active substances <ul style="list-style-type: none"> <li>conformity according to EN 60721-3-3</li> <li>conformity according to EN 60721-3-6</li> </ul>	Yes; Class 3S4 incl. sand, dust; * Yes; Class 6S3 incl. sand, dust; *
environmental category / according to IEC 60721 / note	* The supplied plug covers must remain in place over the unused interfaces during operation!
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high reliability
type of coating <ul style="list-style-type: none"> <li>protection against pollution according to EN 60664-3</li> <li>for electronic devices in railway applications according to EN 50155</li> </ul>	Yes; Type 1 protection Yes; protective coating of the Class PC2 according to EN 50155:2025
type of test / of the coating / according to MIL-I-46058C	Yes; Discoloration of coating possible during service life
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A
protection class IP	IP20
<b>product features, product functions, product components / general</b>	
product feature <ul style="list-style-type: none"> <li>silicon-free</li> </ul>	Yes
product component <ul style="list-style-type: none"> <li>PG connection socket</li> <li>strain relief</li> </ul>	Yes Yes
<b>standards, specifications, approvals</b>	
certificate of suitability <ul style="list-style-type: none"> <li>RoHS conformity</li> <li>UL approval</li> </ul>	Yes Yes
reference code <ul style="list-style-type: none"> <li>according to IEC 81346-2</li> </ul>	XG
<b>further information / internet links</b>	
internet link <ul style="list-style-type: none"> <li>to web page: selection aid TIA Selection Tool</li> <li>to website: Industrial communication</li> <li>to website: Industry Mall</li> <li>to website: Information and Download Center</li> <li>to website: Selection guide for cables and connectors</li> <li>to website: Image database</li> <li>to website: CAx-Download-Manager</li> <li>to website: Industry Online Support</li> </ul>	<a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="https://sie.ag/2QdlxcP">https://sie.ag/2QdlxcP</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>last modified:</b>	10/15/2022 

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

[6AG19720BB427XA0](#)