## SIEMENS

## Data sheet

## 6GK5004-1BD00-1AB2



SCALANCE XB004-1 unmanaged Industrial Ethernet Switch for 10/100 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 4x 10/100 Mbit/s twisted pair ports with RJ45 sockets; 1 x 100 Mbit/s multimode glass fiber-optic cable port with SC socket; manual available as a download .

product type designation	SCALANCE XB004-1	
transfer rate		
transfer rate	10 Mbit/s, 100 Mbit/s	
interfaces / for communication / maximum configuration for modular devices		
number of electrical ports / maximum	4	
number of optical ports / maximum	1	
interfaces / for communication / integrated		
number of electrical connections		
<ul> <li>for network components or terminal equipment</li> </ul>	4; RJ45	
number of 100 Mbit/s SC ports		
• for multimode	1	
interfaces / other		
number of electrical connections		
<ul> <li>for power supply</li> </ul>	1	
type of electrical connection		
<ul> <li>for power supply</li> </ul>	3-pole terminal block	
supply voltage, current consumption, power loss		
type of voltage / 1 / of the supply voltage	DC	
<ul> <li>supply voltage / 1 / rated value</li> </ul>	24 V	
<ul> <li>power loss [W] / 1 / rated value</li> </ul>	2.64 W	
<ul> <li>supply voltage / 1 / rated value</li> </ul>	19.2 28.8 V	
<ul> <li>consumed current / 1 / maximum</li> </ul>	0.11 A	
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	3-pole terminal block	
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes	
<ul> <li>fuse protection type / 1 / at input for supply voltage</li> </ul>	0.6 A / 60 V	
type of voltage / 2 / of the supply voltage		
<ul> <li>supply voltage / 2 / rated value</li> </ul>	19.2 28.8 V	
ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	-10 +60 °C	
<ul> <li>during storage</li> </ul>	-40 +80 °C	
during transport	-40 +80 °C	
relative humidity		
<ul> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %	
protection class IP	IP20	
design, dimensions and weights		
design	Box	
width	45 mm	
height	100 mm	

	07 mm
depth	87 mm
net weight	0.165 kg
fastening method	
35 mm top hat DIN rail mounting	Yes
• wall mounting	Yes
S7-1500 rail mounting	No
product functions / management, configuration, engineering	
product function	
multiport mirroring	No
• CoS	Yes
PROFINET conformity class	A
product function / switch-managed	No
product functions / redundancy	
product function	
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4
<ul> <li>for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-1
<ul> <li>for emitted interference</li> </ul>	EN 61000-6-4 (Class A)
<ul> <li>for interference immunity</li> </ul>	EN 61000-6-2
MTBF	232 a
reference code	
<ul> <li>according to IEC 81346-2</li> </ul>	KF
<ul> <li>according to IEC 81346-2:2019</li> </ul>	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA
	07ATEX0145 X
certificate of suitability	
<ul> <li>CCC / for hazardous zone according to GB standard</li> </ul>	Yes
<ul> <li>CCC / for hazardous zone according to GB standard / as marking</li> </ul>	Ex nA IIC T4 Gc
standards, specifications, approvals / other	
certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
KC approval	Yes
further information / internet links	
internet link	
to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
to website: Industrial communication	http://www.siemens.com/simatic-net
to website: Industry Mall	https://mall.industry.siemens.com
to website: Information and Download Center	http://www.siemens.com/industry/infocenter
to website: Image database	http://automation.siemens.com/bilddb
to website: CAx-Download-Manager	http://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that
	support the secure operation of plants, solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)
	5/27/2023 C
last modified:	

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens: 6GK50041BD001AB2